

TECHNICAL DATA SHEET

OLD MASTERS® MASTERS ARMOR® PART B HARDENER

AVAILABLE SIZES: Four Ounces (118 mL)

PRODUCT CODES: 72432

PRODUCT DESCRIPTION: Masters Armor® Part B Hardener is an additive for Masters Armor® Water-Based Clear Finish. The Hardener Additive provides maximum protection and durability for high traffic floor areas, bar and table tops. For use with Masters Armor® only.

DIRECTIONS FOR USE: 1. Add 4 ounces per gallon.
2. Mix in slowly.
3. Stir thoroughly.

Pot life is 72 hours once added to Masters Armor Acrylic Finish.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

MAX VOC: MAXIMUM VOC DOES NOT EXCEED 107 g/L when mixed with Part A.

TECHNICAL DATA

SOLIDS BY WEIGHT:	41.3%	FLASH POINT:	>/= 212°F Tag Closed Cup
SOLIDS BY VOLUME:	41.2%	VISCOSITY AT 77 °:	19.65 sec #2 Zahn
V.O.C.:	less than 25 g/L	AVERAGE DRY TIME @ 70°F AND 50% R.H.:	Not applicable
THEORETICAL COVERAGE @ Mil DFT:	Not applicable	VEHICLE:	Water
COVERAGE @ RECOMMENDED DFT	Not applicable	RECOMMENDED THINNER:	Do not thin. Used as packaged.
RECOMMENDED DFT PER COAT:	Not applicable		
WEIGHT PER GALLON:	8.33 lbs/gal		

Limited Warranty Since Old Masters® does not control the application of its products, nor is the condition of the surface to which they are applied, a Limited Warranty provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed the replacement of the product.