



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision date 07-Jul-2025

Version 19

1. Identification

Product identifier

Product Name WS Provincial

Other means of identification

Product Code(s) 11504

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use No information available

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Address

Old Masters
303 19th St. SE
Orange City, IA 51041
Phone: 712-737-4993
Fax: 712-737-4997

Manufacturer Address

Diamond Vogel
1020 Albany Place SE
Orange City, IA 51041
Phone: (712) 737-4993
Fax: (712) 737-4997

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. Hazard(s) identification

Classification

Flammable liquids	Category 3
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration hazard	Category 1

Hazards not otherwise classified (HNOC)

Not applicable

Label elements

**Danger****Hazard statements**

Flammable liquid and vapor.
 May cause an allergic skin reaction.
 May cause genetic defects.
 May cause cancer.
 May damage fertility or the unborn child.
 Causes damage to organs through prolonged or repeated exposure.
 May be fatal if swallowed and enters airways.

Precautionary Statements - Prevention

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Contaminated work clothing must not be allowed out of the workplace.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash face, hands and any exposed skin thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Keep container tightly closed.
 Ground/bond container and receiving equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.
 IF skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 IF SWALLOWED: Immediately call a POISON CENTER or doctor.
 Do NOT induce vomiting.
 In case of fire: Use CO₂, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up.
 Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

Other information

No information available.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Trade secret
---------------	---------	----------	--------------

Soybean oil	8001-22-7	35 to <50	*
Talc (powder)	14807-96-6	20 to <35	*
Solvent Naphtha, Medium Aliphatic	64742-88-7	10 to <20	*
Linseed Oil	8001-26-1	1 to <5	*
Zirconium octoate	22464-99-9	0.1 to <1	*
Mineral Spirits	64742-48-9	0.1 to <1	*
Cobalt 2-ethylhexanoate	136-52-7	0.1 to <1	*
Crystalline Silica	14808-60-7	0.1 to <1	*
Methyl Ethyl Ketoxime	96-29-7	0.1 to <1	*
Ethyl Benzene	100-41-4	0.1 to <1	*
Carbon Black	1333-86-4	0.1 to <1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.
Inhalation	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Ingestion	ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

Symptoms	Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.
Effects of Exposure	May cause cancer. May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility. Mutagenic effects. Causes damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.
---------------------------	--

5. Fire-fighting measures

Suitable Extinguishing Media Large Fire	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam. CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact. WARNING: Spontaneous combustion (fire) may result from materials such as rags, steel wool, paper, clothing, and other waste soaked in linseed oil. Place in a sealed, water filled, metal container to prevent this. WARNING: Spontaneous combustion (fire) may result from materials such as rags, steel wool, paper, clothing, and other waste soaked in soybean oil. Place in a sealed, water filled, metal container to prevent this.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Remove contaminated clothing and shoes.
--------------------------------	---

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection**Control Parameters****Exposure Limits**

The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Talc (powder) 14807-96-6	TWA: 2 mg/m ³ respirable particulate matter containing no Asbestos and <1% Crystalline silica	TWA: 20 mppcf if 1% Quartz or more, use Quartz limit (vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
Zirconium octoate 22464-99-9	STEL: 10 mg/m ³ Zr TWA: 5 mg/m ³ Zr	TWA: 5 mg/m ³ Zr (vacated) TWA: 5 mg/m ³ Zr (vacated) STEL: 10 mg/m ³ Zr	IDLH: 25 mg/m ³ Zr TWA: 5 mg/m ³ except Zirconium tetrachloride Zr STEL: 10 mg/m ³ Zr
Crystalline Silica 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
Ethyl Benzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Carbon Black 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

Biological occupational exposure limits

Chemical name	ACGIH
Ethyl Benzene 100-41-4	150 mg/g creatinine - urine (Sum of mandelic acid and phenylglyoxylic acid) - end of shift

Appropriate engineering controls

Engineering controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Physical state Liquid
Appearance No information available
Color No information available
Odor No information available
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
pH (as aqueous solution)		None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flash point	37.8 °C / 100.0 °F	None known
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	1.12	
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information

Explosive properties No information available

Oxidizing properties	No information available
Softening point	No information available
Molecular weight	No information available
VOC content	No information available
Liquid Density	9.35 lbs/gal
Bulk density	No information available
Percent solids by weight	79.9%
Percent volatile by weight	20.1%
Percent solids by volume	71.3%
Actual VOC (lbs/gal)	1.8
Actual VOC (grams/liter)	220
EPA VOC (lbs/gal)	1.8
EPA VOC (grams/liter)	221

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	None known based on information supplied.
Hazardous decomposition products	None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation.
Skin contact	May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Repeated exposure may cause skin dryness or cracking.
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.
----------	--

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	20,453.59 mg/kg
ATEmix (dermal)	8,480.80 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Talc (powder) 14807-96-6	= 55,000 mg/kg (Rat)	-	-
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 25 mL/kg (Rat)	> 4000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Linseed Oil 8001-26-1	> 15,000 mg/kg	-	-
Zirconium octoate 22464-99-9	> 5000 mg/kg (Rat)	-	-
Mineral Spirits 64742-48-9	> 6000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 8500 mg/m ³ (Rat) 4 h
Cobalt 2-ethylhexanoate 136-52-7	= 1300 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 10 mg/L (Rat) 1 h
Crystalline Silica 14808-60-7	> 22,500 mg/kg (Rat)	-	-
Methyl Ethyl Ketoxime 96-29-7	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat) 4 h
Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
Carbon Black 1333-86-4	> 10000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 4.6 mg/m ³ (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Contains a known or suspected mutagen. Classification based on data available for ingredients. May cause genetic defects.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Talc (powder) 14807-96-6	-	Group 2A	-	X
Cobalt 2-ethylhexanoate 136-52-7	-	Group 2B Group 3	Reasonably Anticipated	X
Crystalline Silica 14808-60-7	A2	Group 1	Known	X
Ethyl Benzene 100-41-4	A3	Group 2B	-	X
Carbon Black 1333-86-4	A3	Group 2B	-	X

Legend**ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity	Classification based on data available for ingredients. May damage fertility or the unborn child.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Target organ effects	Respiratory system, Eyes, Central Vascular System (CVS).
Aspiration hazard	May be fatal if swallowed and enters airways.
Other adverse effects	No information available.
Interactive effects	No information available.

12. Ecological information

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Talc (powder) 14807-96-6	-	100: 96 h Brachydanio rerio g/L LC50 semi-static	-	-
Solvent Naphtha, Medium Aliphatic 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static	-	100: 48 h Daphnia magna mg/L EC50
Mineral Spirits 64742-48-9	-	2200: 96 h Pimephales promelas mg/L LC50	-	-
Methyl Ethyl Ketoxime 96-29-7	83: 72 h Desmodesmus subspicatus mg/L EC50	777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through 760: 96 h Poecilia reticulata mg/L LC50 static	-	750: 48 h Daphnia magna mg/L EC50
Ethyl Benzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas	-	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

		mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static		
--	--	--	--	--

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Methyl Ethyl Ketoxime 96-29-7	0.65
Ethyl Benzene 100-41-4	3.6

Other adverse effects No information available.

13. Disposal considerations

Disposal methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

California Hazardous Waste Status This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

DOT Not regulated

15. Regulatory information

International Inventories

TSCA Complies

*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

DSL/NDSL Complies
EINECS/ELINCS Contact supplier for inventory compliance status.
ENCS Contact supplier for inventory compliance status.
IECSC .
KECL Contact supplier for inventory compliance status.
PICCS Contact supplier for inventory compliance status.
AIIC Contact supplier for inventory compliance status.

NZIoC

Contact supplier for inventory compliance status.

Legend:**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**ENCS** - Japan Existing and New Chemical Substances**IECSC** - China Inventory of Existing Chemical Substances**KECL** - Korean Existing and Evaluated Chemical Substances**PICCS** - Philippines Inventory of Chemicals and Chemical Substances**AICS** - Australian Inventory of Chemical Substances**NZIoC** - New Zealand Inventory of Chemicals**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Cobalt 2-ethylhexanoate - 136-52-7	0.1
Ethyl Benzene - 100-41-4	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethyl Benzene 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Ethyl Benzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65
Crystalline Silica - 14808-60-7	Carcinogen
Ethyl Benzene - 100-41-4	Carcinogen
Carbon Black - 1333-86-4	Carcinogen
Naphthalene - 91-20-3	Carcinogen
Benzene(including benzene from gasoline) - 71-43-2	Carcinogen Developmental Male Reproductive
Toluene - 108-88-3	Developmental
Cumene - 98-82-8	Carcinogen
Propylene oxide - 75-56-9	Carcinogen
3,3'-Dichlorobenzidine - 91-94-1	Carcinogen
Ethylene Glycol - 107-21-1	Developmental

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Soybean oil 8001-22-7	-	-	X
Talc (powder) 14807-96-6	X	X	X
Linseed Oil 8001-26-1	-	-	X
Red Iron Oxide 1332-37-2	-	X	-
Xylene 1330-20-7	X	X	X
1,2,4-Trimethylbenzene 95-63-6	X	X	X
Cobalt 2-ethylhexanoate 136-52-7	X	-	X
Crystalline Silica 14808-60-7	X	X	X
Magnesium carbonate 546-93-0	X	X	-
Trimanganese tetraoxide 1317-35-7	X	X	X
Ethyl Benzene 100-41-4	X	X	X
Carbon Black 1333-86-4	X	X	X
Diethylene Glycol Methyl Ether 111-77-3	X	X	X
Aluminum oxide 1344-28-1	X	X	X
Nonane 111-84-2	X	X	X
Stoddard Solvent 8052-41-3	X	X	X
Propylene Glycol Methyl Ether 107-98-2	X	X	X
Diethylene Glycol Butyl Ether 112-34-5	X	-	X
Propionic Acid 79-09-4	X	X	X
2-Ethylhexanoic acid 149-57-5	X	-	-
Naphthalene 91-20-3	X	X	X
Benzene(including benzene from gasoline) 71-43-2	X	X	X
Toluene 108-88-3	X	X	X
Cumene 98-82-8	X	X	X
Propylene oxide 75-56-9	X	X	X
3,3'-Dichlorobenzidine 91-94-1	X	X	X
Ethylene Glycol 107-21-1	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present if listed in Section 3):

Chemical name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Cobalt 2-ethylhexanoate 136-52-7	0.38	0.04
Ethyl Benzene 100-41-4	0.13	0.01

16. Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitizers		

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
 U.S. Environmental Protection Agency ChemView Database
 European Food Safety Authority (EFSA)
 Environmental Protection Agency
 Acute Exposure Guideline Level(s) (AELG(s))
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
 U.S. Environmental Protection Agency High Production Volume Chemicals
 Food Research Journal
 Hazardous Substance Database
 International Uniform Chemical Information Database (IUCLID)
 National Institute of Technology and Evaluation (NITE)
 Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
 NIOSH (National Institute for Occupational Safety and Health)
 National Library of Medicine's ChemID Plus (NLM CIP)
 National Library of Medicine's PubMed database (NLM PUBMED)
 U.S. National Toxicology Program (NTP)
 New Zealand's Chemical Classification and Information Database (CCID)
 Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
 Organization for Economic Co-operation and Development High Production Volume Chemicals Program
 Organization for Economic Co-operation and Development Screening Information Data Set
 World Health Organization

Revision date 07-Jul-2025

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet