

**OLYMPIC MAXIMUM® Clear Waterproofing Sealant****GENERAL DESCRIPTION**

OLYMPIC MAXIMUM Clear Sealant provides exceptional protection for wood. Its unique, penetrating formula enhances the natural look of wood while it strengthens, protects, and conditions wood fibers. Recommended for use on exterior wood decks, fences, siding, railings, outdoor furniture and other wood surfaces. Apply to new, dry, pressure-treated wood, uncoated new or weathered wood, or previously coated wood with a weathered, clear sealant or semi-transparent stain.

**RECOMMENDED SUBSTRATES**

Wood	Siding
Pressure-treated wood	Railings
Decks	Plywood
Fences	Outdoor Furniture

**FEATURES / BENEFITS**

Penetrating Formula for Strong Protection  
Advanced *SunBlock*® U.V. Protection  
Exclusive *Scuff Guard*® Formula  
Provides a Mildew Resistant Coating  
Enhanced Waterproofing Protection  
Easy Water Cleanup  
*Weather-Ready*™ Application – Clean and stain on the same day even after rain, mist and apply on hot sunny days, rain-ready in 8 hours, and apply down to 35°F

**LIMITATIONS OF USE**

Apply when no precipitation is expected for 8 hours, and when air and surface temperatures are 35°F to below 120°F (2°C to 49°C) and will remain above 35°F (2°C) for the next 24 hours. If the surface is too hot to touch, lightly mist the surface using a garden hose to cool the surface before application of the stain. Caution: Avoid direct skin contact with hot surfaces. Avoid staining in direct sunlight.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

Not recommended for recently painted or sealed surfaces. Do not use on plastic, rubber, asphalt, tile, vinyl, concrete or any non-porous surface.

FOR EXTERIOR USE ONLY. PROTECT FROM FREEZING.

**PRODUCT INFORMATION**

56500 Clear Waterproofing Sealant

DO NOT TINT.

**PRODUCT DATA**

<b>PRODUCT TYPE:</b>	Acrylic/Oil Resin
<b>VOLUME SOLIDS:</b>	17% +/- 2%
<b>WEIGHT SOLIDS:</b>	19% +/- 2%
<b>VOC:</b>	<100 g/L (0.83 lbs./gal.)
<b>WEIGHT/GALLON:</b>	8.4 lbs. (3.8 kg) +/- 0.2 lbs. (91 g)

**COVERAGE:** Approximately 250 to 350 sq. ft. (23.2 to 32.5 sq. meters) per gallon (3.78 L) depending upon wood texture. One coat application is recommended.

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

**DRYING TIME:** Normally dries in 24 hours when applied in optimal temperatures of 50°F (10°C) to 90°F (32°C). Application in high humidity or in temperatures below 50°F (10°C) may prolong drying time. Allow 24 to 48 hours of drying time before light foot traffic and 72 hours before normal foot traffic or replacing furniture. Allow new stain to cure 30 days before washing.

**CLEANUP:** Clean brushes and tools with warm soapy water.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT:** Over 200°F (93°C)

**PACKAGING**

5-Gallon (18.9 L)  
1-Gallon (3.78 L)  
Quart (946 mL)

## OLYMPIC MAXIMUM Waterproofing Sealant Clear

### GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the *OLYMPIC* limited warranty to apply. Surface must be clean. Remove all dust, dirt, mildew, oil, loose wood fibers and other contaminants. Previous coatings must be completely removed. To ensure proper adhesion, weathered, dirty or mildewed surfaces should be cleaned with *OLYMPIC* Deck Cleaner prior to applying stain. After rinsing, ensure surface is free of standing water. Remove grade stamps or pencil marks by sanding.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**FENCES, SIDING OR DECKS:** Clean weathered, dirty or mildewed surfaces with *OLYMPIC* Deck Cleaner prior to applying product. Before use, be sure to read and follow the instructions and warnings on the label.

**PRETEST:** Test a small hidden area prior to application to ensure acceptable appearance and penetration.

**EXTRACTIVE BLEEDING:** Some woods, such as redwood and cedar contain natural water-soluble colorings or extractives that tend to “bleed” or migrate to the surface. If extractive bleeding occurs, allow the coating to dry completely, then wash with a mild detergent solution and rinse with clear water.

### APPLICATION INFORMATION

Stir thoroughly before and often during use.

**Pretest:** Apply to a small area and allow to dry to ensure applicable appearance and penetration. For previously coated wood: If the product is not absorbed into the surface and is still tacky after 12 hours, the surface is not suitable for a waterproofing sealant. For damp wood: If wood is too damp to allow penetration, allow to dry further and retest for penetration.

**Application Method:** Apply one thin coat. To help avoid lapmarks, apply to only a few boards at a time keeping a wet edge. Do not saturate or puddle on horizontal surfaces.

**Application Equipment:** Apply with a high quality brush, paint / stain pad or by spray equipment. When spraying, always back brush for best results. To help avoid lap marks, apply to only a few boards at a time, and maintain a wet edge.

**Thinning:** DO NOT THIN.

### PRECAUTIONS

**DANGER! HARMFUL OR FATAL IF SWALLOWED.** Can enter lungs and cause damage. Do not breathe vapor or mist. Do not swallow. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *Olympic*, *Olympic & Design*, *MAXIMUM*, *Scuff Guard*, and *SunBlock* are registered trademarks and *Weather-Ready* is a trademark of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



Olympic - US  
PPG Industries, Inc.  
Architectural Coatings  
One PPG Place  
Pittsburgh, PA 15272  
[www.olympic.com](http://www.olympic.com)

Technical Services  
1-800-426-6306

Architect/Specifier  
1-888-PPG-IDEA

Olympic - Canada  
PPG Architectural Coatings Canada Inc.  
2505, rue de la Métropole,  
Longueuil (Québec) Canada J4G 1E5

T.D. 56500 2/2016