



OLYMPIC®

58800 Series

## OLYMPIC Deck, Fence, Siding Semi-Transparent Stain

### GENERAL DESCRIPTION

OLYMPIC Deck, Fence & Siding Semi-Transparent Stain provides a beautiful, subtle color that allows wood's natural grain and texture to show through. Our hybrid resin technology penetrates deep into your wood to strengthen, protect, and condition wood fibers, ensuring the natural beauty of your wood lasts.

Recommended for use on exterior wood decks, fences, siding, railings, outdoor furniture and other wood surfaces. May be used on new wood, pressure-treated wood, weathered wood, and wood previously coated with a solvent-based clear or semi-transparent stain.

### RECOMMENDED USES

Pressure-treated wood  
Weathered wood  
Wood decks  
Wood siding

### FEATURES / BENEFITS

Durable Acrylic/Oil Formula  
WaterGuard® Waterproofing Protection

### APPLICATION INFORMATION

Stir thoroughly and often during use. When using more than one can of the same color, intermix to ensure color uniformity.

**Pretest:** Test a small hidden area prior to application to ensure acceptable appearance and penetration. Apply one small area before treating the entire surface. If the product is not absorbed into the surface and is still tacky after 12 hours, the surface is not suitable for a waterproofing sealant.

**Application Equipment:** Apply with a high quality brush, roller, paint pad, or by spray equipment.

**Application Method:** Apply a thin coat. To help avoid lapmarks, apply to only a few boards at a time keeping a wet edge. When spraying or rolling, always backbrush for best results.

**Thinning:** Do not thin.

### PRODUCT INFORMATION

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

58800	Neutral Base*
58803	Clove Brown
58804	Cedar Naturaltone
58805	Redwood Naturaltone
58806	Brick Red

\*Must be tinted before use.

Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

### PRODUCT DATA

<b>PRODUCT TYPE:</b>	Hybrid Resin Technology
<b>VOLUME SOLIDS*:</b>	20% +/- 2%
<b>WEIGHT SOLIDS*:</b>	20% +/- 2%
<b>VOC*:</b>	<100 g/L (0.8 lbs./gal.)
<b>WEIGHT/GALLON*:</b>	8.4 lbs. (3.8 kg) +/- 0.2 lbs. (91 g)
<b>FLASH POINT:</b>	Over 200°F (93°C)

\*Product data calculated on 58800.

**COVERAGE:** Approximately 250 to 350 sq. ft. (23.2 to 32.5 sq. meters) per gallon (3.78 Liters) depending upon wood texture.

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

**DRYING TIME:** Normally dries in 24 hours when applied in temperatures of 50°F (10°C) to 85°F (29°C). High humidity or low temperature application may prolong drying time. It is not recommended to apply product if rain is expected within 24 hours.

Drying times listed may vary depending on temperature, humidity, color and air movement.

**CLEAN UP:** Clean brushes and tools with warm soapy water.

**DANGER:** Rags, steel wool or waste soaked with OLYMPIC Deck, Fence, and Siding Semi-Transparent Stain may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool or waste in a sealed water-filled container.

## OLYMPIC Deck, Fence, Siding Semi-Transparent Stain

### GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the *OLYMPIC* limited warranty to apply. All surfaces must be clean and free of dirt, dust, oil, mildew, and other contaminants. Remove grade stamps, pencil marks, etc. by sanding.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**DECKS:** Clean weathered, dirty or mildewed surfaces with *OLYMPIC* Deck Cleaner prior to applying product.

**FENCES OR SIDING:** Remove and inhibit mildew with *OLYMPIC* Mildew Check® Multi-Purpose Wash. Before use, be sure to read and follow the instructions and warnings on the label.

**PRETEST:** Test a small hidden area prior to application to ensure acceptable appearance and penetration.

**EXTRACTIVE BLEEDING:** Some woods, such as redwood and cedar contain natural water-soluble colorings or extractives that tend to "bleed" or migrate to the surface. If extractive bleeding occurs, allow the coating to dry completely, then wash with a mild detergent solution and rinse with clear water.

### LIMITATIONS OF USE

Apply when air and surface temperatures are 35°F (2°C) or above and when the air and surface temperatures will remain above 35°F (2°C) for the next 24 hours. Avoid staining in direct sunlight or on hot surfaces. **FOR EXTERIOR USE ONLY.** Do not use on metallic, masonry, or interior surfaces.

#### PROTECT FROM FREEZING.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

### SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

**USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.**

### PACKAGING

1-Gallon (3.78 L)

5-Gallon (18.9 L)

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *OLYMPIC*, *OLYMPIC* design, *WaterGuard*, and *OLYMPIC MILDEW CHECK* are registered trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



Olympic - US  
PPG Architectural Finishes, Inc.  
One PPG Place  
Pittsburgh, PA 15272  
[www.olympic.com](http://www.olympic.com)

Technical Services  
1-800-426-6306

Architect/Specifier  
1-888-PPG-IDEA

Olympic - Canada  
PPG Canada, Inc.  
4 Kenview Blvd  
Brampton, ON L6T 5E4

T.D. 58800 2/2013  
(Supersedes 10/2007)