A44

SINGLE DEVICE HANDY BOXES & EXTENSION RINGS

4 in. x 2 in. Handy Boxes, 1-7/8 in. Deep - Drawn with Conduit KO's Raised Ground



Catalog #: 8660

APPLICATIONS

RACO® Handy boxes, also called utility boxes, are used for convenience outlets, switch boxes or small junction boxes They are popular for exposed work applications (surface mounted wiring) The NEC requires that surface-mounted wiring be enclosed with a protective covering such as EMT conduit

PRODUCT FEATURES

N/A

UL LISTED

File E195978

COMPLIANCES

All RACO® single gang, two gang, 4 in. square, and single gang gangable UL listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult UL "Fire Resistance Directory" or the UL website at www.ul.com

FIRE RESISTANCE

Acceptable for use in 2-hour rated walls

GENERAL PRODUCT INFORMATION

GENERAL PRODUCT INFORMATION Wiring System: Country of Origin:	Conduit USA
CONFIGURATION End Knockouts: Bracket Type: Drawn or Welded: Raised Ground: Side Knockout(s): Bottom Knockouts(s):	(2) 1/2 in. No Bracket Drawn Yes (6) 1/2 in. (2) 1/2 in.
DRAWING DIMENSIONS Dimension A:	1-7/8 in.
PRODUCT MEASUREMENTS Depth: Cubic Inches (cm3): Wt. Ea. (Lbs.): Product Length (in.): Product Width (in.): Product Height (in.):	1-7/8 in. 13.0 (213.0) 0.484 1.94 4.00 2.13
PACKAGING Minimum Pack Qty.: Std. Pkg.: Product UPC-A Labeled: Weight (Lbs. Per/C): Ship Carton Length (in.): Ship Carton Width (in.): Ship Carton Height (in.): Ctn Weight (Lbs.): Pallet Qty: UPC Number:	50 50 Yes 48.40 11.13 8.50 10.00 24.20 4000 050169006603



50050169006608