

**Architectural Coatings**
**PITTSBURGH® Paints Premium Ceiling White Interior Flat Latex**
**Generic Type**

Vinyl Acrylic Latex

**Tinting and Base Information**

Refer to THE VOICE OF COLOR® formula book for tinting instructions.

17-45

Bright White

**General Description**

Our premium ceiling paint is designed to meet the performance requirements of the residential and commercial markets. PITTSBURGH® Paints Premium Ceiling Paint is high hiding and spatter resistant. The bright white, flat latex provides a beautiful, premium finish to interior ceilings. Recommended on properly prepared and primed ceilings made of wallboard, cured plaster, wood and masonry.

**Recommended Uses**

Drywall	Interior Ceilings
Masonry	Plaster
Wood	

**Features / Benefits**

- True Flat Finish
- Excellent Hide
- Spatter Resistant
- Easy cleanup with soap and water
- Can earn LEED NC Version 2.2. Credits

**Limitations of Use**

Apply when air, surface and product temperatures are above 50°F (10°C). PROTECT FROM FREEZING. Not recommended for use on floors. Not intended for use on walls. Drying times listed may vary depending on temperature, humidity, color and air movement.

**Product Data**

<b>Gloss:</b>	Flat: 0 to 3 (85° Gloss Meter)
<b>VOC*:</b>	0.23 lbs/gal (28.00 g/L)
<b>DFT:</b>	1.00 minimum to 1.20 maximum mils
<b>Coverage:</b>	400 to 500 sq. ft./gal. (37 to 46 sq. m/3.78L)

Note: Does not include loss due to varying application method, surface porosity, or mixing.

<b>Volume Solids*:</b>	32% +/- 2.0%
<b>Weight Solids*:</b>	51% +/- 2.0%
<b>Viscosity:</b>	88 to 98 KU
<b>Weight/Gallon*:</b>	11.7 lbs. (5.3 kg) +/- 0.2 lbs. (91 g)

**Cleanup:** Soap and Water

\*Product data calculated on product 17-45.

**Drying Time:**

To Touch:	30 minutes
To Handle:	1 hour
To Recoat:	4 hours
To Full Cure:	30 days

**Dry Time @77°F (25°C); 50% relative humidity**

**Flash Point:** Over 200°F, (93°C)

## Architectural Coatings

## PITTSBURGH® Paints Premium Ceiling White Interior Flat Latex

## General Surface Preparation

Surface to be painted must be clean, dry, smooth, and free from dirt, grease, powdery or peeling paint, and other surface contaminants. All cracks and other surface imperfections must be repaired using high quality patching compounds, then allowed to dry thoroughly. Repaired areas should be sanded smooth and then spot-primed. Slick or glossy surfaces of previously applied paint, in sound condition, must be dulled by sanding. Prime all bare wood, plaster, masonry, metal, patched and porous surfaces with the appropriate primer. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**NEW WOOD:** New wood should be sanded smooth and wiped clean. Any knots or resinous areas should be sealed before painting. Countersink all nails. Putty flush with surface, then prime.

**NEW PLASTER:** Fresh plaster, hardcoat, skim coat, or other alkaline surfaces should be allowed to cure for at least 30 days prior to priming with an alkali resistant primer.

**WATER-SOLUBLE STAINS:** Apply SEAL-GRIP® Primer 17-921 or 17-931, over stained area prior to coating, to avoid bleeding of the stain into the topcoat.

## Recommended Primers

Wood	17-921, 17-955, 17-956
Gypsum Wallboard-Drywall	6-2, 17-921, 9-900
Plaster	4-603

## Directions for Use

Stir thoroughly before using and occasionally when in use. When using more than one can of the same color, mix together (box) before applying. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.** Read all label and Material Safety Data Sheet (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-441-9695.

## Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	50 to 100°F	10 to 38°C
Substrate:	50 to 100°F	10 to 38°C

## Application Information

## Recommended Spread Rates:

Wet Mills :	3.2 minimum to	4.0 maximum
Wet Microns:	81.2 minimum to	101.6 maximum
Dry Mills :	1.0 minimum to	1.2 maximum
Dry Microns:	20.5 minimum to	30.4 maximum

**Application Equipment:** Apply with a high quality brush, roller, paint pad, or by spray equipment. Where necessary, apply a second coat. Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

**Airless Spray: Pressure 2000 psi, tip 0.015" - 0.021"**

**Brush: Polyester/Nylon Brush**

**Roller: 3/8" - 3/4" nap roller cover.**

## Thinning:

No thinning is usually required. If necessary add up to 1/4 pint (118 mL) of water per gallon (3.78 L) of paint.

**Packaging: 1-Gallon (3.78L)  
5-Gallon (18.9L)**

Not all products are available in all sizes.

PPGAF believes the technical data presented is currently accurate: however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Industries, Inc.  
Architectural Coatings  
One PPG Place  
Pittsburgh, PA 15272  
[www.pittsburghpaints.com](http://www.pittsburghpaints.com)

Technical Services  
1-800-441-9695  
1-888-807-5123 fax

Architect/Specifier  
1-888-PPG-IDEA

PPG Architectural Finishes  
400 S. 13th Street  
Louisville, KY 40203

PPG Canada, Inc.  
Architectural Coatings  
4 Kenview Blvd  
Brampton, ON L6T 5E4

A2.15 5/2007