SAFETY DATA SHEET



Date of issue/Date of revision12 December 2018Version 13

Section 1. Identification			
Product name	: 6-517 SPEEDHIDE ENAMEL LATEX INTERIOR SEMI-GLOSS-NEUTRAL BASE		
Product code	: 00401310		
Other means of identification	: Not available.		
Product type	: Liquid.		
Relevant identified uses of the substance or mixture and uses advised against			
Product use	: Consumer applications, Professional applications.		
Use of the substance/ mixture	: Coating.		
Uses advised against	: Not applicable.		
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272		
<u>Emergency telephone</u> <u>number</u>	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 or + 52 55 5559 1588 (Mexico)		
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)		

Section 2. Hazards identification

OSHA/HCS status	: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	: Not classified.
	Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 6.1% (Oral), 12.5% (Dermal), 24.7% (Inhalation)
GHS label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Not applicable.

Date of issue 12 December 2018 Version 13

Product name 6-517 SPEEDHIDE ENAMEL LATEX INTERIOR SEMI-GLOSS-NEUTRAL BASE

Section 2. Hazards identification

Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable.
Supplemental label elements	 Contains isothiazolinones. May cause allergic reaction. Sanding and grinding dusts may be harmful if inhaled. Emits toxic fumes when heated.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: 6-517 SPEEDHIDE ENAMEL LATEX INTERIOR SEMI-GLOSS-NEUTRAL BASE

Ingredient name	%	CAS number	
Kaolin	≥5.0 - ≤10	1332-58-7	

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	-	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	1	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	1	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact :	No known significant effects or critical hazards.
Inhalation :	No known significant effects or critical hazards.
Skin contact :	No known significant effects or critical hazards.
Ingestion :	No known significant effects or critical hazards.
Over-exposure signs/symptom	IS

United States Page: 2/11

Product name 6-517 SPEEDHIDE ENAMEL LATEX INTERIOR SEMI-GLOSS-NEUTRAL BASE

Section 4. First aid measures

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary			
Notes to physician	eat symptomatically. Contact poison treatment sp antities have been ingested or inhaled.	ecialist immediately if large	
Specific treatments	specific treatment.		
Protection of first-aiders	action shall be taken involving any personal risk	or without suitable training.	

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Product name 6-517 SPEEDHIDE ENAMEL LATEX INTERIOR SEMI-GLOSS-NEUTRAL BASE

Section 6. Accidental release measures

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up
if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and
place in an appropriate waste disposal container. Dispose of via a licensed waste
disposal contractor.Large spill: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers,

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	
Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Special precautions	: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

<u>Control parameters</u> <u>Occupational exposure limits</u>

Product name 6-517 SPEEDHIDE ENAMEL LATEX INTERIOR SEMI-GLOSS-NEUTRAL BASE

Section 8. Exposure controls/personal protection

Ingre	dient name	Exposure limits
Kaolir	ז	ACGIH TLV (United States, 3/2018). TWA: 2 mg/m ³ 8 hours. Form: Respirable fraction OSHA PEL (United States, 5/2018). TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction TWA: 15 mg/m ³ 8 hours. Form: Total dust
A ACGIH C	Key to abbreviations = Acceptable Maximum Peak = American Conference of Governmental Industrial Hygienists. = Ceiling Limit	S = Potential skin absorption SR = Respiratory sensitization SS = Skin sensitization
F	= Fume	STEL = Short term Exposure limit values

TD

TLV

TWA

= Total dust

= Threshold Limit Value

= Time Weighted Average

IPEL = Internal Permissible Exposure Limit

OSHA = Occupational Safety and Health Administration.

R = Respirable

Z = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	es	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection <u>Skin protection</u>	:	Safety glasses with side shields.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue 12 December 2018 Version 13

Product name 6-517 SPEEDHIDE ENAMEL LATEX INTERIOR SEMI-GLOSS-NEUTRAL BASE

Section 8. Exposure controls/personal protection

Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Various
Odor	: Characteristic.
Odor threshold	: Not available.
рН	: 8.6
Melting point	: Not available.
Boiling point	: 100°C (212°F)
Flash point	: Closed cup: Not applicable. [Product does not sustain combustion.]
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Evaporation rate	: 0.05 (butyl acetate = 1)
Vapor pressure	: 3.3 kPa (25 mm Hg) [room temperature]
Vapor density	Not available.
Relative density	: 1.06
Density(lbs / gal)	: 8.85
Solubility	: Soluble in the following materials: cold water.
Partition coefficient: n- octanol/water	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)
Volatility	: 76% (v/v), 71.394% (w/w)
% Solid. (w/w)	: 28.606

Section 10. Stability and reactivity

	United States Page: 6/11
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	: The product is stable.
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.

Date of issue 12 December 2018 Version 13

Product name 6-517 SPEEDHIDE ENAMEL LATEX INTERIOR SEMI-GLOSS-NEUTRAL BASE

Section 10. Stability and reactivity

Refer to protective measures listed in sections 7 and 8.

Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	:	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Kaolin	LD50 Oral	Rat	>5000 mg/kg	-
Conclusion/Summary	: There are no data avai	lable on the mixture itse	elf.	
Irritation/Corrosion				
Conclusion/Summary				
Skin	: There are no data avai	lable on the mixture itse	elf.	
Eyes	: There are no data avai	lable on the mixture itse	elf.	
Respiratory	: There are no data avai	lable on the mixture itse	elf.	
Sensitization				
<u>Conclusion/Summary</u>				
Skin	: There are no data avai	lable on the mixture itse	elf.	
Respiratory	: There are no data avai	lable on the mixture itse	elf.	
Mutagenicity				
Conclusion/Summary	: There are no data avai	lable on the mixture itse	elf.	
Carcinogenicity				
Conclusion/Summary	: There are no data avai	lable on the mixture itse	elf.	
Reproductive toxicity				
Conclusion/Summary	: There are no data availa	able on the mixture itse	lf.	
Feratogenicity				
Conclusion/Summary	: There are no data availa	able on the mixture itse	lf.	
Specific target organ toxici				
Not available.	<u></u>			
<u>Specific target organ toxici</u>	ty (repeated exposure)			
Not available.				
<u>Farget organs</u>	: Contains material which Contains material which respiratory tract, stomad	n may cause damage to		

Aspiration hazard

Not available.

Product name 6-517 SPEEDHIDE ENAMEL LATEX INTERIOR SEMI-GLOSS-NEUTRAL BASE

Section 11. Toxicological information

		-	
Information on the likely rou	tes	of exposure	
Potential acute health effec	<u>ts</u>		
Eye contact	:	No known significant effects or critical h	azards.
Inhalation	:	No known significant effects or critical h	azards.
Skin contact	:	No known significant effects or critical h	azards.
Ingestion	1	No known significant effects or critical h	azards.
Over-exposure signs/symp	<u>tom</u>	<u>IS</u>	
Eye contact	1	No specific data.	
Inhalation	1	No specific data.	
Skin contact	1	No specific data.	
Ingestion	1	No specific data.	
Delayed and immediate effect	<u>:ts a</u>	and also chronic effects from short ar	<u>id long term exposure</u>
Conclusion/Summary	:	cause irritation and reversible damage. vomiting. This takes into account, when	ure itself. If splashed in the eyes, the liquid may Ingestion may cause nausea, diarrhea and e known, delayed and immediate effects and n short-term and long-term exposure by oral, re and eye contact.
<u>Short term exposure</u>			,
Potential immediate effects	:	There are no data available on the mixto	ure itself.
Potential delayed effects		There are no data available on the mixto	ure itself.
Long term exposure			
Potential immediate effects	:	There are no data available on the mixte	ure itself.
Potential delayed effects	1	There are no data available on the mixtu	ure itself.
Potential chronic health effe	<u>ects</u>		
General	1	No known significant effects or critical h	azards.
Carcinogenicity	:	No known significant effects or critical h	azards.
Mutagenicity	1	No known significant effects or critical h	azards.
Teratogenicity	1	No known significant effects or critical h	azards.
Developmental effects	1	No known significant effects or critical h	azards.
Fertility effects	1	No known significant effects or critical h	azards.
Numerical measures of toxic	<u>:ity</u>		
Acute toxicity estimates			
Route			ATE value
Oral			166933.3 mg/kg

Product name 6-517 SPEEDHIDE ENAMEL LATEX INTERIOR SEMI-GLOSS-NEUTRAL BASE

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewere
	sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information DOT IMDG ΙΑΤΑ **UN number** Not regulated. Not regulated. Not regulated. **UN proper shipping** _ name **Transport hazard class** _ (es) Packing group **Environmental hazards** No. No. No. Not applicable. Not applicable. Not applicable. Marine pollutant substances

		United States	Page: 9/11
--	--	---------------	------------

Date of issue 12 December 2018 Version 13

Product name 6-517 SPEEDHIDE ENAMEL LATEX INTERIOR SEMI-GLOSS-NEUTRAL BASE

14. Transport information

Additional information

- **DOT** : None identified.
- **IMDG** : None identified.
- IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are listed or exempted.

United States - TSCA 5(a)2 - Final significant new use rules: Øs(2-(2-methoxyethoxy)ethyl) ether	Listed	
United States - TSCA 5(a)2 - Proposed significant new use rules: 5-chloro-2-methyl-2H-isothiazol-3-one	Listed	P-96-1251
<u>SARA 302/304</u>		
SARA 304 RQ : Not applicable.		
Composition/information on ingredients		
No products were found.		
SARA 311/312		

Classification : Not applicable.

Composition/information on ingredients

No products were found.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health: 3 Flammability: 0 Physical hazards: 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health:3Flammability:0Instability:0Date of previous issue:11/6/2018

United States Page: 10/11

Product name 6-517 SPEEDHIDE ENAMEL LATEX INTERIOR SEMI-GLOSS-NEUTRAL BASE

Section 16. Other information

Organization that prepared the MSDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.