

POWER TECH®

3ft 12/3 SJTW GFCI Adapters



Power Tech® GFCI Adapters offer extra shock protection by incorporating GFCI units rated at 20A instead the standard 15A units commonly found in the market. Our patented solid state GFCI unit provides protection from electrical shock by interrupting the circuit to a load when a fault current of 6mA or higher is detected. It offers neutral protection, ground neutral protection, and built in surge protection for cords, power tools, small appliances, electronics, and more when they are plugged into the GFCI adapter.

FEATURES

- Our GFCI Adapter acts as an interface between a regular non-GFCI extension cord and the power source when ground fault protection is needed at the jobsite.
- The GFCI has a manual reset feature that ensures that equipment won't have accidental restarts without fixing the issue, providing additional protection for you, your tools and your equipment.
- Class A GFCI unit with a 4-6mA trip level
- Power On indicator (Red means on)
- Cords are manufactured to 12/3 AWG (American Wire Gauge) specifications
- Each of the three conductors contain 65 strands of 30 AWG 100% copper wire
- All copper is soft drawn & annealed for maximum flexibility under full load
- Our Century® coldweather PVC insulation and jacket guarantees working flexibility in temperatures down to -40°F
- SJTW outside jacket is rated at 300 volts
- We use heavy duty molded on 15A-125V NEMA 5-15 plugs & connectors that will not to pull away from the cord body
- Cord Jacket color: Yellow
- Length: 3 feet
- Surge Suppression: 13 Joules
- UL Listed and CSA Approved for Canada

WARNING: ⚠️ This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number
D18020003

Length
3'

Description
12/3 SJTW Triple Tap Adapter with Inline GFCI

Product line
Power Tech® GFCI Extension Cord

Color
Yellow

Gauge/Conductors
12/3

Wire type
SJTW

Certifications
CSA, UL, OSHA

Electrical ratings
15A, 125V, 1875W

Product packaging
Cuff wrapper

Unit dimensions D x W x H (inches)
9.0 x 9.0 x 2.0

Unit weight (lbs)
1.4

Master carton type
Plain corrugated

Master carton dimensions D x W x H
23.0 x 19.0 x 9.0

Master carton weight (lbs)
52

Master carton case quantity
36

Master carton cube (cu. ft.)
2.3

UPC
661899 116076

**Custom Print Available,
Absolutely Free!
Allow 7 Extra Days For
Delivery.**

We'll print your customer's name and telephone number every 12 inches down the entire length of the cord. Printed cords discourage jobsite theft and provide instant advertising and company recognition which will promote more business.