



**PROFESSIONAL MEGA MARKING PAINT  
QUARTER MILE DISTANCE SPRAYS**

**DESCRIPTION AND USES**

Rust-Oleum® Professional Mega Marking Paint Quarter Mile Distance Sprays are an aerosol coating packaged for use in an inverted position as a marking paint. Use for marking construction and excavation sites, underground utilities and for traffic safety. This product is not water soluble and withstands general weathering. These sprays are recommended for use with Rust-Oleum® #2393000 Marking Wand and feature fast dry and adhesion to concrete, blacktop, gravel, soil and grass.

**PRODUCTS**

SKU	DESCRIPTION
350994	Fluorescent Red-Orange
350997	White

**NOTE:** Flat to semi-gloss finish (dependent on surface porosity)

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Remove excessive loose debris from the surface before application of the coating.

**PAINTING CONDITIONS**

Use when temperature is 40-90°F (4-32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Protect surrounding surfaces from overspray. Overspray can carry a significant distance.

**PRODUCT APPLICATION (cont.)**

**APPLICATION**

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle **DO NOT STRIKE CAN**. Contact Rust-Oleum. Shake often during use. Hold can upright 6-8" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart. **Do not use near open flame.**

**DRY & RECOAT**

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 15 minutes and is fully dry in 8 hours.

**CLEAN-UP**

When finished spraying, clear spray valve by turning can upright and pushing spray button for 2-3 seconds. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

**CLOGGING**

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve

	<b>TECHNICAL DATA</b>	<b>PRO-17</b>
	<b>PROFESSIONAL MEGA MARKING PAINT QUARTER MILE DISTANCE SPRAYS</b>	

**PHYSICAL PROPERTIES**

		MEGA MARKING PAINT QUARTER MILE DISTANCE SPRAYS
<b>Resin Type</b>		Modified Alkyd
<b>Pigment Type</b>		Varies with color
<b>Solvents</b>		Acetone, Aliphatic Hydrocarbons
<b>Fill Weight</b>		15 ounces
<b>MIR</b>		0.85 max
<b>Practical Coverage at Recommended DFT (assumes 15% material loss)</b>		Up to one quarter mile, 1320 linear feet (402 meters) at 1.5 in. wide (3.8 cm) Depending on surface porosity
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	<b>Touch</b>	15 minutes
	<b>Fully Dry</b>	8 hours
<b>Shelf Life</b>		5 years
<b>Flash Point</b>		-156°F (-104°C)
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.