

Low Dust / Mold Protection Ready Mix Joint Compounds



PROFORM[®]
BRAND
Interior Finishing Products

National 
Gypsum[®]

Low Dust / Mold Protection Ready Mix Joint Compounds

Description

Dust management has never been more crucial on jobsites. ProForm® BRAND XP® and ProForm® BRAND XP® Lite with Dust-Tech® are specifically formulated to reduce airborne dust by up to 60%, thereby reducing the impact on indoor air quality. Less dust also saves time with quick and easier clean-up. Both offer superior mold resistance by achieving the highest mold-resistant scores on industry tests.

ProForm® XP® with Dust-Tech® is an all purpose, vinyl-based joint compound that is excellent for all phases of drywall finishing, texturing, patching and renovations. ProForm® XP® Lite with Dust-Tech® is 30% lighter than conventional joint compounds and is easier to sand.

Features/Benefits

- Three-in-one product – mold-resistant, dust-reducing All Purpose or Lite.
- Reduces airborne dust by up to 60%, saving time with quick and easy clean-up.
- Resists the growth of mold per ASTM G21 with a score of 0, the best possible score.
- Resists the growth of mold per ASTM D3273 with a score of 10, the best possible score.
- ProForm XP with Dust-Tech achieves GREENGUARD GOLD Certification for indoor air quality.
- Sands without clogging sandpaper.
- Sands and finishes with ease.
- Ready to use right from the container once mixed.

Recommendations

- Use nothing coarser than 120-grit sandpaper or 220-grit sanding screen for ProForm XP with Dust-Tech. Use nothing coarser than 150-grit sandpaper or 220-grit sanding screen for ProForm XP Lite with Dust-Tech.
- Protect from freezing and exposure to extreme heat and direct sunlight, conditions which will cause premature aging of the product.
- Do not overthin.
- Excessive mixing with an electric drill can cause undesirable changes in viscosity and in finished surface appearance.

Storage

Storage life varies with climatic conditions, up to 9 months under good conditions. Store compound away from extreme cold or heat to avoid accelerating aging. Regularly check production dates and rotate inventory on a first-in, first-out plan.



Dust-Tech does not clog sanding screens, leaving an even surface for painting.



Other low-dust products can clog, polishing the finish and leading to paint flashing.

Technical Data

PACKAGING & COVERAGE

ProForm XP Lite with Dust-Tech	4.5 gal. (17 L) pails 3.5 gal. (13.2 L) cartons
Approximate Coverage	123-140 lbs. (9 gal.)/1,000 sq. ft.
ProForm XP with Dust-Tech	61.7 lbs. (28 kg) pails 50 lbs. (22.7 kg) cartons
Approximate Coverage	123-140 lbs. (9 gal.)/1,000 sq. ft.

APPLICABLE STANDARDS AND REFERENCES

ASTM C475
ASTM C840
ASTM D3273
ASTM E119
ASTM G21
Gypsum Association, GA-214
Gypsum Association, GA-216
National Gypsum Company, <i>NGC Construction Guide</i>
National Gypsum Company, <i>ProForm® BRAND Interior Finishing Products Construction Guide</i>



Corporate Headquarters

National Gypsum Company
2001 Rexford Road
Charlotte, NC 28211
Phone: (704) 365-7300
Web: nationalgypsum.com

Technical Information

Phone: (800) NATIONAL
(800) 628-4662
Fax: (800) FAX-NGC1
(800) 329-6421

