

QUAKER STATE® HIGH MILEAGE 5W-30 MOTOR OIL

SYNTHETIC BLEND MOTOR OIL

TECHNICAL DATA SHEET



Quaker State® High Mileage motor oil helps engines defy time giving them more engine life*. How? Quaker State® is a synthetic blend motor oil formulated to help protect against the wear stresses that high mileage engines experience in everyday driving. What's more, it helps stop leaks from seals and reduces oil consumption in worn engines too.

Protects modern turbocharged engines - API SN PLUS, API SN and all previous categories.

*Compared to industry standard Sequence IVA

PERFORMANCE, FEATURES & BENEFITS

- Helps reduce wear for more engine life*
- Active seal conditioning agents to keep seals pliable to prevent leaks and oil loss
- Advanced thermal and oxidative stability to help reduce oil burn-off and maximize power output
- Contains additional friction modifiers for improved fuel economy.
- Low-speed pre-ignition protection for modern turbocharged engines.

*Compared to industry standard Sequence IVA

MAIN APPLICATIONS

Quaker State® High Mileage 5W-30 is recommended for use in all vehicles requiring the use of SAE 5W-30 viscosity grade engine oils under all driving conditions.

It is also suitable for use in modern direct injection turbocharged gasoline engines where it provides protection against damaging low-speed pre-ignition (LSPI).

Quaker State® High Mileage 5W-30 can be mixed with other synthetic and mineral oils and is recommended for use in all vehicle applications under all driving conditions.

Always consult your owner's manual for the correct viscosity grade and performance recommendation required for your vehicle.

SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

Exceeds the requirements of the following industry specifications:

- API SN PLUS
- API SN, API SN-RC and all previous categories
- ILSAC GF-5

For a full listing of equipment approvals and recommendations, please consult your local Technical Helpdesk.

To find the right Quaker State® product for your vehicles and equipment, please consult www.quakerstate.com to look-up the right motor oil recommendation using our oil selector.

© SOPUS Products 2018. All rights reserved.

QUAKER STATE® HIGH MILEAGE 5W-30 MOTOR OIL

SYNTHETIC BLEND MOTOR OIL

TYPICAL PHYSICAL CHARACTERISTICS

| Properties | | | Method | Quaker State® High Mileage 5W-30 Motor Oil |
|---------------------|--------|-------------------|------------|--|
| Kinematic Viscosity | @40°C | cSt | ASTM D445 | 68.37 |
| Kinematic Viscosity | @100°C | cSt | ASTM D445 | 11.11 |
| Viscosity Index | | | ASTM D2270 | 155 |
| Dynamic Viscosity | @-30°C | cP | ASTM D5293 | 6480 |
| MRV | @-35°C | cP | ASTM D4684 | 29600 |
| Density | @15°C | kg/m ³ | ASTM D4052 | 858.2 |
| Flash Point | | °C | ASTM D92 | 236 |
| Flash Point | | °C | ASTM D93 | 213 |
| Pour Point | | °C | ASTM D97 | -45 |

These characteristics are typical of current production. While future production will conform to Quaker State's® specification, variations in these characteristics may occur.

HEALTH, SAFETY & ENVIRONMENT

Health and Safety

This Product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <http://www.epc.shell.com>

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

ADDITIONAL INFORMATION

Advice

Advice on applications not covered here may be obtained from your Quaker State® representative.