



CEMENT & CONCRETE PRODUCTS™

F3: Epoxies

SAFETY DATA SHEET
(Complies with OSHA 29 CFR 1910.1200)

SECTION I: PRODUCT IDENTIFICATION

The QUIKRETE® Companies
One Securities Centre
3490 Piedmont Road, Suite 1300
Atlanta, GA 30305

Emergency Telephone Number
(770) 216-9580
Information Telephone Number
(770) 216-9580

SDS F3B
Revision: May-15

NOTE: TWO SDS ARE REQUIRED FOR THESE PRODUCTS

QUIKRETE® Product Name	Item #(s)
ANCHORING EPOXY – FASTSET (PART B)	8620-30
ANCHORING EPOXY – HIGH STRENGTH (PART B)	8620-31

Product Use: Epoxies for anchoring objects to concrete.

SECTION II - HAZARD IDENTIFICATION

Hazard-determining components of labeling: Nonylphenol, Ethylene Glycol

2.1 Classification of the substance or mixture

Skin Corrosion- Category 1
Serious Eye Damage - Category 1
Skin Sensitization - Category 1
Reproductive Toxin – Category 2
Toxic to Aquatic Life – Category 2

2.2a Signal word DANGER

2.2b Hazard Statements

Causes severe skin burns and serious eye damage
May cause an allergic skin reaction
Suspected of damaging fertility or the unborn child
Very toxic to aquatic life with long lasting effects

QUIKRETE**CEMENT & CONCRETE PRODUCTS™****2.2c Pictograms****2.2d Precautionary statements**

Do not handle until all safety precautions have been read and understood.

Avoid contact with the skin and eyes

Avoid breathing fumes

Wear protective gloves, eye protection and clothing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If on skin (or hair): Remove immediately all contaminated clothing and wash before re-use. Rinse skin or hair with water.

If significant skin irritation or rash occurs: get medical advice or attention.

Immediately seek medical advice or attention if symptoms are significant or persist.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/containers in accordance with all regulations.

2.3 Additional Information**Carcinogenicity**

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. Note: sanding of this product will create a possible silica dust hazard.

This product or one of its ingredients present at 0.1% or more IS listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.

2.3a HNOC – Hazards not otherwise classified: Not applicable

2.3b Unknown Acute Toxicity: 40-60% of this mixture is of unknown acute toxicity.

2.3C WHMIS Classification

TBD

2.3d Label Elements According To WHMIS

QUIKRETE**CEMENT & CONCRETE PRODUCTS™****Hazard Symbols****Signal Word**

DANGER!

SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components	CAS No.	% by Weight
Non – Hazardous Proprietary Ingredients	Proprietary	40 – 60
Liquid Polyamide Resin	68082-29-1	15 – 30
n-aminoethylpiperazine	140-31-8	3 – 7
Nonylphenol	84852-15-3	3 – 7
Tris-2, 4, 6(dimethylaminomethyl) phenol	90-72-2	3 – 7
Quartz Silica Sand (Crystalline Silica)	14808-60-7	1 – 5
Ethylene Glycol	107-21-1	0.1– 1

*The concentrations ranges are provided due to batch-to-batch variability.

SECTION IV – FIRST AID MEASURES

Inhalation: Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

Skin: Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

Ingestion: Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

Other: Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

Immediately seek medical advice or attention if symptoms are significant or persist.

SECTION V - FIRE FIGHTING MEASURES

5.1 Flammability of the Product: Flash point >93 °C (200 °F)

5.2 Suitable extinguishing agents: Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

5.3 Special hazards arising from the substance or mixture: None known

5.3a Products of Combustion: None known

5.3b Explosion Hazards in Presence of Various Substances: None known



CEMENT & CONCRETE PRODUCTS™

SECTION VI – ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures: Wear personal protective equipment (See section VIII). Keep unprotected persons away.

6.2 Methods and material for containment and cleaning up:

Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting. Do not allow to enter sewers/ surface or ground water. Dispose of unwanted materials and containers properly in accordance with all regulations.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE

7.1 Handling

Precautions for safe handling: Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.

7.2 Storage

Requirements to be met by storerooms and receptacles: Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature range in between 4 °C and 35 °C (40°F and 95° F).

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep out of the reach of children.

SECTION VIII – EXPOSURE CONTROL MEASURES / PERSONAL PROTECTION

Exposure Guidelines

Component	CAS #	OSHA PEL	TLV
Ethylene Glycol	107-21-1	50 ppm (Ceiling)	100 mg/ m3 (Ceiling)
Quartz Silica Sand (Crystalline Silica)	14808-60-7	0.1 mg/m3	0.025 mg/m3

Engineering Measures: Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

Personal Protective Equipment

Respiratory Protection


CEMENT & CONCRETE PRODUCTS™

None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

Eye / Face Protection

Wear splash proof chemical goggles/full face shield if there is a potential for splashing.

Skin / Body Protection

Wear Suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

Other Protective Clothing or Equipment

Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance:	Black Paste
Evaporation Rate:	Not applicable
Odor:	Slight Odor
Solubility in Water:	Insoluble
Specific Gravity (H₂O=1):	1.05
Vapor Density (Air = 1):	Non-Volatile
Vapor Pressure:	Not applicable
VOC Content:	7.84 g/l (when mixed)
pH:	Not determined
Boiling Point:	Not applicable

SECTION X – STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal storage conditions.

10.3 Possibility of hazardous reaction

No dangerous reaction known under conditions of normal use.

10.4 Thermal decomposition / conditions to be avoided Exposure to excessive heat and storage above 35 °C (95 °F) will shorten shelf life

10.5 Incompatible materials Strong acids, peroxides and other oxidizing agents

10.6 Hazardous Decomposition or By-products Can yield CO, CO₂ and organic Nitrogen compounds

SECTION XI – TOXICOLOGICAL INFORMATION



CEMENT & CONCRETE PRODUCTS™

11. Toxicological Information (Part A)

Acute Oral Toxicity: Not Determined

Acute Dermal Toxicity: Not Determined

Acute Inhalation Toxicity: Not Determined

Skin Irritation: Corrosive to skin. The product has not been tested. The statement has been derived from the properties of the individual components.

Eye Irritation: Causes severe damage to eyes. The product has not been tested. The statement has been derived from the properties of the individual components.

Respiratory Irritation: Inhalation of vapors or mists may cause irritation to the respiratory system.

Sensitization: May cause allergic skin reaction and irritation to the respiratory system. The product has not been tested. The statement has been derived from the properties of the individual components.

Carcinogenicity Classification:

Quartz Silica Sand (Crystalline Silica) - See Part A Section 2.

IARC Group1: Known human carcinogen based on human evidence.

NTP (National Toxicology Program) has classified Crystalline Silica as a known human carcinogen.

SECTION XII – ECOLOGICAL INFORMATION

12. Ecological Information (Part A)

Acute Toxicity for:

Fish:

Liquid Polyamide Resin:

Zebrafish /LC50 (96hrs) : >5.0mg/l

Aquatic Invertebrates:

Liquid Polyamide Resin:

Water Flea Daphnis/EC 50 (48hrs): > 7.07mg/l

Algae:

No Data Available



CEMENT & CONCRETE PRODUCTS™

Microorganisms:

No Data Available

Mobility:

Considering the use of the substance, it is unlikely that significant environmental exposure is the air or water will arise.

SECTION XIII – DISPOSAL CONSIDERATIONS

13.1 Waste Disposal Method

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

SECTION XIV – TRANSPORT INFORMATION

DOT (US)

CARTRIDGE: Limited Quantity, LTD QTY

BULK: Corrosive Liquid, n.o.s. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 1760, PG III

IATA/ICAO

CARTRIDGE/BULK: Corrosive Liquid, n.o.s. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 1760, PG III

IMDG

CARTRIDGE/BULK: Corrosive Liquid, n.o.s. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 1760, PG III

SECTION XV – OTHER REGULATORY INFORMATION

Federal Regulations:

CERCLA RQ	CAS #	Chemical Name
5000 lbs.	107-21-1	Ethylene Glycol
SARA Title 311/312		Chronic Health Hazard
TSCA	Listed	

State Regulations:

State RTK	CAS #	Chemical Name

CEMENT & CONCRETE PRODUCTS™

NJ, MA, PA 107-21-1
14808-60-7
140-31-8



Ethylene Glycol
Quartz Silica Sand (Crystalline Silica)
n-aminoethylpiperazine

State Right to Know Laws

California Prop. 65 Components

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

15.5 NFPA Rating



SECTION XVI – OTHER INFORMATION

Last Updated: May 29, 2015

NOTE: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.

Prepared by

The QUIKRETE® Companies
Phone (800) 282-5828
www.QUIKRETE.com

End of SDS