



CEMENT & CONCRETE PRODUCTS™

CONCRETE REPAIR

PRODUCT NOS. 8620-10, -13

DIVISION 3

Concrete Materials &
Methods 03 05 00

PRODUCT DESCRIPTION

QUIKRETE® Concrete Repair is a superior acrylic latex formulation for crack repair in concrete, including concrete, stucco or masonry walls, sidewalks, patios and driveways.

PRODUCT USE

QUIKRETE® Concrete Repair fills and repairs cracks up to ½" (13 mm) wide in concrete, masonry, stucco, sidewalks, patios and driveways. Benefits include:

- Dries quickly to a tough and flexible finish
- Helps prevent water and ice damage to concrete surfaces
- Weather resistant
- Excellent adhesion
- Textured to blend with concrete surfaces
- Easy clean up with water before product dries

SIZES

• QUIKRETE® Concrete Repair is available in 5.5-fl.oz. (163 ml) squeeze tubes and 10-fl.oz. (296 ml) standard caulking tubes

YIELD

• 5.5-fl.oz (163 ml) tubes will yield about 12 linear feet (3.7 M) at a ¼" (6 mm) diameter bead
• 10.1-fl.oz (296 ml) tubes will yield about 24 linear feet (7.3 M) at a ¼" (6 mm) diameter bead or 12 linear feet (3.7 M) for a 3/8" (9mm) diameter bead

INSTALLATION

SURFACE PREPARATION

Clean all loose dirt, dust and gravel from the crack. Surfaces to receive Concrete Repair should be dry and free of oil and grease.

APPLICATION

- (1) Cut tip of spout on angle to make a ¼" (6 mm) to 3/8" (9 mm) hole.
- (2) Use cartridge in standard caulking gun. Apply by pushing cartridge tip over surface and forcing bead of Concrete Repair deep into the crack. Apply no thicker than 3/8" (9 mm) at a time. On horizontal surfaces, deep cracks can be partially filled with sand prior to application.
- (3) Concrete Repair can be tooled to smooth the surface.



- (4) Excess Concrete Repair can be wiped off with a damp cloth.
- (5) Wait at least 24 hours before painting. Use latex paints only. Air and surface temperature should be above 40°F (4°C) for proper application.
- (6) Do not apply if rain threatens or is predicted within 12 hours

PRECAUTIONS

Do not use to fill control / expansion joints. Do not use for structural repairs. For horizontal structural repairs, use QUIKRETE Polyurethane Self-Leveling Sealant (#8660-10). For vertical & overhead repairs, use QUIKRETE Polyurethane Non-Sag Sealant (#8660-11). May cause eye, skin and respiratory irritation. Avoid contact with eyes, skin and clothing. Avoid breathing vapor. Use only with adequate ventilation. Ingestion may cause irritation. Store between 35 °F (2°C) and 100 °F (38°C). Do not apply where temperatures may reach 140°F (60°C) or higher (fireplaces, electric wires, etc.)

WARRANTY

NOTICE: Obtain the applicable LIMITED WARRANTY: at www.quikrete.com/product-warranty or send a written request to The Quikrete Companies, LLC, Five Concourse Parkway, Atlanta, GA 30328, USA. Manufactured under the authority of The Quikrete Companies, LLC. © 2018 Quikrete International, Inc.

* Refer to www.quikrete.com for the most current technical data, MSDS, and guide specifications