
Spiegel Grove® - Data


Item / Image

Description - Brushed Cedar Woodgrain Finish




Double 4" 20D4__

Length 12' - 6" | 24 Panels/Ctn. | 2 Sq./Ctn. | Ctn. Weight: 87.08 lbs.




Length 12' - 1" | 22 Panels/Ctn. | 2 Sq./Ctn. | Ctn. Weight: 83.99 lbs.



Dutchlap 5" 20DL5

Length 12' - 0" | 20 Panels/Ctn. | 2 Sq./Ctn. | Ctn. Weight: 82.76 lbs.



Color # / Colors

02 White Birch

11 Classic Sand

17 Warm Sandalwood

22 Sunny Maize

43 Pebble Clay

26 Summer Wheat

41 Soft Willow


79 Seagrass 49 Graphite Grey

82 Meadow

61 Artisan Clay

44 Harbor Stone 52 Java

86 Nutmeg



Double 5" 20D5

Length 12' - 0" | 20 Panels/Ctn. | 2 Sq./Ctn. | Ctn. Weight: 82.87 lbs.

Color # / Colors

02 White Birch 17 Warm Sandalwood

22 Sunny Maize

44 Harbor Stone 47 Slate Blue

43 Pebble Clay

82 Meadow 86 Nutmeg

79 Seagrass

46 Basket Beige

47 Slate Blue

41 Soft Willow

T3.3" 20T333_

Length 12' - 0" | 20 Panels/Ctn. | 2 Sq./Ctn. | Ctn. Weight: 83.98 lbs.



Color # / Colors

02 White Birch 17 Warm Sandalwood

44 Harbor Stone 46 Basket Beige

22 Sunny Maize

82 Meadow

43 Pebble Clay

86 Nutmeg

Product Test Data - Spiegel Grove Vinyl Siding w/Reinforced Nail Hem

SCI® Vinyl Siding meets or exceeds all industry standards per ASTM D3679.

.0.3%

Siding Thickness. .040" ± .001" Specific Gravity. .1.45 Tensile Strength (PSI). .7,154 ..416,900 Tensile Modulars (PSI) IZOD Impact Strength @ 32°F... .Passes per ASTM D3679 Heat Deflection Temp. @ 264 PSI... ..169°F Coefficient of Linear Expansion. ..3.30 x 10⁻⁵ .0.00"

Surface Distortion @ 140°F. Flame Spread Index. .10 Fire Rating. ..Class A Smoke Developed. ..395 Fuel Contribution... Average Time Of Burning. .Self extinguished ..2.379 mm Average Extent Of Burning. .Passes per ASTM D3679 Weathering.. Impact Resistance. .Passes per ASTM D3679





Heat Shrinkage



Spiegel Grove® Vinyl Siding

Classic Character







Strong relationships. Strong results.

RMC Siding® continually brings our customers innovation with an extensive line of beautiful, high-performance products. As an integrator and value creator, we provide only the best products that meet and exceed the needs of today's homeowners for style, durability and carefree enjoyment. Through every interaction, we also strive to build lasting partnerships with our customers. Because we believe strong relationships lead to strong results. Our shared commitment leads to our shared success.



Performance that matters to you.

Each of our product lines is unique, with its own distinctive performance properties.



Style:

- Choose from several beautiful colors
- Freshly painted wood look
- Deep, 9/16" profile height for distinctive shadow lines



Durability:

- · Impervious to wood-boring insects, fungus and mildew
- · Positive Locking System for ease of installation
- · Resists dents, hail damage, scratches and fading



Maintenance:

- Limited Lifetime Warranty
- · Easy-care convenience, never needs painting



Quality:

- Armor Coat[™] finish protects the color and provides outstanding weatherability
- · Meets or exceeds industry standards for **ASTM D3679**
- Meets VSI Standards



Responsible:

NGBS Green Approved Product



Go to www.vinylsiding.org for a current list of certified products and colors.





Available Profiles:

Double 4, Double 5

Dutchlap 4.5, Dutchlap 5

Triple 3.3

Available Colors:









Summer Wheat 26



Soft Willow 41



Pebble Clay 43

Graphite Grey 49

Meadow 82



Harbor Stone 44

Sunny Maize 22





Artisan Clay 61



Seagrass 79





Java 52

Nutmeg 86

NOTE: Color representation may vary from actual product color.