



ADHESIVES • ACCESSORIES • TROWELS



a quality brand of





In 1938, the carpet industry had just begun to use liquid latex for carpet seaming and repair. The newly formed Roberts Company developed a new latex formula of its own and labeled it Rubber-edge, laying the groundwork for today's thriving Adhesives Division of Roberts Company Canada, Ltd.

Roberts continued with innovations in the industry and pioneered the Double Bond Carpet Installation method which is now a recognized standard that has stood the test of time. Roberts has been a leader in the manufacturing of adhesives ever since, producing its first solvent free adhesive in the 1980's and continuing to develop environmentally friendly products.

With locations and product lines known and used throughout the world, Roberts has been recognized as the premier brand of adhesives, carpet installation tools and accessories. Worldwide, the Roberts name continues to be the manufacturer of choice for installation professionals who demand quality and reliability.

**Supporting Professional
Installers Since 1938**

CONTENTS

Multipurpose Adhesives 3

Carpet Adhesives 5

Resilient Adhesives 9

Wood Adhesives 12

Specialty Adhesives 14

Adhesive Cleaners 16

Adhesive Reference Chart 17

Trowel Chart 18

Roberts®, GoldGuard®, Tiger Tooth® and the e® logo are registered trademarks of Roberts Company Canada, Ltd.
Q.E.P.® is a registered trademark of Q.E.P. Co., Inc.

CRI Green Label +Plus® is a registered trademark of The Carpet and Rug Institute
'LEED®' and related logo is a trademark owned by the Canada Green Building Council®

ActionBac® is a registered trademark of Propex Operating Company, LLC | Enhancer™ is a trademark of
The Dow Chemical Company | SoftBac® is a registered trademark of Shaw Industries, Inc.

ADHESIVE SOLUTIONS



Roberts® Moisture Control Adhesives

Enhanced, superior-grade adhesives made to withstand up to 10 lbs. moisture vapor emission rates (MVER) and up to 90% relative humidity (RH), over newly poured concrete with declining values. This improvement simplifies the moisture mitigation process:

SAVE TIME. SAVE STEPS. SAVE MONEY.



UP TO 8 LBS.



UP TO 10 LBS.

Roberts Company Canada actively participates with governing agencies and organizations to establish the highest standards for environmentally conscientious products. We seek continuous improvement in our product development to globally offer the most ecologically responsible products.



GoldGuard® Antimicrobial Technology

Roberts two-tier antimicrobial protection system for both the wet and dry state inhibits the growth of mold, mildew and odor causing bacteria.



CRI Green Label +Plus®

These adhesives have been rigorously tested and meet the most stringent criteria for low chemical emissions and are among the lowest emitting VOC products in the market.



Enviro Friendly

Environmentally conscious products manufactured by a company committed to protect and sustain our environment.



LEED® Canada Green Building Council

Many of our adhesives contribute one or more points in the LEED® rating system. The LEED green building certification program is the nationally accepted benchmark for the design, construction, and operation of green buildings.

INDUSTRY PARTNERSHIPS





Multipurpose Adhesives

3300 Multipurpose Adhesive

SUPERIOR


- **MOISTURE CONTROL** – Up to 8 lbs. MVER / 85% RH
- Aggressive grab for reduced bubbling and curling
- Excellent rebond properties
- Ideal for direct and double bond installations
- Traffic - Heavy commercial



Roberts 3300 is a superior performing, high solids multipurpose adhesive formulated for the installation of hard-to-bond commercial carpet and most types of felt-backed, fiber-backed and paper-backed resilient floor coverings. It provides an aggressive upfront grab for reduced bubbling and curling; yet remains tacky with great repositionable characteristics. VOC: < 1 g/L.

Open Time: Up to 30 min. **Working Time:** Up to 60 min.

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
3300RB020	18.9 L (5 gal)	1
3300RB015	15.14 L (4 gal)	1
3300RB004	3.78 L (1 gal)	4
3300RB001	946 mL (1 qt)	6




3200 Multipurpose Adhesive

PREFERRED

- Fast tacking and fast setting
- Ideal open time with good leg development
- Superb rebond characteristics
- Traffic - Heavy residential / Moderate commercial

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
3200RB020	18.9 L (5 gal)	1

Roberts 3200 is a top performer in the mid-range class of multipurpose adhesives. 3200 offers the ideal open time and leg development for mid-range commercial job sites, then develops a strong bond for great holding power. VOC: < 1 g/L.

Open Time: Up to 35 min. **Working Time:** Up to 65 min.



3030 Multipurpose Adhesive

PREFERRED

- Medium tack development
- Great adjustability time
- Traffic - Heavy residential / Moderate commercial

Roberts 3030 is a multipurpose adhesive designed for the installation of carpet and sheet vinyl flooring. It is a good tacking adhesive which offers great flexibility in open time – not too fast, not too slow for mid-sized jobs. VOC: < 1 g/L.

Open Time: Up to 30 min. **Working Time:** Up to 90 min.

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
3030RB020	18.9 L (5 gal)	1
3030RB004	3.78 L (1 gal)	4
3030RB001	946 mL (1 qt)	6



2MX5 Multipurpose Adhesive

PREFERRED

- Quick leg development
- High tack and fast setting with maximum grab
- Traffic - Heavy residential / Moderate commercial

Roberts 2MX5 Multipurpose is a maximum grabbing adhesive designed to accelerate the installation process of most carpet. It also allows enough open time for small installations of felt-backed sheet goods. VOC: < 1 g/L.

Open Time: Up to 35 min. **Working Time:** Up to 55 min.

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
2MX5RB020	18.9 L (5 gal)	1
2MX5RB015	15.14 L (4 gal)	4



2980 Multipurpose Adhesive

PRIMARY

- Optimal open time for felt-backed sheet vinyl
- Contract-grade formula for most types of carpet
- Traffic - Moderate residential / Light commercial

Roberts 2980 Multipurpose is a contract-grade adhesive formulated for the installation of most types of carpet and felt-backed sheet vinyl. Developed to have a longer open time for the optimal positioning of felt-backed vinyl flooring while it also develops tack for the installation of rigid-backed carpets. VOC: 18 g/L.

Open Time: Up to 60 min. **Working Time:** Up to 90 min.

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
2980RB020	18.9 L (5 gal)	1
2980RB015	15.14 L (4 gal)	1





Carpet Adhesives

PRESSURE SENSITIVE ADHESIVES

6300 Pressure Sensitive Adhesive

SUPERIOR

- MOISTURE CONTROL – Up to 10 lbs. MVER / 90% RH
- Persistent tack and high shear strength
- Releasable for ease of replacement or wet-set for permanent bond
- Excellent resistance to plasticizer migration
- Traffic - Heavy commercial



TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
R6300RB015	15.14 L (4 gal)	1
R6300RB004	3.78 L (1 gal)	4

Roberts 6300 is a high performance pressure sensitive adhesive which may be used to install carpet tiles, commercial carpet cushion, fibreglass reinforced sheet vinyl and luxury vinyl tiles. This product dries quickly and offers a high shear strength, making it the adhesive of choice for commercial installations where performance is key. VOC: 9 g/L.

Permanent Install Open Time: Up to 20 min.

Working Time: Up to 40 min.

Releasable Install Tack Time: Up to 45 min.



6280 Pressure Sensitive Adhesive

PREFERRED

- Permanent or releasable installations
- Good plasticizer migration resistance
- Works with a variety of flooring types
- Traffic - Heavy residential / Moderate commercial

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
R6280RB015	15.14 L (4 gal)	1
R6280RB004	3.78 L (1 gal)	4

Roberts 6280 is an acrylic pressure sensitive adhesive designed for the installation of vinyl backed carpet tiles, commercial carpet cushion, luxury vinyl tiles (up to 12" x 12") and fibreglass reinforced sheet vinyl. This product may be used as a releasable adhesive or a permanent adhesive, if flooring is installed while adhesive is still wet. VOC: < 1 g/L.

Permanent Open Time: Up to 20 min.

Working Time: Up to 40 min.

Releasable Tack Time: Up to 45 min.



3095 Carpet Adhesive

SUPERIOR

- **MOISTURE CONTROL** – Up to 10 lbs. MVER / 90% RH
- High tack and fast grab for holding stiff, rigid backings
- Outstanding leg development and superior bond strength
- Traffic - Heavy commercial



TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
3095RB020	18.9 L (5 gal)	1
3095RB010	10 L (2.6 gal)	1
3095RB004	3.78 L (1 gal)	4
3095RB001	946 mL (1 qt)	6

Roberts 3095 is a premium commercial-grade carpet adhesive developed for the most demanding carpet installations, including broadloom carpet. This high solids latex-based adhesive is fast grabbing and produces great bond and shear strengths. Roberts 3095 is an excellent adhesive for direct or double bond installations. VOC: < 1 g/L.

Open Time: Up to 20 min. **Working Time:** Up to 40 min.



OUTDOOR CARPET ADHESIVES

6040 Outdoor Carpet Adhesive

SUPERIOR

- High strength, solvent-based and rapid setting
- Waterproof once cured
- Sets rapidly for a secure bond
- Ideal for patios, boats and decks
- Permanent installation of outdoor carpet and artificial turf

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
6040RB35U	13.25 L (3.5 gal)	1

Roberts 6040 is a superior grade carpet adhesive developed for exterior installations of most types of outdoor commercial carpets. VOC: 352 g/L. **EXTREMELY FLAMMABLE**

Open Time: Up to 15 min. **Working Time:** Up to 30 min.



6700 Indoor/Outdoor Carpet Adhesive

SUPERIOR

- Solvent-free, non-flammable and suitable for use in enclosed spaces
- Excellent moisture resistance when cured
- Ideal for decks, sunrooms and basements

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
6700RB015	15.14 L (4 gal)	1
6700RB004	3.78 L (1 gal)	4
6700RB001	946 mL (1 qt)	6

Roberts 6700 is a solvent-free adhesive designed for the interior or exterior installation of indoor/outdoor carpet. This adhesive is ideal for interior patios, decks, sunrooms and basements. VOC: < 1 g/L.

Open Time: Up to 30 min. **Working Time:** Up to 60 min.





Carpet Accessories

8015 Universal Carpet Seam Sealer

SUPERIOR

- Fast drying solvent-free formula; dries clear
- Compatible with vinyl-backed carpets
- Contains UV tracers for easy identification with UV light sources
- Can be used on both direct- and double-bond applications as a seam sealer

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
8015RB001	946 mL (1 qt)	6
8015RB250	236 mL (8 oz)	12

Roberts 8015 is a universal, solvent-free carpet seam sealer developed for seaming most types of carpets, including vinyl backed. This product seals cut edges to prevent ravelling and may also be used to repair bubbles in installations. VOC: < 1 g/L.

Coverage: Up to 200 lineal meters per 946 mL. **Open Time:** Up to 10 min.



8502 Latex Carpet Seam Sealer

PREFERRED

- Binds and seals carpet edges to prevent raveling
- Contains UV tracers for easy detection
- Use to apply new backings to area rugs
- Provides enhanced slip resistance

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
8502RB020	18.9 L (5 gal)	1
8502RB001	946 mL (1 qt)	12

Roberts 8502 Latex Carpet Seam Sealer is recommended for seam sealing carpets, sealing raw edges, binding, strengthening worn backings and applying new backings on area rugs. Roberts 8502 may also increase slip resistance on mats or area rugs. Roberts 8502 contains UV tracers for easy detection. VOC: 19 g/L.

Coverage: Up to 221 lineal meters per 946 mL. **Open Time:** Up to 10 min.



8415 Carpet Seam Sealer

PREFERRED

- Fast drying, superior permanent bond – Prevents edge ravelling and seals seams
- For direct-glue and double-glue down installations
- Contains UV tracers for easy detection of use

Roberts 8415 is a solvent-based commercial grade adhesive developed to seam most types of carpets and to prevent edge ravelling. May also be used to repair bubbles in installations. VOC: 573 g/L. **EXTREMELY FLAMMABLE**

Coverage: Up to 200 lineal meters per 946 mL. **Open Time:** Up to 10 min.

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
8415RB004	3.78 L (1 gal)	4
8415RB001	946 mL (1 qt)	6



1000 Seam Adhesive Dispenser

- Designed to apply seam sealer to the seams of carpet and vinyl flooring
- Use with the “stepped” applicator tip for best results
- Holds up to 236 mL (8 U.S. ounces)

Roberts 1000-8 is an empty seam adhesive applicator bottle used for dispensing seam sealing products, such as Roberts 8015 Universal Carpet Seam Sealer.



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
1000-8	Holds 236 mL	12

4020 Carpet Pad Adhesive

SUPERIOR

- Superior wet grab for easy installations
- Powerful initial tack and high strength
- Rapid installation with a permanent bond

Roberts 4020 is a premium solvent-based adhesive with powerful initial grab to hold carpet pads in place quickly. Roberts 4020 is a superior adhesive developed for the adherence of carpet pads prior to the installation of stretch-in carpet. VOC: 520 g/L. **EXTREMELY FLAMMABLE**

Coverage: Up to 213 lineal meters per 3.78 L, depending on application method

Open Time: Up to 5 min. **Working Time:** Up to 60 min.

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
4020RB004	3.78 L (1 gal)	4





Resilient Adhesives

7350 UNIVERSAL Vinyl Flooring Adhesive

SUPERIOR

- NEW Powerhouse LVT/LVP formula
- MOISTURE CONTROL – Up to 10 lb. MVER / 90% RH
- High solids, high performing pressure sensitive
- Aggressive bond with permanent tack
- Traffic - Heavy commercial



TROWELS

1/16" x 1/16" x 1/16"

1/16" x 1/32" x 1/32"

Medium Nap Roller

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
7350RB015	15.14 L (4 gal)	1

Roberts 7350 UNIVERSAL is a high quality, high solid cross-linking adhesive designed specifically for installing luxury/solid vinyl tiles and planks. It has tremendous bond and shear strength, plus excellent moisture and plasticizer migration resistance. Roberts 7350 can also be used to adhere carpet tiles and specialty vinyl flooring underlayment, such as Roberts Cork Pro Plus, to the subfloor and may also be used to install VCT, homogeneous and heterogeneous sheet flooring. VOC: 9 g/L.

Dry Method Installation Tack Time: Approx. 45 mins.

Permanent Installation Open Time: Up to 20 mins.

Working Time: Up to 40 mins.



2350 HARD-SET Vinyl Flooring Adhesive

SUPERIOR

- MOISTURE CONTROL – Up to 8 lb. MVER / 85% RH
- Firm Setting Transitional Pressure Sensitive
- Very high peel and shear strengths to lock flooring in place
- Outstanding plasticizer migration resistance
- Traffic - Heavy commercial



TROWELS

1/16" x 1/16" x 1/16"

1/16" x 1/32" x 1/32"

3/32" x 3/32" x 3/32"

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
2350RB015	15.14 L (4 gal)	1
2350RB004	3.78 L (1 gal)	4
2350RB001	946 mL (1 qt)	6

Roberts 2350 HARD-SET Adhesive is a high performance acrylic formulation that offers up front pressure sensitive characteristics, then turns to a hardset and develops a strong bond to withstand heavy rolling loads. Designed for the installation of most vinyl-backed floor coverings and offers the flexibility of installing over porous and non-porous substrates. VOC: < 1 g/L.

Open Time: Up to 15 min. **Working Time (Wet):** 60 mins.

Working Time (Semi-Tacky): Up to 60 mins.



2001 Felt-Back Sheet Vinyl Adhesive

PREFERRED

- Non-staining formulation
- Extended open and working time
- Traffic - Residential / Moderate commercial

Roberts 2001 is a commercial-grade, felt-backed sheet vinyl adhesive. This adhesive was developed with the optimum open time and working time for the positioning of felt-backed sheet vinyl flooring, plus provides a lifetime non-staining warranty. Accepts residential to moderate commercial foot traffic. VOC: < 1 g/L.

Open Time: Up to 25 min. **Working Time:** Up to 45 min.

TROWELS

1/16" x 1/16" x 3/32"

1/16" x 1/16" x 1/16"

1/16" x 1/32" x 1/32"

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
2001RB015	15.14 L (4 gal)	1
2001RB010	10 L (2.6 gal)	4
2001RB004	3.78 L (1 gal)	4
2001RB001	946 mL (1 qt)	6



2057 VCT Adhesive

SUPERIOR

- MOISTURE CONTROL – Up to 8 lb. MVER / 85% RH
- Dries clear for visible chalk lines
- Good residual tack
- Extended working time
- Traffic - Heavy residential / Moderate commercial



TROWELS

1/16" x 1/16" x 3/32"

1/16" x 1/16" x 1/16"

1/16" x 1/32" x 1/32"

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
2057RB020	18.9 L (5 gal)	1
2057RB015	15.14 L (4 gal)	4
2057RB004	3.78 L (1 gal)	4
2057RB001	946 mL (1 qt)	6

Roberts 2057 is a clear thin spread adhesive designed for the installation of vinyl composition tile (VCT). VOC: < 1 g/L.

Open Time: Up to 60 min. **Working Time:** 8-12 hrs.



2038 Asphalt Emulsion VCT Adhesive

SUPERIOR

- Black thin spread
- Superior holding power
- Resists tile shifting
- Traffic - Heavy commercial

TROWELS

1/16" x 1/16" x 3/32"

1/16" x 1/16" x 1/16"

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
2038RB020	18.9 L (5 gal)	1
2038RB015	15.14 L (4 gal)	4
2038RB010	10 L (2.6 gal)	4
2038RB004	3.78 L (1 gal)	4
2038RB001	946 mL (1 qt)	6

Roberts 2038 is a solvent-free latex based asphalt emulsion adhesive developed for the installation of vinyl composition tile. May be used over existing black out adhesive residue. VOC: < 2 g/L.

Open Tack Time: Aprox. 45 min. **Working Time:** 8-12 hrs.





Wall Base Adhesives

7200 Wall Base Adhesive

SUPERIOR

- Excellent holding power and great wet suction
- Strong initial grab for holding heavy rubber wall base
- Fast set-up and non-staining formula
- Easy application and cleanup

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
7200RB001	946 mL (1 qt)	6
7200RB852	887 mL (30 oz)	12
7200RB313	325 mL (11 oz)	12

Roberts 7200 is a superior performing wall base adhesive with quick grab and rapid set-up for the fast installation of wall base. VOC: < 1 g/L.

Open Time: Up to 10 min. **Working Time:** Up to 30 min.



7051 Wall Base Adhesive

SUPERIOR

- High performance acrylic
- Extra high wet strength for bonding heavy rubber base
- Quick grabbing, fast set-up and solvent-free

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
7051RB010	10 L (2.6 gal)	1
7051RB004	3.78 L (1 gal)	4
7051RB852	887 mL (30 oz)	12

Roberts 7051 is a superior performing wall base adhesive with quick grab and rapid set-up for the fast installation of wall base. VOC: < 1 g/L.

Open Time: Up to 10 min. **Working Time:** Up to 30 min.





Wood Adhesives

1540 ALL-IN-ONE Urethane Flooring Adhesive

SUPERIOR

- ALL-IN-ONE: Sound reducer, moisture barrier, 1/8" crack suppressant and bonding system
- Remains flexible to expand and contract with wood flooring
- Best for solid wood planks wider than 5"
- Ideal for use over radiant heat subfloors

Roberts 1540 is a single step, 100% solids moisture-cure polyurethane adhesive formulated to bond engineered wood, solid wood and bamboo flooring. Roberts 1540 provides moisture vapor emissions control on concrete slabs (up to 20 lbs. MVER or 90% RH); once cured the adhesive forms a water-resistant membrane. It also bridges non-structural cracks in concrete (up to 1/8"). This adhesive is suitable for use with radiant heat systems. VOC: < 1 g/L.

Working Time: Up to 120 min. **Initial Cure:** 8-10 hrs. **Final Cure:** 12 hr minimum

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
R1540RB015	15.14 L (4 gal)	1

IIC 70 STC 66 ΔIIC 22



1409 Wood Flooring Adhesive

SUPERIOR

- Permanent, tenacious bond with high elongation properties
- Cured adhesive is unaffected by moisture
- Excellent green grab, low VOC
- Suitable for rubber flooring installations
- Ideal for wood planks wider than 5"

A single component, moisture-cure urethane adhesive formulated to bond engineered wood, solid wood, bamboo and teak flooring to concrete, plywood and other approved substrates. Develops a permanent bond and remains flexible to withstand expansion and contraction of the flooring without stressing the adhesive. Suitable for all wood flooring that is intended for glue-down installations, plus it can be used for installing rubber flooring too.

Open Time: Up to 80 min. **Working Time:** Up to 120 min. **Cure Time:** 8-10 hrs.

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
R1409RB015	15.14 L (4 gal)	1




1407 Engineered Wood Flooring Adhesive

PREFERRED

- Easy to trowel; great green grab; strong durable bond
- Available in cartridge sizes – Perfect for quick repairs and installing thresholds, wood stair nosing, wood risers, moldings, stair wood moldings and medallions
- Great for double bond installs; cork underlayment to subfloor / wood flooring to cork underlayment

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
1407RB015	15.14 L (4 gal)	1
1407RB004	3.78 L (1 gal)	4
1407RB852	887 mL (30 oz)	12
1407RB313	295 mL (10 oz)	12

Roberts 1407 is an acrylic tri-polymer urethane adhesive designed for the installation of engineered and parquet wood flooring. Smooth and easy to trowel formula with great green grab. VOC: < 1 g/L.

Open Time: Up to 20 min. **Working Time:** Up to 30 min.



1406 Tongue & Groove Flooring Adhesive

SUPERIOR

- Exceptional bond strength and fast drying
- Applies white and dries clear
- Meets the specifications of ANSI/HPVA Type II/D3

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
1407RB004	3.78 L (1 gal)	4
1407RB500	473 mL (1 pint)	12

Roberts 1406 is a high strength PVA adhesive with specialized applicator tip for precise placement of the adhesive. VOC: 7 g/L.

Coverage: Up to 122 lineal meters per 473 mL.

Assembly Time: Within 5 min.

Drying Time: 12-24 hrs.



10-33 Universal Putty Repair Kit

- Quickly repair scratches, cracks and other damage on wood floors, vinyl floors and counters, wood cabinets, moldings and furniture
- Easy to sand, accepts top coat finishes and stainable
- 5 colors to custom mix and create unlimited shades to match any project
- List of colour formulas available at www.robertsconsolidated.com

Shipped in a master pack of six kits with clip strip for easy display





Specialty Adhesives

QUICKBOND

8200 Spray Adhesive *For Carpet Pads & More!*

SUPERIOR

- Tacks quickly with a web spray pattern
- Permanent or repositionable bond
- VOC compliant and meets OTC specifications
- Does not contain chlorofluorocarbons (CFCs), ozone depleting chemicals, or methylene chloride
- Reduces install time
- Quick installation of carpet pads, cork wall tiles and much, much more!

Roberts 8200 QUICK BOND is a fast tacking aerosol construction adhesive with the versatility to be used on a wide array of substrates. 8200 is formulated to bond to paper, cardboard, fabric, leather, foil, fiberglass to metal, drywall, masonry, wood and a variety of other substrates. **EXTREMELY FLAMMABLE**

Coverage: Up to 9.3 m² per 340g can

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
8200RB355	355 mL (12 oz)	1



RB40 HEAVY-DUTY Construction Adhesive

PREFERRED

- Fast tacking, flexible adhesive with a permanent bond
- Absorbs vibration; eliminating squeaks
- Solvent-based; excellent for exterior use

Roberts RB40 HEAVY-DUTY Construction Adhesive is specially formulated to permanently bond wood subfloors, plywood, paneling, fibre board and more. This rapid tacking and flexible adhesive eliminates squeaks, bounce and absorbs vibration. VOC: 390 g/L. **FLAMMABLE**

Coverage: 1/4" Bead – Up to 29.3 lineal meters per 857 mL
3/8" Bead – Up to 12.8 lineal meters per 857 mL

Working Time: 10-15 min. **Drying Time:** 24 hr.

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
40RB001	946 mL (1 qt)	6
40RB825	857 mL (29 oz)	12
40RB300	295 mL (10 oz)	12



5900 Ceramic Tile Adhesive


PREFERRED

- Premixed; ready-to-use
- Quick grabbing and fast drying
- Type I Mastic for floors and walls

Roberts 5900 is a high performance, ready to use, ANSI A136.1 Type I organic ceramic tile mastic used to install ceramic wall tile over a variety of substrates. May also be used for countertop and backsplash installations. VOC: 56 g/L.

Open Time: Up to 20 min. **Working Time:** Up to 25 min.

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
5900RB35U	13.25 L (3.5 gal)	1
5900RB004	3.78 L (1 gal)	4
5900RB001	946 mL (1 qt)	6



2072 Linoleum Adhesive

SUPERIOR

- Strong initial grab
- Great working time
- Low odour
- Traffic - Heavy commercial

Roberts 2072 is a superior, commercial grade adhesive designed specifically for the installation of linoleum flooring. This adhesive is designed with an early strength to grab and hold stiff linoleum floors in place. VOC: 6 g/L.

Open Time: Up to 45 min. **Working Time:** Up to 25 min.

TROWELS



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
2072RB020	18.9 L (5 gal)	1



1010 Contact Cement

PREFERRED

- Multi-use brush-grade contact cement
- Dries fast, increased bond strength with age
- Resists water

Roberts 1010 is a brush-grade contact cement with powerful bonding power. It forms high strength bonds on contact. Finished assemblies can be used immediately. Bonds made with Roberts 1010 are highly resistant to the effects of water and weather elements. VOC: 649 g/L. **FLAMMABLE**

Coverage: Up to 24.5 m² (12 m² of bonded material) per 3.78 liters
Assembly Time: Until dry, approx. 15 min. **Tack Range:** 4 hr. max.

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
1010RB020	20 L (5.28 gal)	1
1010RB35U	13.25 L (3.5 gal)	4
1010RB004	3.78 L (1 gal)	12
1010RB001	946 mL (1 qt)	12



1030 Latex Contact Cement

PREFERRED

- Solvent Free
- Water resistant
- Heat resistant bond

Roberts 1030 is a solvent free, brush grade, polychloroprene latex based contact cement adhesive. It may be used to bond a wide variety of surfaces and offers a high strength, heat resistant bond. Finished assemblies can be used immediately. VOC: < 1 g/L.

Coverage: Up to 35.5 m² (17.7 m² of bonded material) per 3.78 liters
Assembly Time: Up to 30 min. **Tack Range:** 2 hr. max.



AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
1030RB004	3.78 L (1 gal)	4
1030RB001	946 mL (1 qt)	6



Adhesive Cleaners

5505 Urethane Adhesive Remover

SUPERIOR

- Quick and easy adhesive spot removal
- Extremely low odor
- Advanced technology formula

Roberts 5505 is a superior cleaner to aid in the removal of fresh and dried adhesive from flooring surfaces and tools. VOC: < 500 g/L.

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
R5505RB709	710 mL (24 oz)	12



8000 Flooring and Adhesive Remover Concentrate

SUPERIOR

- Higher coverage rate – Up to 23.2 m² per 3.78 liters (diluted)
- Fast acting concentrate formula
- Non-flammable, low odor, VOC and OTC Clean Air Act compliant

Roberts 8000 Remover is a concentrated environmentally-friendly formula developed to penetrate the floor covering, and break down the adhesive for quick and easy removal. This commercial strength product is also ideal for stripping the toughest latex and acrylic adhesives from flooring surfaces. VOC: < 50 g/L.

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
R8000RB004	3.78 L (1 gal)	4



1902 Cleaner and Thinner

PRIMARY

- Removes most types of adhesives
- Fast acting, no residue




























Roberts 1902 is a special blend of solvents that may be used for cleaning and removal of solvent-based products or to thin Roberts solvent-based contact cements. VOC: 520 g/L. **HIGHLY FLAMMABLE**

AVAILABLE SIZES

Item No.	Unit Size	Pkg. Qty.
1902RB001	946 mL (1 qt)	6



ADHESIVE REFERENCE CHART

			CARPET										RESILIENT & WALL BASE										WOOD				
			Polypropylene (ActionBac)	Jute	Hot Melt	Enhancer (Urethane Foam)	Latex Unitary	Needle Punch	Woven Interlock	Vinyl-Backed Carpet/Carpet Tile	Closed Cell Urethane	Double-Bond Method (Carpet-to-Cushion/Cushion-to-Floor)	Vinyl Composition Tile (VCT)	Sheet Goods (Felt/Mineral Backed)	Sheet Goods (Solid Vinyl/Homogeneous/Heterogeneous)	Sheet Goods (Fiberglass)	Luxury Vinyl Tile (Up to 12" x 12")	Luxury Vinyl Tile / Plank (Large Format, > 12" x 12")	Double-Bond Method (Vinyl-to-Underlay/Underlay-to-Floor)	Vinyl/Rubber (TPR) Cove Base	Polyurethane Laminate (LifeSpan)	Recycled Rubber Flooring (Tile, Sheet)	Engineered Wood Plank (< 5" wide)	Engineered Wood Plank (> 5" wide)	Parquet (Non-Foam Backed)	Solid Plank/Parquet/Exotics (Bamboo, Cork, Teak)	
MULTI PURPOSE		3300 SUPERIOR 	BEST	BEST	BEST	GOOD	BEST	BEST	BEST		BETTER	BEST		BETTER													
		3200 PREFERRED	BETTER	BETTER	BETTER	GOOD	BETTER	BETTER	BETTER		GOOD	BETTER		GOOD													
		3030 PREFERRED	BETTER	BETTER	GOOD		GOOD	BETTER	BETTER		GOOD			GOOD													
		2MX5 PREFERRED	GOOD	GOOD			GOOD							GOOD													
		2980 PRIMARY	GOOD	GOOD			GOOD							GOOD													
CARPET		6300 SUPERIOR 				BEST				BEST	BEST				BETTER	BETTER	BETTER	BETTER									
		6280 PREFERRED				BETTER				BETTER					GOOD	GOOD	GOOD										
		3095 SUPERIOR 	BEST	BEST	BEST	BEST	BEST	BEST	BEST		BEST	BEST															
		6040 SUPERIOR	BEST	BEST			BEST																				
		6700 SUPERIOR	BEST	BEST	BEST	GOOD	BEST	BEST	BEST		GOOD																
		8015 SUPERIOR	BEST	BEST		BEST	BEST	BEST	BEST		BEST																
		8415 PREFERRED	BETTER	BETTER		BETTER	BETTER				BETTER																
		5200 PREFERRED	BETTER	BETTER		BETTER	BETTER				BETTER																
RESILIENT		7350 SUPERIOR 								BEST			BETTER		BEST	BEST	BEST	BEST	BEST			GOOD					
		2350 SUPERIOR 														BETTER	BETTER		BETTER			BETTER					
		2001 PREFERRED												BEST													
		2057 SUPERIOR 											BEST														
		2038 SUPERIOR											BETTER														
		7200 SUPERIOR																		BEST							
		7051 SUPERIOR																		BETTER							
WOOD		1540 SUPERIOR																				BEST			BEST	BEST	BEST
		1409 SUPERIOR																			BETTER			BEST	BETTER	BETTER	
		1407 PREFERRED																				BEST			BEST		
		1406 SUPERIOR																			BEST						

TROWEL CHART

All trowels measure: Width x Depth x Space Apart

Notch Size	Application	Item No.	Coverage
1/8" x 1/8" x 1/16" 	Carpet (polypropylene, woven)	49737, 10137-12	8.4-10.2 m ² per 3.78 liters 90-110 ft ² per gallon
1/8" x 1/8" x 1/8" 	Carpet (polypropylene, woven)	n/a	6-7 m ² per 3.78 liters 65-75 ft ² per gallon
3/32" x 3/32" x 3/32" 	Carpet (closed-celled urethane, Enhancer™), Carpet (vinyl backed broad-loom)	10-820, 10-833	9.3-11.2 m ² per 3.78 liters 100-120 ft ² per gallon
1/16" x 1/16" x 3/32" 	Felt-Back Sheet Vinyl, Vinyl Composition Tile, Fiberglass Sheet & Luxury Vinyl Tile	49736, 10121-12	14.9-16.7 m ² per 3.78 liters 160-180 ft ² per gallon
1/16" x 1/16" x 1/16" 	Felt-Back Sheet Vinyl, Carpet Tile, Vinyl Tile & Plank, Vinyl Tile Composition, Fiberglass Sheet & Luxury Vinyl Tile	10-810, 10-823, 10125, 10-180 (DOUBLE SIDED)	15.8-17.6 m ² per 3.78 liters 170-190 ft ² per gallon
1/16" x 1/32" x 1/32" 	Vinyl Tile & Plank, VCT over VCT	10-816, 10-829, 10-180 (DOUBLE SIDED)	20.4-22.3 m ² per 3.78 liters 220-240 ft ² per gallon
Medium Nap Roller 	Vinyl Tile & Plank, Carpet Tile (Vinyl-Backed)	n/a	Up to 27.9 m ² per 3.78 liters Up to 300 ft ² per gallon
3/16" x 5/32" 	Wall Base (4")	10033	36.5-45.7 lineal meters per 3.78 liters 36.5-45.7 m ² per 3.78 liters 120-150 lineal feet per gallon 45-50 ft ² per gallon
Snozzle Applicator 	Wall Base	10-981-25	15-18 lineal meters per 887 mL 40-60 lineal feet per 30 ounces
1/8" x 1/8" x 1/8" 	Wall Base, Prefinished Parquet	10123-12	30.5-45.7 lineal meters per 3.78 liters 6.5-7.4 m ² per 3.78 liters 100-150 lineal feet per gallon 70-80 ft ² per gallon
1/4" x 1/4" x 1/4" 	Prefinished Engineered Wood (1/2" thick) Solid Wood & Bamboo Flooring (1/2" thick)	49713QC, 10113Q	2.2-3.7 m ² per 3.78 liters 30-40 ft ² per gallon
1/4" x 1/4" x 1/4" 	Prefinished Engineered Wood (1/2" thick)	10142-12	4.2-5.1 m ² per 3.78 liters 45-55 ft ² per gallon
3/8" x 5/16" 	Wood Flooring (1/2" to 3/4" thick)	10143	2.2-2.8 m ² per 3.78 liters 25-30 ft ² per gallon
1/4" x 3/16" Tiger Tooth® 	Wood Flooring (1/2" thick)	10144	2.8-3.25 m ² per 3.78 liters 30-35 ft ² per gallon

The trowel notches shown are those typically recommended for the type of wall/flooring products being installed. They are normally the minimum size recommended. Consult wall/ flooring manufacturer for their specific trowel recommendation. Surface conditions (roughness and porosity of surface/substrate) type of product and backing of product will ultimately determine the required trowel notch size and coverage.

See our Tool Catalog online at www.qep.com for a complete listing of our Carpet, Tile, Stone, Laminate, Wood and Vinyl Installation Tools and Accessories.

The products and specifications listed in this catalog are current as of the printed date of this catalog and are subject to change.

Refer to product data sheet and material safety data sheet for additional information.



Roberts Company Canada, Ltd.
34 Hansen Road South
Brampton, Ontario L5A 4A8

www.robertsconsolidated.com

Customer Service: 800-840-9422

Technical Assistance: 905-791-4444

Access product data sheets, technical bulletins, warranties and SDS documents
24 hours a day, 7 days a week through our continuously updated website

