



SAFETY DATA SHEET

1. Identification

Product identifier Motor Medic Universal Power Steering Fluid with Stop Leak

Other means of identification

SDS number M2713
Part No. M2713, M2732, M2734, M2713ES, M2734ES
Tariff code 3819.00.0090

Recommended use Power Steering Fluid

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name RSC Chemical Solutions
Address 600 Radiator Road
Indian Trail, NC 28079
United States
Telephone Customer Service: (704) 821-7643
Technical: (704) 684-1811
Website www.rscbrands.com
E-mail sds@rscbrands.com
Emergency phone number Emergency Telephone: (303) 623-5716
Emergency Contact: RMPDC (877) 740-5015

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3

Hazardous to the aquatic environment, long-term hazard Category 3

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Avoid release to the environment.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information 86.75% of the mixture consists of component(s) of unknown acute dermal toxicity.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|-----------|
| Distillates (petroleum), Hydrotreated Heavy Naphthenic | | 64742-52-5 | 80 - < 90 |
| Solvent Naphtha (petroleum), Light Arom. | | 64742-95-6 | 1 - < 3 |
| Trimethylbenzene | | 25551-13-7 | < 1 |
| 1,2,4-Trimethylbenzene | | 95-63-6 | < 0.3 |
| Kerosene (petroleum) Hydrodesulfurized | | 64742-81-0 | < 0.3 |
| 1,2,3-trimethylbenzene | | 526-73-8 | < 0.2 |
| Mesitylene; (1,3,5-trimethylbenzene) | | 108-67-8 | < 0.2 |
| BENZENE, DIMETHYL | | 1330-20-7 | < 0.1 |
| BENZENE,1-METHYLETHYL- | | 98-82-8 | < 0.1 |
| NAPHTHALENE | | 91-20-3 | < 0.1 |
| Other components below reportable levels | | | 10 - < 20 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|---|
| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. |
| Skin contact | Wash off with soap and water. Get medical attention if irritation develops and persists. |
| Eye contact | Rinse with water. Get medical attention if irritation develops and persists. |
| Ingestion | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. |
| Most important symptoms/effects, acute and delayed | Aspiration may cause pulmonary edema and pneumonitis. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | Move containers from fire area if you can do so without risk. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | No unusual fire or explosion hazards noted. |

6. Accidental release measures

| | |
|--|---|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Prevent product from entering drains. Stop the flow of material, if this is without risk. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. |

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---|------|-----------------------------------|-------|
| BENZENE, DIMETHYL (CAS 1330-20-7) | PEL | 435 mg/m3 | |
| BENZENE,1-METHYLETHY L- (CAS 98-82-8) | PEL | 100 ppm 245 mg/m3 | |
| Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5) | PEL | 50 ppm 5 mg/m3 | Mist. |
| NAPHTHALENE (CAS 91-20-3) | PEL | 2000 mg/m3 500 ppm 50 mg/m3 | |
| Solvent Naphtha (petroleum), Light Arom. (CAS 64742-95-6) | PEL | 10 ppm 400 mg/m3 | |
| | | 100 ppm | |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|---|------|-----------|---------------------|
| 1,2,3-trimethylbenzene (CAS 526-73-8) | TWA | 25 ppm | |
| 1,2,4-Trimethylbenzene (CAS 95-63-6) | TWA | 25 ppm | |
| BENZENE, DIMETHYL (CAS 1330-20-7) | STEL | 150 ppm | |
| BENZENE,1-METHYLETHY L- (CAS 98-82-8) | TWA | 100 ppm | |
| Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5) | TWA | 50 ppm | |
| Kerosene (petroleum) Hydrodesulfurized (CAS 64742-81-0) | TWA | 5 mg/m3 | Inhalable fraction. |
| Mesitylene; (1,3,5-trimethylbenzene) (CAS 108-67-8) | TWA | 200 mg/m3 | Non-aerosol. |
| NAPHTHALENE (CAS 91-20-3) | TWA | 25 ppm | |
| Trimethylbenzene (CAS 25551-13-7) | TWA | 10 ppm | |
| | | 25 ppm | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|--|-------------|---|-------|
| 1,2,3-trimethylbenzene (CAS 526-73-8) | TWA | 125 mg/m3 | |
| 1,2,4-Trimethylbenzene (CAS 95-63-6) | TWA | 25 ppm 125 mg/m3 | |
| BENZENE,1-METHYLETHYL- (CAS 98-82-8) | TWA | 25 ppm 245 mg/m3 | |
| Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5) | Ceiling | 50 ppm 1800 mg/m3 | |
| Kerosene (petroleum) Hydrodesulfurized (CAS 64742-81-0) | STEL TWA | 10 mg/m3 100 mg/m3 | Mist. |
| Mesitylene; (1,3,5-trimethylbenzene) (CAS 108-67-8) | TWA | 125 mg/m3 | |
| NAPHTHALENE (CAS 91-20-3) | STEL | 25 ppm 75 mg/m3 | |
| Solvent Naphtha (petroleum), Light Arom. (CAS 64742-95-6) | TWA | 15 ppm 50 mg/m3 10 ppm 400 mg/m3 | |
| | | 100 ppm | |

Biological limit values

ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time |
|--------------------------------------|---------|-------------------------|------------------------|---------------|
| BENZENE, DIMETHYL (CAS 1330-20-7) | 1.5 g/g | Methylhippuric acids | Creatinine in urine | * |

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.
 NAPHTHALENE (CAS 91-20-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Skin designation applies.

US - Tennessee OELs: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Kerosene (petroleum) Hydrodesulfurized (CAS 64742-81-0) Can be absorbed through the skin.
 NAPHTHALENE (CAS 91-20-3) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) or a face shield. Face shield is recommended.

| | |
|---------------------------------------|---|
| Skin protection | |
| Hand protection | Wear appropriate chemical resistant gloves. |
| Other | Wear suitable protective clothing. |
| Respiratory protection | Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded. Dust mask. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties

| | |
|---|---------------------------------------|
| Appearance | Liquid Clear. |
| Physical state | Liquid. |
| Form | Liquid. |
| Color | Yellow. |
| Odor | Naphthenic |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | -20 °F (-28.89 °C) estimated |
| Initial boiling point and boiling range | 500 °F (260 °C) estimated |
| Flash point | > 205.0 °F (> 96.1 °C) Tag Closed Cup |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | Not available. |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | 600 °F (315.56 °C) estimated |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Density | 7.42 lbs/gal |
| Explosive properties | Not explosive. |
| Flammability class | Combustible IIIB estimated |
| Oxidizing properties | Not oxidizing. |
| Percent volatile | 0.04 % estimated |
| Refractive index | 1.49 |
| Specific gravity | 0.89 |
| VOC | 0.04 % estimated |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | Prolonged inhalation may be harmful. |
| Skin contact | No adverse effects due to skin contact are expected. |
| Eye contact | Direct contact with eyes may cause temporary irritation. |
| Ingestion | Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. |

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

| Components | Species | Test Results |
|--------------------------------------|----------------|---------------------|
| 1,2,4-Trimethylbenzene (CAS 95-63-6) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 3160 mg/kg |
| BENZENE, DIMETHYL (CAS 1330-20-7) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | 3523 - 8600 mg/kg |
| BENZENE,1-METHYLETHYL- (CAS 98-82-8) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | 1400 mg/kg |
| NAPHTHALENE (CAS 91-20-3) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 2 g/kg |
| Oral | | |
| LD50 | Rat | 490 mg/kg |

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

| | |
|--------------------------------------|---|
| BENZENE, DIMETHYL (CAS 1330-20-7) | 3 Not classifiable as to carcinogenicity to humans. |
| BENZENE,1-METHYLETHYL- (CAS 98-82-8) | 2B Possibly carcinogenic to humans. |
| NAPHTHALENE (CAS 91-20-3) | 2B Possibly carcinogenic to humans. |

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

| | |
|--------------------------------------|--|
| BENZENE,1-METHYLETHYL- (CAS 98-82-8) | Reasonably Anticipated to be a Human Carcinogen. |
| NAPHTHALENE (CAS 91-20-3) | Reasonably Anticipated to be a Human Carcinogen. |

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

| Components | | Species | Test Results |
|---|------|--|------------------------------|
| 1,2,4-Trimethylbenzene (CAS 95-63-6) | | | |
| Aquatic | | | |
| Fish | LC50 | Fathead minnow (<i>Pimephales promelas</i>) | 7.19 - 8.28 mg/l, 96 hours |
| BENZENE, DIMETHYL (CAS 1330-20-7) | | | |
| Aquatic | | | |
| Fish | LC50 | Bluegill (<i>Lepomis macrochirus</i>) | 7.711 - 9.591 mg/l, 96 hours |
| BENZENE,1-METHYLETHYL- (CAS 98-82-8) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Brine shrimp (<i>Artemia</i> sp.) | 3.55 - 11.29 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) | 2.7 mg/l, 96 hours |
| Mesitylene; (1,3,5-trimethylbenzene) (CAS 108-67-8) | | | |
| Aquatic | | | |
| Fish | LC50 | Goldfish (<i>Carassius auratus</i>) | 9.89 - 15.05 mg/l, 96 hours |
| NAPHTHALENE (CAS 91-20-3) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (<i>Daphnia magna</i>) | 1.09 - 3.4 mg/l, 48 hours |
| Fish | LC50 | Pink salmon (<i>Oncorhynchus gorbuscha</i>) | 1.11 - 1.68 mg/l, 96 hours |
| Solvent Naphtha (petroleum), Light Arom. (CAS 64742-95-6) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (<i>Daphnia pulex</i>) | 2.7 - 5.1 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) | 8.8 mg/l, 96 hours |
| | | | 8.8 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

| | |
|------------------------|------------|
| BENZENE, DIMETHYL | 3.12 - 3.2 |
| BENZENE,1-METHYLETHYL- | 3.66 |
| NAPHTHALENE | 3.3 |

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number Not available.

UN proper shipping name Consumer commodity, MARINE POLLUTANT (RMM27HCOMPB Power Steering Comp, Solvent Naphtha (Petroleum) Light Aromatic)

Transport hazard class(es)

Class ORM-D

Subsidiary risk -

Label(s) None

Packing group Not available.

Environmental hazards

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging exceptions 156, 306

Packaging non bulk 156, 306

Packaging bulk None

IATA

UN number UN3082

UN proper shipping name Environmentally Hazardous Substance, Liquid, N.O.S.

Transport hazard class(es)

Class 9

Subsidiary risk -

Label(s) 9

Packing group Not available.

Environmental hazards Yes

ERG Code 9L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Distillates (petroleum), Hydrotreated Heavy Naphthenic), MARINE POLLUTANT (Solvent Naphtha (Petroleum) Light Aromatic)

Transport hazard class(es)

Class 9

Subsidiary risk -

Packing group III

Environmental hazards

Marine pollutant Yes

EmS F-A, S-F

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Solvent Naphtha (Petroleum) Light Aromatic
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

IATA; IMDG



Marine pollutant



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

| | |
|--------------------------------------|---------|
| BENZENE, DIMETHYL (CAS 1330-20-7) | Listed. |
| BENZENE,1-METHYLETHYL- (CAS 98-82-8) | Listed. |
| NAPHTHALENE (CAS 91-20-3) | Listed. |

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

| |
|------------------------|
| Immediate Hazard - Yes |
| Delayed Hazard - No |
| Fire Hazard - No |
| Pressure Hazard - No |
| Reactivity Hazard - No |

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. |
|---------------|------------|----------|
| NAPHTHALENE | 91-20-3 | < 0.1 |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE, DIMETHYL (CAS 1330-20-7)
 BENZENE,1-METHYLETHYL- (CAS 98-82-8)
 NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**BENZENE,1-METHYLETHYL- (CAS 98-82-8) Listed: April 6, 2010
NAPHTHALENE (CAS 91-20-3) Listed: April 19, 2002**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE, DIMETHYL (CAS 1330-20-7)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)
Kerosene (petroleum) Hydrodesulfurized (CAS 64742-81-0)
Mesitylene; (1,3,5-trimethylbenzene) (CAS 108-67-8)
NAPHTHALENE (CAS 91-20-3)
Solvent Naphtha (petroleum), Light Arom. (CAS 64742-95-6)**International Inventories**

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | No |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | No |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | No |
| New Zealand | New Zealand Inventory | No |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| | |
|----------------------|--|
| Issue date | 05-19-2015 |
| Revision date | 05-23-2017 |
| Version # | 05 |
| HMIS® ratings | Health: 3 Flammability: 0 Physical hazard: 0 |
| NFPA ratings | Health: 2 Flammability: 0 Instability: 0 |

NFPA ratings**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

