

• TRUSTED QUALITY SINCE 1921 •



**RUST-OLEUM®  
HEAVY-DUTY DEGREASER**

**DESCRIPTION AND USES**

Rust-Oleum® Heavy-Duty Degreaser is formulated to clean grease and oil stains from concrete surfaces and is recommended for use prior to painting, staining and sealing. Use at full strength to clean tough grease and oil stains, transmission & brake fluids, gasoline, anti-freeze and other stains from concrete surfaces.

For general purpose cleaning, add 1 quart (32 oz.) of degreaser to 1 gallon (128 oz.) of water and mix thoroughly before cleaning. To keep your painted floor looking great, wash with 1 cup (8 oz.) of degreaser added to 1 gallon (128 oz.) of water.

Heavy-Duty Degreaser is suitable for use on bare concrete surfaces, including garage floors, basements, driveways, sidewalks, porches, patios and stairs.

**FEATURES**

- Concentrated formula promotes adhesion of paints, stains & sealers
- Use on garages, basements, driveways, sidewalks, patios & more
- Environmentally friendly, will not hurt grass or plants
- For interior and exterior use

**PRODUCT**

SKU	Container Size
214382	1-Gallon Heavy-Duty Degreaser

**PRODUCT APPLICATION**

**PREPARATION**

Newly poured concrete must cure for a minimum of 30 days prior to cleaning or coating. Wear protective clothing and eyewear when applying product. Wipe up excess oil and grease spills. Scrape and sweep away dirt and loose contaminants on surface.

**PRODUCT APPLICATION (cont.)**

**MIXING INSTRUCTIONS**

Use Rust-Oleum heavy-Duty Degreaser at full strength to clean tough stains. Dilute 1:4 [1 qt. (32 oz.) degreaser in 1 gal. (128 oz.) water] for general purpose cleaning. To keep your painted floor looking great, dilute 1:16 [1 cup (8 oz.) degreaser in 1 gal. (128 oz.) water]. Stir diluted solution thoroughly. Avoid splashing.

DILUTION TABLE	
Tough Stains	Full Strength
General Purpose Cleaning	1 qt. (32 oz.) degreaser in 1 gal. (128 oz.) of water
Painted Surfaces	1 cup (8 oz.) degreaser in 1 gal. (128 oz.) of water

**APPLICATION**

Wet the surface first by spraying with a garden hose. Then apply the product (full strength for tough stains, diluted for general purpose cleaning and painted floors) and thoroughly scrub the surface with a stiff bristle brush or broom. Wait 10-15 minutes while Rust-Oleum Heavy-Duty Degreaser lifts stains from the surface. Wipe up excess degreaser with rags or paper towels to keep contaminants from spreading. Rinse thoroughly with fresh water. Repeat applications may be necessary for difficult stains. Remove excess water with a squeegee or mop.

**STORAGE & DISPOSAL**

Store at room temperature. Keep container closed when not in use. Dispose of container and/or unused contents in accordance with local, state and federal regulations.

**PROTECT FROM FREEZING**

**KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.**

**TECHNICAL DATA**

**RUST-OLEUM® HEAVY-DUTY DEGREASER**

**PHYSICAL PROPERTIES**

<b>Composition</b>		Surfactants and Water
<b>Weight</b>	<b>Per Gallon</b>	8.4 lbs.
	<b>Per Liter</b>	1.01 kg
<b>Solids</b>	<b>By Weight</b>	<5%
	<b>By Volume</b>	<5%
<b>pH</b>		13+
<b>Volatile Organic Compounds</b>		0 g/l
<b>Dry Times @ 70-80° F (21-27°C) and 50% Relative Humidity</b>		Allow to dry for 24 hours before staining, sealing or coating
<b>Shelf Life</b>		NA
<b>Flash Point</b>		>200°F (93°C)
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.