

THINNER	TECHNICAL DATA	ATO-60
	ACETONE	

DESCRIPTION AND USES

Rust-Oleum® Acetone is the strongest and fastest evaporating solvent available. It is recommended for thinning many types of epoxy and fiberglass resins. It will soften plastic, plexiglass, linoleum, latex paint, synthetic fabrics, asphalt and tar. It can be used as a special purpose thinner, cleaner and remover. It is not recommended for most conventional oil-based paints, stains, varnishes or lacquers.

PRODUCTS

SKU	Description
248667	1-Quart
248668	1-Gallon

PRODUCT APPLICATION

SURFACE PREPARATION

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Use outdoors or in a well ventilated area such as an open garage. Use with caution on any type of rubber, plastic, asphalt tile, linoleum or synthetic fabric. Acetone is extremely flammable. Do not use as a cleaner or degreaser to remove linoleum tile adhesive or carpet adhesive. For uses of this type, use a non-flammable product

PHYSICAL PROPERTIES

Physical Properties		ACETONE
Solvent Type		Ketone
Weight	Per Gallon	6.60 lbs.
	Per Liter	0.79 kg
VOC		0 g/l
Shelf Life		5 years
Flash Point		-4°F (-20°C)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.