

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®
SPECIALTY

SPECIALTY
METALLIC SPRAYS

DESCRIPTION AND USES

Rust-Oleum® Specialty Metallic sprays provide a rich, brilliant finish on wood, metal, and more. These sprays add a shiny metallic look to picture frames, candle holders, holiday crafts, and much more. This leafing metallic is designed for use on interior decorative items only.

PRODUCTS

SKU	Description
1910830	Gold
1915830	Silver
1936830	Brass
1937830	Copper

PAINTING CONDITIONS

Use outdoors or in a well ventilated area. Use when temperature is between 50-90°F (10-32°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces, when heated, exceed 200°F (93°C). Do not apply to galvanized steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

PRODUCT APPLICATION

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile.

WARNING! LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you sand, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Hold can upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can in motion while spraying. Keep the can the same distance from the surface. Apply two or more light coats a few minutes apart to avoid drips and runs. Metallic sprays are not recommended for outdoor use. **Do not use near open flame.**

DRY & RECOAT

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 15 minutes, to handle in 30 minutes and is fully dry in 24 hours. Apply a second coat within 1 hour or after 24 hours. A clear coat finish is not recommended.

CLEAN-UP

Clean valve immediately after use by turning can upside down and depressing the spray button for 3-5 seconds (some paint will be sprayed out, so be careful to not inadvertently spray yourself or other objects). Clean up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

TECHNICAL DATA

METALLIC SPRAY

PHYSICAL PROPERTIES

Physical Properties		METALLIC SPRAYS
Resin Type		Solvent Acrylic
Pigment Type		Varies with color
Solvents		Acetone, Toluene, Xylene
MIR		1.25 Max
Fill Weight		11 ounces
Practical Coverage at Recommended DFT (assumes 15% material loss)		Approximately 10-12 sq.ft./can (0.9-1.09 m ² /can)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	15 minutes
	Handle	30 minutes
	Recoat	Within 1 hour or after 24 hours
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Flash Point		-156°F (-104°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.