



**AMERICAN ACCENTS®  
DECORATIVE PAINT PEN**

**DESCRIPTION AND USES**

Rust-Oleum® American Accents® Decorative Paint Pens are designed to decorate and personalize items around the home such as picture frames, candy jars, vases, storage bins, greeting cards, candle holders and more. Use on wood, metal, glass, unglazed ceramic, paperboard and some plastics. The Decorative Paint Pen is suitable for used outdoors on mailboxes, planters and birdhouses.

**PERFORMANCE CHARACTERISTICS**

- Easy to use with excellent coverage
- Rich satin finish
- Durable and permanent
- Special chisel tip for broad or narrow lines
- Dries to the touch in 15-30 minutes

**PRODUCTS**

<b>SKU (1/3 fl. oz.)</b>	<b>Description</b>
215123	Black
215153	White
215154	Ruby
215155	Sapphire
215156	Buttercup
215157	Bayberry
222644	Espresso

**PRODUCT APPLICATION**

**PAINTING CONDITIONS**

Apply only when air and surface temperatures are above 50-90°F (10-32°C) and humidity is below 85% to ensure proper drying.

**DIRECTIONS**

Hold cap in place and shake paint pen for 30 seconds. Twist and remove cap. Lightly depress tip several times on scrap paper to start paint flow. Recap and shake as needed. When finished, replace cap tightly and store on side.

**DRY & RECOAT TIMES**

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 15-30 minutes, dry to handle in 1 hour, and fully dry in 2-4 hours.

**CLEAN-UP**

Wipe up spills and excess with mineral spirits.

**TECHNICAL DATA**

**AMERICAN ACCENTS® DECORATIVE PAINT PEN**

**PHYSICAL PROPERTIES**

		<b>PAINT PEN</b>
<b>Resin Type</b>		Polystyrene Modified Alkyd
<b>Pigment Type</b>		Varies with color
<b>Solvents</b>		Mineral Spirits
<b>Specific Gravity</b>		1.12
<b>Volatile Organic Compounds</b>		<230 g/l
<b>Recommended Dry Film Thickness (DFT) per Coat</b>		NA
<b>Practical Coverage at Recommended DFT (assumes 15% material loss)</b>		Varies with surface type and porosity
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	<b>Touch</b>	15-30 minutes
	<b>Handle</b>	1 hour
	<b>Fully Dry</b>	2-4 hours
<b>Shelf Life</b>		3 years
<b>Flash Point</b>		<70°F (21°C)
<b>Safety Information</b>		For more information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.