



**PAINTER'S TOUCH  
ULTRA COVER 2X ENAMEL BRUSH**

**DESCRIPTION AND USES**

Rust-Oleum® Painter's Touch® Ultra Cover 2X Enamels provides long lasting protection and durability. This enamel offers excellent coverage, chip resistance and color retention. For even longer, lasting protection, use a Painter's Touch® Primer first.

**PRODUCTS**

**Gloss Finish Unless Otherwise Noted**

<b>QUARTS</b>	<b>½ PINTS</b>	<b>DESCRIPTION</b>
1922502	1922730	Navy Blue
1938502	1938730	Hunter Green
1945502	1945730	Sun Yellow
1964502	1964730	Colonial Red
1966502	1966730	Apple Red
1974502	1974730	Semi-Gloss Black
1976502	1976730	Flat Black
1977502	1977730	Kona Brown
1979502	1979730	Black
1986502	1986730	Dark Gray
1990502	1990730	Flat White
1992502	1992730	White
1993502	1993730	Semi-Gloss White
1994502	1994730	Gloss Almond
224428T	224423	Deep Blue
240286		Satin Claret Wine
240284	240290	Nutmeg
242018	242054	Espresso
240285		Heirloom White
242057		Clear
*258203		Aged Copper
*254100	*240288	Metallic Silver
*254079	*240287	Metallic Gold
*254101		Oil Rubbed Bronze

\*Oil-modified Alkyds

**PAINTING CONDITIONS**

Apply only when air and surface temperatures are above 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying.

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent or other suitable cleaning method. Rinse thoroughly with fresh water and allow to fully dry. All surfaces must be dry at time of application. Scrape and wire brush or power tool clean to remove loose rust, scale and deteriorated previous coatings.

Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile. The Painter's Touch® Enamels are compatible with most coatings, but a test patch is suggested. **WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).



## TECHNICAL DATA

# PAINTER'S TOUCH ULTRA COVER 2X ENAMEL BRUSH

### PRODUCT APPLICATION (cont.)

#### PRIMING

Use of Painter's Touch® Primer provides a sound base for topcoat adhesion and is especially recommended for bare wood and metal. The following primers are recommended.

1980502      Gray Primer  
224430T      Black Primer

#### APPLICATION

Before using, stir thoroughly to ensure any settled pigment is re-dispersed. Thinning is not required. In hot, dry conditions, thin with up to 2 ounces of water per quart to extend dry time. Avoid painting in direct sunlight or on hot surfaces. Use a good quality synthetic brush. Avoid excessive brushing as this will reduce film thickness and protection. Use light even strokes to ensure smooth and uniform flow.

#### DRY & RECOAT TIMES

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 30 minutes, dry to handle in 1 hour, and fully dry in 2-4 hours. Primers may be top coated after 2-4 hours.

#### CLEAN-UP

Clean brush and other application tools immediately with soap and water.



## TECHNICAL DATA

# PAINTER'S TOUCH ULTRA COVER 2X ENAMEL BRUSH

### PHYSICAL PROPERTIES

	High Gloss	Satin	Flat	Solvent Metallic
<b>Resin Type</b>	Water-based Acrylic	Water-based Acrylic	Water-based Acrylic	Oil-based Alkyd
<b>Pigment Type</b>	Varies with Color	Varies with Color	Varies with Color	Leafing Aluminum, Gold Metallic
<b>Solvents</b>	Water, Glycol Ethers	Water, Glycol Ethers	Water, Glycol Ethers	Aromatic Hydrocarbons, Xylene
<b>Weight - per Gallon</b>	8.6-11.8 lbs.	9.0-10.2 lbs.	9.8-11.8 lbs.	7.6-8.5 lbs.
<b>per Liter</b>	1.03-1.41 kg	1.08-1.22 kg	1.17-1.41 kg	0.91- 1.02 kg
<b>Solids by Weight</b>	33.2-58.3%	32.3-42.8%	43.0-58.3%	45.7-60.2%
<b>Solids by Volume</b>	31.0-41.1%	26.6-30.1%	32.6-41.1%	36.3-48.6%
<b>Volatile Organic Compounds</b>	<200 g/l 1.67 lbs./gal.	<180 g/l 1.50 lbs./gal.	<190 g/l 1.70 lbs./gal.	<500 g/l 4.20 lbs./gal.
<b>Recommended Dry Film Thickness (DFT) per Coat</b>	1.5 - 2.5 mils (37.5-62.5µ)	1.5-2.5 mils (37.5-62.5µ)	1.5-2.5 mils (37.5-62.5µ)	1.0-1.5 mils (25-37.5µ)
<b>Wet Film to Achieve DFT (unthinned material)</b>	5.0-6.0 mils (125-150µ)	5.0-9.0 mils (125-225µ)	3.5-7.5 mils (87.5-187.5µ)	2.0-4.0 mils (50-100µ)
<b>Theoretical Coverage at 1 mil DFT (25µ)</b>	124-165 sq.ft./qt. (3.0-4.1 m <sup>2</sup> /l)	106-120 sq.ft./qt. (2.6-3.0 m <sup>2</sup> /l)	130-165 sq.ft./qt. (3.2-4.1 m <sup>2</sup> /l)	146-195 sq.ft./qt. (3.6-4.8 m <sup>2</sup> /l)
<b>Practical Coverage at Recommended DFT (assumes 15% material loss)</b>	40-90 sq.ft./qt. (1.0-2.2 m <sup>2</sup> /l)	35-70 sq.ft./qt. (0.9-1.7 m <sup>2</sup> /l)	45-95 sq.ft./qt. (1.1-2.3 m <sup>2</sup> /l)	80-165 sq.ft./qt. (2.0-4.0 m <sup>2</sup> /l)
<b>Dry Times at 77°F (25°C) and 50% Relative Humidity</b>				
<b>Touch</b>	30 minutes	30 minutes	30 minutes	2-4 hours
<b>Handle</b>	1 hour	1 hour	1 hour	5-9 hours
<b>Recoat</b>	2-4 hours	2-4 hours	2-4 hours	After 24 hours
<b>Dry Heat Resistance</b>	200°F (93°C)	200°F (93°C)	200°F (93°C)	200°F (93°C)
<b>Shelf Life</b>	5 years	5 years	5 years	5 years
<b>Flash Point</b>	>200°F (93°C)	>150°F (66°C)	>150°F (66°C)	80°F (27°C)
<b>Safety Information</b>	For additional information, see MSDS			

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.