



# ANTI-SLIP AEROSOL

## DESCRIPTION AND USES

Anti-slip aerosols provide a slip resistant surface for most interior/exterior metal, concrete, ceramic and wood surfaces. These aerosols apply easily and provide uniform coverage with a low-luster. They dry to a tough, durable finish that resists peeling and cracking while providing resistance to gasoline, oil and other harsh substances.

Use anti-slip aerosols wherever a slip-resistant surface is desired. Ideal for use on stairs, pool decks, ramps, walkways and much more.

## PRODUCTS

270610 Clear

## PACKAGING

6 aerosols 340g. (15 fl. oz. container) per carton.

## PRODUCT APPLICATION

### SURFACE PREPARATION

**ALL SURFACES:** Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with EpoxyShield Heavy Duty Cleaner N266001, commercial detergent or other suitable cleaner. Mold and mildew must be cleaned with a chlorinated cleaner or bleach solution. Rinse with fresh water and allow to dry.

**STEEL:** Hand tool (SSPC-SP-2) or power tool (SSPC-SP-3) clean to remove loose rust, mill scale, and deteriorated previous coatings.

**PREVIOUSLY COATED:** Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile. Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead.

### APPLICATION

Apply only when air and surface temperatures are between 0-38°C (50-100°F) and surface temperature is at least 5°F above dew point.

## TECHNICAL DATA

# ANTI-SLIP AEROSOL

### PHYSICAL PROPERTIES

		ANTI-SLIP AEROSOL
Resin Type		Chain Stop Alkyd
Pigments Type		NONE
Solvents		Acetone, Xylene, Toluene
Volatile Organic Compounds		Max VOC 80% (meets CA standards)
MIR		Maximum value of 2.45
Fill Weight		340g. (15 oz.)
Solids by weight		18-25% (varies by color)
Recommended Dry Film Thickness (DFT) per Coat		1.0-2.0 mils (25-50µ)
Coefficient of Friction	Dry	0.72
	Wet	0.85
Practical Coverage at Recommended DFT (assumes 15% material loss)		Approximately 1.3 m <sup>2</sup> (14 ft. <sup>2</sup> )
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Tack Free	N/A
	Walk-on	24-48 hours
	Recoat	1-2 hours
Dry Heat Resistance		79°C (175°F)
Shelf Life		5 years
Specification and Performance Alternatives		USDA acceptable
Safety Information	Contains	<p><b>THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. DANGER! EXTREMELY FLAMMABLE. MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL. FOR INDUSTRIAL OR COMMERCIAL USE ONLY. REFER TO MATERIAL SAFETY DATA SHEET AND LITHOGRAPHED CANS FOR MORE COMPLETE SAFETY INFORMATION.</b></p>
	Warning!	

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.