



ROCKSOLID® HEAVY DUTY CLEANER

DESCRIPTION AND USES

RockSolid® Heavy Duty Cleaner is formulated to clean grease and oil stains on concrete, brick and masonry. It also prepares surfaces for finishing by promoting adhesion when staining, sealing or coating. RockSolid Heavy Duty Cleaner is suitable for interior and exterior use and is safe to use near grass and plants.

RockSolid Heavy Duty Cleaner is suitable for use on garage floors, basements, driveways, carports, patios, walkways and pool decks prior to staining, sealing or coating. It can be used on freshly poured concrete.

PRODUCTS

SKU	Container Size
293422	1-Gallon Heavy Duty Cleaner

PRODUCT FEATURES

- Removes oil, grease, tire marks, dirt and stains
- Cleans surface prior to sealing
- Designed for use on concrete and masonry

PRODUCT APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

SURFACE PREPARATION

Proper surface preparation is critical to achieve best results. Wipe up excess oil and grease spots. Scrape and sweep away dirt and loose contaminants on the surface.

PRODUCT APPLICATION (cont.)

APPLICATION

RockSolid Heavy Duty Cleaner is ready to use. Do not thin. Use only when air (ambient) temperature is between 50-90°F (10-32°C) and the relative humidity is below 85%. Dampen the surface with water. Apply RockSolid Heavy Duty Cleaner to the entire floor and allow it to soak into the surface for 5-10 minutes, misting the surface as needed to keep it damp. Work the product into the surface with a stiff bristle brush or broom.

Rinse the surface thoroughly with water or power wash to remove all cleaner residue. Note: If cleaner dries before rinsing, apply more cleaner and then scrub and rinse. Use a squeegee or broom to remove excess water from the surface. A wet/dry shop vacuum can be used. Repeat the application as needed for hard-to-remove stains.

COVERAGE

Each gallon will cover 200 square feet per gallon.

DRY TIME

Dry time is based on 70°F and 50% relative humidity. Allow to dry for 24 hours before staining, sealing or coating.

CLEAN-UP

Wash tools and equipment with soap and warm water. Properly dispose of all soiled rags and protect unused product from freezing.

DANGER: CAUSES BURNS TO EYES, SKIN AND IS A RESPIRATORY IRRITANT. HARMFUL IF SWALLOWED.

KEEP OUT OF REACH OF CHILDREN.



TECHNICAL DATA

ROCKSOLID® HEAVY DUTY CLEANER

PHYSICAL PROPERTIES

Composition		Citrus Based Liquid
Solvent		Glycol Ethers, Water
Weight	Per Gallon	8.4 lbs.
	Per Liter	1.01 kg
Volatile Organic Compounds		0 g/l
Practical Coverage at Recommended DFT		Up to 200 sq.ft./gal.
Dry Times @ 70-80° F (21-27°C) and 50% Relative Humidity		Allow to dry for 24 hours before staining, sealing or coating
Shelf Life		3 years
Flash Point		>200°F (93°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.