

• TRUSTED QUALITY SINCE 1921 •



ROOF ACCESSORY COATING

DESCRIPTION AND USES

Rust-Oleum® Roof Accessory Coating creates a durable, weather-resistant finish that can be applied to stacks, vents and other roof penetrations. Roof Accessory Coating protects and matches a variety of roof accessories and can be applied to wood, metal, masonry and plastic. Not for use on galvanized steel.

FEATURES

- Protects and matches roof accessories
- Adheres to metal, plastic, masonry and wood
- Durable weather resistant finish

PRODUCTS

SKU (12 ounces)	Description
302121	Weathered Wood
302122	Rustic Slate
302123	Dark Gray
302124	Shakewood
302125	Espresso Shake
302126	Carbon Black
313815	Red Tile
314061	Cedar

PRODUCT APPLICATION

PAINTING CONDITIONS

Use outdoors or in a well ventilated area such as an open garage. Use when the temperature is between 50-90°F (10-32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F (93°C) or on galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

SURFACE PREPARATION

Remove all dirt, grease, oil, and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION

APPLICATION

Shake can vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle, DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold the can upright 10-16" from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface and keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart.

DRY & RECOAT TIMES

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Dries to the touch in 20 minutes, to handle in 1 hour and is fully dry in 24 hours. Apply a second coat or clear coat within 1 hour or after 48 hours. Apply a clear coat in 2-3 light coats a few minutes apart. NOTE: On plastic, maximum paint adhesion and durability is achieved in 5-7 days.

CLEAN-UP

When finished spraying, wipe off tip before storing. Clean up wet paint with xylene or mineral spirits. Dispose of empty can in recycle pickup. Do not burn or place in home trash compactor.

CLOGGING

If valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not stick pin or other object into the stem.

TECHNICAL DATA

ROOF ACCESSORY COATING

PHYSICAL PROPERTIES

		ROOF ACCESSORY COATING
Resin Type		Modified Alkyd Resin
Pigment Type		Varies with color
Solvents		Acetone, Hydrotreated Light Distillate, n-Butane, Naphtha, Xylene
MIR		1.00 Max
Fill Weight		12 ounces
Recommended Dry Film Thickness (DFT) Per Coat		1.0-2.5 mils (25-62.5μ)
Wet Film to Achieve DFT		Varies depending on porosity and texture of surface
Practical Coverage at Recommended DFT		10-12 sq.ft./can (0.9-1.1 m ² /can)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	20 minutes
	Handle	1 hour
	Recoat	Within 1 hour or after 48 hours
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Flash Point		-141°F (-96°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.