

• TRUSTED QUALITY SINCE 1921 •

**RUST-OLEUM®**  
INDUSTRIAL  
— CHOICE —

# INDUSTRIAL CHOICE® LIVESTOCK MARKING PAINT

## DESCRIPTION AND USES

Create ultra-crisp, long-lasting marks with Industrial Choice® Water-Base Inverted Livestock Marking Paint. This water-based formula creates easy-to-read markings in bright, durable colors, for use in heat detection tail painting and general livestock identification applications.

## PRODUCT FEATURES

- Safe for all livestock
- Weather resistant
- Easy to read
- Fast drying

## PRODUCTS

SKU	DESCRIPTION
383005	Fluorescent Red
383006	Fluorescent Orange
383007	Fluorescent Green
383018	Fluorescent Pink
383019	Fluorescent Blue
383020	Fluorescent Yellow
383021	Fluorescent Purple

## PACKAGING

17 fl. oz. fill weight, 12 aerosols/carton.

## PRODUCT APPLICATION

### SURFACE PREPARATION

Remove any excess dirt or debris prior to application.

### APPLICATION

Use when temperature is 40-90°F (10-32°C) and humidity is below 85% to ensure proper drying. This product can be used down to 25°F (-4°C) which may result in a slight reduction of delivery rate. Overspray can carry a significant distance. Shake can vigorously for one minute after mixing ball is heard. DO NOT STRIKE CAN. Hold can 4 to 10 inches from surface to be marked. Press spray tip sideways to spray. Keep can moving to prevent build-up. Clean valve by spraying upright for 2-3 seconds after each use. If valve clogs, carefully remove spray tip and clean in thinner. Do not insert any object into can or valve.

When used as directed, Industrial Choice Livestock Marking Paint will cause no lasting harm, nor significant irritation to the skin of the animal, namely livestock, upon which it is applied as a temporary marker.

### CLEAN-UP

Wipe off spray tip when finished using. Properly discard empty container. Do not burn or place in trash compactor. Empty container can be recycled.

<b>AEROSOLS</b>	<b>TECHNICAL DATA</b>	<b>IC-48</b>
• TRUSTED QUALITY SINCE 1921 • <b>RUST-OLEUM®</b> INDUSTRIAL — CHOICE —	<b>INDUSTRIAL CHOICE®</b> <b>LIVESTOCK MARKING PAINT</b>	

**PHYSICAL PROPERTIES**

	LIVESTOCK MARKING PAINT
<b>Resin Type</b>	Modified Alkyd
<b>Pigment Type</b>	Varies with color
<b>Solvents</b>	Acetone, Xylene, and Toluene
<b>MIR</b>	Maximum value of 0.80
<b>Fill Weight</b>	17 oz.
<b>Practical Coverage</b>	Approximately 600-700 linear feet at 1 inch wide
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	Less than 15 minutes
<b>Shelf Life</b>	5 years
<b>Safety Information</b>	For additional information, see SDS

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.