



# RUST-OLEUM® AIRCRAFT REMOVER AEROSOL

## DESCRIPTION AND USES

Rust-Oleum® Aircraft Remover is fast-acting and will efficiently remove all types of finish from metal surfaces of automobiles and trucks. Effective on acrylics, lacquers, polyurethanes and baked enamels. Non-corrosive to all common metals under normal exposure time.

**NOTE:** Depending on the type and thickness of previous coatings to be stripped, application times or number of applications of stripper may vary. This product may not be compatible with all surfaces and all conditions surrounding application. Before applying to any surface, always test product in a small, inconspicuous area to ensure no damage will result. Not recommended for use on fiberglass, plastics, or any other synthetic surfaces.

## PRODUCT

SKU	DESCRIPTION (AEROSOL)
352969	Air Craft Remover

## PRODUCT APPLICATION

**READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT**

### APPLICATION CONDITIONS

Protect hands with solvent-resistant gloves and eyes with chemical splash goggles. **ONLY USE OUTDOORS OR IN A WELL VENTILATED AREA.** Do not use in small, enclosed areas where vapors can accumulate and concentrate. If sensitive to organic vapors, use a NIOSH approved gas and vapor respirator.

Use when temperature is between 65-90°F (18-32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

## PRODUCT APPLICATION (cont.)

### APPLICATION

1. Remove or protect any portions of the vehicle not being stripped.
2. Mask seams and trim openings as this will prevent bleed-back stripping of new finish.
3. Shake well. Hold can in an upright position and point arrow on top of button away from you. Spray at a distance of approximately 12" to 18" from surface. To avoid sagging on vertical surfaces, use a back and forth motion to apply a generous, even coat.
4. Let the stripper stand until finish is completely blistered or liquefied; the time will vary from 20 to 45 minutes or longer.
5. After 20 minutes, test a small area to see if old finish is ready for removal. The loosened finish may be removed with a flexible plastic scraper. Multiple coats may require repeat application. If paint has not bubbled, surface must be kept wet with stripper. Do not allow to dry out.
6. Remove paint with a flexible plastic scraper, and then clean with mineral spirits soaked rag to remove any residue. Allow surface to dry before applying a new finish. Prime metal as soon as possible to prevent flash rust.
7. If the product experiences sputtering, place at room temperatures to achieve desired performance.

### CLOGGING

If valve clogs, twist and pull off spray tip. Rinse it with a solvent such as xylene. Place the can in a warm ambient temperature (77°F) and allow it to reach equilibrium.



**RUST-OLEUM®  
AIRCRAFT REMOVER AEROSOL**

**PHYSICAL PROPERTIES**

		<b>AIRCRAFT REMOVER</b>
<b>Resin Type</b>		Contains Paraffin Wax
<b>Solvents</b>		1,3-Dioxolane, Dimethoxymethane, Methyl Acetate
<b>Weight</b>	<b>Per Gallon</b>	7.98 lb/gal.
	<b>Per Liter</b>	0.96 kg
<b>Volatile Organic Compounds</b>		<50% by weight
<b>Fill Weight</b>		18 oz.
<b>Practical Coverage Rate</b>		Varies by coating
<b>Shelf Life</b>		2 years
<b>Flash Point</b>		-42°F (-41°C)
<b>Safety Information</b>		See SDS

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.