SAFETY DATA SHEET



1. Identification

Telephone E-mail

Product identifier Rapid Set OnePass

Other means of identification

Product code 701010025, 701013000, 701020002, 701020009, 701990002, 701990009

Recommended use Industrial use.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name CTS Cement Manufacturing Corporation

Address 12442 Knott St.

Garden Grove, CA 92841

United States
1-800-929-3030
info@ctscement.com

Contact person Safety Officer

Emergency telephone 1-800-929-3030 (8 AM - 5 PM)

number

2. Hazard(s) identification

Physical hazards Not classified.

Health Hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Carcinogenicity Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. Suspected of causing cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye

protection/face protection.

Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and

wash before reuse. If exposed or concerned: Get medical advice/attention.

Storage Keep container tightly closed. Store in dry location.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Calcium Sulfoaluminate Cement	960375-09-1	40-50
Limestone	1317-65-3	40-50
Vinyl acetate	108-05-4	0-3

Rapid Set OnePass SDS US

922491 Version #: 02 Revision date: 24-October-2018 Issue date: 24-October-2018

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

If dust from the material is inhaled, remove the affected person immediately to fresh air. Call a

physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Ingestion

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately. Immediately rinse mouth and drink plenty of water. Call an ambulance and take these instructions.

Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

Indication of immediate

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Upper respiratory tract irritation. Coughing. Discomfort in the chest. Shortness of breath. Skin irritation.

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

General information

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Stop the flow of material, if this is without risk. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Collect dust using a vacuum cleaner. Minimize dust generation and accumulation. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains or water courses.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide appropriate exhaust ventilation at places where dust is formed. Minimize dust generation and accumulation. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store in dry location. Store away from incompatible materials (see Section 10 of the SDS).

Rapid Set OnePass SDS US

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	
Vinyl acetate (CAS 108-05-4)	STEL	15 ppm	
·	TWA	10 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	
Vinyl acetate (CAS 108-05-4)	Ceiling	15 mg/m3	
,		4 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses or safety goggles unless full face respirator is in use.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels Respiratory protection

exceeding the exposure limits.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Solid. Physical state Powder. **Form** Tan. Color Odor Low.

Odor threshold Not available. 11 - 12 when wet Melting point/freezing point Not applicable. Initial boiling point and boiling Not applicable.

range

Not applicable. Flash point **Evaporation rate** Not applicable. Flammability (solid, gas) Non combustible.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not applicable.

Flammability limit - upper Not applicable.

(%)

Vapor pressure Not applicable.

Rapid Set OnePass SDS US Vapor density Not applicable.

Relative density 2.7-3.1@ 20°C

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperature Not applicable.

Decomposition temperature 2462 °F (1350 °C)

Viscosity Not applicable.

Other information

Bulk density 60 lb/ft³ **VOC (Weight %)** 0 g/l

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the decomposition temperature. Contact with incompatible

materials. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).

Incompatible materials

Hazardous decomposition

Carbon oxides. Sulfur oxides.

Strong oxidizing agents.

products

11. Toxicological information

Information on likely routes of exposure

InhalationInhalation of dusts may cause respiratory irritation. Prolonged inhalation may be harmful.Skin contactCauses skin irritation. Prolonged contact with wet cement/mixture may cause burns.

Eye contact Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns.

Ingestion Swallowing may cause gastrointestinal irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Upper respiratory tract irritation.

Coughing. Discomfort in the chest. Shortness of breath. Skin irritation.

Information on toxicological effects

Acute toxicity May cause respiratory irritation.

Components Species Test Results

Vinyl acetate (CAS 108-05-4)

Acute Oral

LD50 Rat 2920 mg/kg

Skin corrosion/irritation

Serious eye damage/eye

Causes skin irritation.

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization No data available.

Skin sensitization No data available.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Vinyl acetate (CAS 108-05-4) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Rapid Set OnePass SDS US

Reproductive toxicity

Specific target organ toxicity -

single exposure

No data available. No data available.

Specific target organ toxicity -

repeated exposure

No data available.

Aspiration hazard

Due to the physical form of the product it is not an aspiration hazard.

Chronic effects No data available.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Vinyl acetate (CAS 108-05-4)

0.73

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

Not applicable.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Vinyl acetate (CAS 108-05-4) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Rapid Set OnePass SDS US

SARA 302 Extremely hazardous substance

Chemical name CAS number Reportable **Threshold** Threshold **Threshold** planning quantity, quantity planning quantity planning quantity,

Vinyl acetate 108-05-4

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. Vinyl acetate 108-05-4 0 - 3

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Vinyl acetate (CAS 108-05-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Vinyl acetate (CAS 108-05-4)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Vinyl acetate (CAS 108-05-4)

US. New Jersey Worker and Community Right-to-Know Act

Vinyl acetate (CAS 108-05-4)

US. Pennsylvania Worker and Community Right-to-Know Law

Vinyl acetate (CAS 108-05-4)

US. Rhode Island RTK

Vinyl acetate (CAS 108-05-4)

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

⚠ WARNING

CANCER and REPRODUCTIVE HARM - www.P65Warnings.ca.gov

International Inventories

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

upper value

lower value

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 24-October-2018 24-October-2018 **Revision date**

Version # 02

Health: 3* **HMIS®** ratings

Flammability: 0 Physical hazard: 0

Disclaimer CTS Cement Manufacturing Corporation cannot anticipate all conditions under which this

> information and its product, or the products of other manufacturers in combination with its product. may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper

use. The information in the sheet was written based on the best knowledge and experience

currently available.

Rapid Set OnePass SDS US

922491 Version #: 02 Revision date: 24-October-2018 Issue date: 24-October-2018