

## Paint Thinner

### SECTION 1. IDENTIFICATION

<b>Product Identifier</b>	Paint Thinner
<b>Other Means of Identification</b>	13-311, 13-314
<b>Recommended Use</b>	Please refer to Product label.
<b>Restrictions on Use</b>	None known.
<b>Manufacturer / Supplier</b>	Recochem Inc., 850 Montee de Liesse, Montreal, QC, H4T 1P4, Compliance and Regulatory Department, 905-878-5544, www.recochem.com
<b>Emergency Phone No.</b>	CANUTEC, 613-996-6666, 24 Hours
<b>SDS No.</b>	1608

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquid - Category 3; Acute toxicity (Inhalation) - Category 3; Skin corrosion/irritation - Category 2; Serious eye damage/eye irritation - Category 2A; Carcinogenicity - Category 2; Specific target organ toxicity (single exposure) - Category 3; Aspiration hazard - Category 1; Aquatic hazard (Acute) - Category 2

#### GHS Label Elements



Signal Word:  
Danger

#### Hazard Statement(s):

H226	Flammable liquid and vapour.
H331	Toxic if inhaled.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H336	May cause drowsiness or dizziness.
H401	Toxic to aquatic life.

#### Prevention:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames, and hot surfaces. – No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting, and other equipment.
P242	Use only non-sparking tools.

Product Identifier: Paint Thinner  
 SDS No.: 1608  
 Date of Preparation: November 11, 2015

P243 Take precautionary measures against static discharge. fume  
mist  
vapours  
spray  
P264 Wash hands and skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/eye protection/face protection.  
P273 Avoid release to the environment.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor.  
P331 Do NOT induce vomiting.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P312 Call a POISON CENTRE/doctor if you feel unwell.  
P332 + P313 If skin irritation occurs: Get medical advice/attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTRE/doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 Call a POISON CENTRE/doctor if you feel unwell.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P370 + P378 In case of fire: Use appropriate foam, carbon dioxide, dry chemical powder, water spray or fog to extinguish.

**Storage:**

Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

**Other Hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Hydrotreated kerosene	64742-47-8	60-100	
n-Nonane	111-84-2	1-5	

**Notes**

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

**SECTION 4. FIRST-AID MEASURES**

**First-aid Measures**

**Inhalation**

Take precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). Remove source of exposure or move to fresh air. Keep at rest in a position comfortable for breathing. Call a Poison Centre or doctor if you feel unwell or are concerned.

Product Identifier: Paint Thinner  
SDS No.: 1608  
Date of Preparation: November 11, 2015

### **Skin Contact**

Avoid direct contact. Wear chemical protective clothing if necessary. Take off immediately contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Quickly and gently blot or brush away excess chemical. Immediately rinse with lukewarm, gently flowing water for 15-20 minutes. Call a Poison Centre or doctor if you feel unwell or are concerned. If skin irritation occurs get medical advice/attention. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely.

### **Eye Contact**

Avoid direct contact. Wear chemical protective gloves if necessary. Quickly and gently blot or brush chemical off the face. Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists, get medical advice/attention.

### **Ingestion**

Never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. Rinse mouth with water. If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again. If breathing has stopped, trained personnel should immediately begin rescue breathing. If the heart has stopped, trained personnel should start cardiopulmonary resuscitation (CPR) or automated external defibrillation (AED). Avoid mouth-to-mouth contact by using a barrier device. Immediately call a Poison Centre or doctor. Treatment is urgently required.

### **First-aid Comments**

Get medical advice/attention if you feel unwell or are concerned.

### **Most Important Symptoms and Effects, Acute and Delayed**

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

### **Immediate Medical Attention and Special Treatment**

#### **Target Organs**

Eyes, skin, nervous system.

#### **Special Instructions**

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

#### **Medical Conditions Aggravated by Exposure**

Dermatitis.

## **SECTION 5. FIRE-FIGHTING MEASURES**

### **Extinguishing Media**

#### **Suitable Extinguishing Media**

Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog.

#### **Unsuitable Extinguishing Media**

None known.

### **Specific Hazards Arising from the Chemical**

Flammable liquid and vapour. Can ignite at room temperature. Releases vapour that can form explosive mixture with air. Can be ignited by static discharge. Can accumulate static charge by flow, splashing or agitation. Liquid can float on water and may travel to distant locations and/or spread fire. May travel a considerable distance to a source of ignition and flash back to a leak or open container. See Section 9 (Physical and Chemical Properties) for flash point and explosive limits. May accumulate in hazardous amounts in low-lying areas especially inside confined spaces, resulting in a fire hazard. May accumulate in hazardous amounts in low-lying areas especially inside confined spaces, resulting in a health hazard. Closed containers may rupture violently when heated releasing contents.

In a fire, the following hazardous materials may be generated: very toxic carbon monoxide, carbon dioxide.

### **Special Protective Equipment and Precautions for Fire-fighters**

Review Section 6 (Accidental Release Measures) for important information on responding to leaks/spills. See Skin Protection in Section 8 (Exposure Controls/Personal Protection) for advice on suitable chemical protective

---

Product Identifier: Paint Thinner  
SDS No.: 1608  
Date of Preparation: November 11, 2015

materials.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment, and Emergency Procedures

No special precautions are necessary.

### Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway.

### Methods and Materials for Containment and Cleaning Up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

## SECTION 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Conditions for Safe Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Hydrotreated kerosene	200 mg/m3 A3	Not established	Not established	Not established		
n-Nonane	200 ppm	Not established	200 ppm	Not established		

### Appropriate Engineering Controls

The hazard potential of this product is relatively low. General ventilation is usually adequate. For large scale use of this product: use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored. Control static electricity discharges which includes bonding of equipment to ground. Use only non-combustible, compatible materials for walls, floors, ventilation system, air cleaning devices, pallets, shelving. Provide eyewash and safety shower if contact or splash hazard exists.

Product Identifier: Paint Thinner  
SDS No.: 1608  
Date of Preparation: November 11, 2015

## Individual Protection Measures

### Eye/Face Protection

Wear chemical safety goggles.

### Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.

### Respiratory Protection

Not usually required when working with small quantities. For non-routine or emergency situations: wear a NIOSH approved air-purifying respirator with an appropriate cartridge.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### Basic Physical and Chemical Properties

<b>Appearance</b>	Clear colourless liquid.
<b>Odour</b>	Hydrocarbon
<b>Odour Threshold</b>	Not available
<b>pH</b>	Not available
<b>Melting Point/Freezing Point</b>	< -75 °C (-103 °F) (melting); < -75 °C (-103 °F) (freezing)
<b>Initial Boiling Point/Range</b>	161 - 198 °C (322 - 388 °F)
<b>Flash Point</b>	> 40 °C (104 °F) (closed cup)
<b>Evaporation Rate</b>	0.18 (n-butyl acetate = 1)
<b>Flammability (solid, gas)</b>	Not applicable
<b>Upper/Lower Flammability or Explosive Limit</b>	5.6% (upper); 0.8% (lower)
<b>Vapour Pressure</b>	2.03 mm Hg (0.27 kPa) at 20 °C
<b>Vapour Density (air = 1)</b>	4.9
<b>Relative Density (water = 1)</b>	0.776 at 15 °C
<b>Solubility</b>	Practically insoluble in water; Not available (in other liquids)
<b>Partition Coefficient, n-Octanol/Water (Log Kow)</b>	Not available
<b>Auto-ignition Temperature</b>	260 °C (500 °F)
<b>Decomposition Temperature</b>	Not available
<b>Viscosity</b>	1.09 - 1.30 centistokes at 25 °C (kinematic); Not available (dynamic)
<b>Other Information</b>	
<b>Physical State</b>	Liquid
<b>Molecular Weight</b>	Not applicable

## SECTION 10. STABILITY AND REACTIVITY

### Reactivity

None known.

### Chemical Stability

Normally stable.

### Possibility of Hazardous Reactions

None known.

### Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources. Temperatures above 40.0 °C (104.0 °F)

### Incompatible Materials

Increased risk of fire and explosion on contact with: strong oxidizing agents (e.g. perchloric acid).

---

Product Identifier: Paint Thinner  
SDS No.: 1608  
Date of Preparation: November 11, 2015

## Hazardous Decomposition Products

None known.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Likely Routes of Exposure

Skin contact; eye contact; ingestion; inhalation.

### Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Hydrotreated kerosene	> 5 mg/L (rat) (4-hour exposure)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
n-Nonane	3200 ppm (rat) (4-hour exposure)	15 g/kg (rat)	Not available

LC50: Not applicable.

LD50 (oral): Not applicable.

LD50 (dermal): Not applicable.

### Skin Corrosion/Irritation

Human experience and animal tests show moderate or severe irritation.

### Serious Eye Damage/Irritation

Human experience and animal tests show mild irritation. The vapour also irritates the eyes.

### STOT (Specific Target Organ Toxicity) - Single Exposure

#### Inhalation

May be harmful based on human experience and animal tests. At high concentrations depression of the central nervous system. Symptoms may include headache, nausea, dizziness, drowsiness and confusion. A severe exposure can cause unconsciousness. (Hydrotreated kerosene). (n-Nonane)

May be harmful At high concentrations based on human experience and animal tests. Nose and throat irritation. (n-Nonane)

#### Skin Absorption

Not harmful based on animal tests. (Hydrotreated kerosene)

No information was located. (n-Nonane)

#### Ingestion

May be harmful based on limited evidence. (n-Nonane)

### Aspiration Hazard

Can cause lung damage if aspirated based on human experience. Death can result.

### STOT (Specific Target Organ Toxicity) - Repeated Exposure

Causes damage to organs based on studies in people and animals. Following skin contact: dermatitis. Symptoms may include dry, red, cracked skin (dermatitis). effects similar to STOT (Specific Target Organ Toxicity) - Single Exposure, as described above. (Hydrotreated kerosene). (n-Nonane).

### Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer. Not known to be a skin sensitizer.

### Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Hydrotreated kerosene	Group 3	A3	Not Listed	Listed
n-Nonane	Not Listed	Not designated	Not Listed	Not Listed

Key to Abbreviations

A3 = Animal carcinogen.

Group 3 = Not classifiable as to its carcinogenicity to humans.

Product Identifier: Paint Thinner  
SDS No.: 1608  
Date of Preparation: November 11, 2015

## Reproductive Toxicity

### Development of Offspring

Does not cause harm to the unborn child. (Hydrotreated kerosene)  
No information was located. (n-Nonane)

### Sexual Function and Fertility

No information was located. (Hydrotreated kerosene). (n-Nonane)

### Effects on or via Lactation

No information was located.

## Germ Cell Mutagenicity

Not known to be a mutagen. (Hydrotreated kerosene)  
No information was located. (n-Nonane)

## Interactive Effects

No information was located.

## SECTION 12. ECOLOGICAL INFORMATION

### Toxicity

#### Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Hydrotreated kerosene	2.2 mg/L (Lepomis macrochirus (bluegill); 96-hour)	Not available		
n-Nonane	Not available	Not available		

#### Chronic Aquatic Toxicity

Chemical Name	NOEC Fish	EC50 Fish	NOEC Crustacea	EC50 Crustacea
Hydrotreated kerosene	Not available		Not available	
n-Nonane	Not available		Not available	

## Persistence and Degradability

No information was located.

## Bioaccumulative Potential

No information was located.

## Mobility in Soil

No information was located.

## Other Adverse Effects

There is no information available.

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal Methods

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	1268	PETROLEUM DISTILLATES, N.O.S. (distillates petroleum, hydrotreated light)	3	III
US DOT	1268	PETROLEUM DISTILLATES, N.O.S. (distillates petroleum, hydrotreated light)	3	III

**Environmental Hazards** Marine Pollutant (Hydrotreated kerosene)

**Special Precautions for User** Please note: In containers of 450 L or less this product is not classified as a Dangerous Good according to TDG Exemption 1.33  
In containers of 450 L or less this product is not classified as a Dangerous Good according to DOT Exemption 49 CFR section 173.150 (f)

**Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

## SECTION 15. REGULATORY INFORMATION

**Safety, Health and Environmental Regulations**

**Canada**

**Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)**

All ingredients are listed on the DSL/NDSL.

**CEPA - National Pollutant Release Inventory (NPRI)**

Part 5. (Hydrotreated kerosene). (n-Nonane)

**USA**

**Toxic Substances Control Act (TSCA) Section 8(b)**

All ingredients are listed on the TSCA Inventory.

## SECTION 16. OTHER INFORMATION

**SDS Prepared By** Compliance and Regulatory Department

**Phone No.** 905-878-5544

**Date of Preparation** November 11, 2015

**Additional Information** We are committed to uphold the Industry Consumer Ingredient Communication Voluntary Initiative.  
Please send us your request by visiting our website at [www.recochem.com](http://www.recochem.com).

Ingredients present (intentionally added ingredients) at a concentration of greater than one percent (1%) shall be listed in descending order of predominance. Ingredients present at a concentration of not more than one percent shall be listed but may be disclosed without respect to order of predominance.

**Disclaimer**

Notice to reader: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Product Identifier: Paint Thinner

SDS No.: 1608

Date of Preparation: November 11, 2015

Page 08 of 08