



unit: INCH

Bolt Size		F		G	H	I
		Basic	Across Flat	Width across Corner	THICKNESS	Wrenching Height
6-32	Min	5/16	0.302	0.399	0.168	0.103
	Max		0.313		0.188	
8-32	Min	11/32	0.332	0.374	0.219	0.140
	Max		0.345		0.239	
10-24	Min	3/8	0.362	0.410	0.229	0.140
	Max		0.376		0.249	
10-32	Min	3/8	0.362	0.410	0.229	0.140
	Max		0.376		0.249	
1/4	Min	7/16	0.430	0.488	0.298	0.225
	Max		0.439		0.328	
5/16	Min	1/2	0.489	0.557	0.329	0.250
	Max		0.502		0.359	
3/8	Min	9/16	0.551	0.628	0.438	0.335
	Max		0.564		0.468	
7/16	Min	5/8	0.616	0.698	0.438	0.324
	Max		0.627		0.468	
1/2	Min	3/4	0.736	0.840	0.579	0.464
	Max		0.752		0.609	
9/16	Min	7/8	0.861	0.982	0.626	0.469
	Max		0.877		0.656	
5/8	Min	15/16	0.922	1.051	0.735	0.593
	Max		0.940		0.765	
3/4	Min	1-1/16	1.052	1.191	0.860	0.742
	Max		1.064		0.890	

Hexagon Lock Nut with Nylon Insert (Grade NE2), Zinc plated

Date : 1 mars 2016

Done by : P.B.