

PROFESSIONAL DRAIN**1069, 1071, 1079, 1084**

COMPANY IDENTITY: ROOTO CORPORATION
PRODUCT IDENTITY: SULFURIC ACID 93%
COMPANY MANUFACTURER IDENTITY: ROOTO CORPORATION

SDS DATE: 05/13/2024
ORIGINAL DATE: 05/01/2015

SAFETY DATA SHEET

This Safety Data Sheet conforms to ANSI Z40035, and to the format requirements of the Global Harmonizing System.

THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) IMPORTANT: Read this SDS before handling & disposing of this product. Pass this information on to employees, customers and users of this product.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

PRODUCT IDENTITY: SULFURIC ACID 93%
PRODUCT USES: Mineral Acid
COMPANY IDENTITY: Rooto Corporation
COMPANY ADDRESS: 3505 W. Grand River
COMPANY CITY: Howell, MI 48855
COMPANY PHONE: 517-546-8330
EMERGENCY PHONE: CHEMTREC: 1-800-424-9300 (USA)

SECTION 2. HAZARDS IDENTIFICATION**2.1 Classification of Substance or Mixture:**

GHS Classification:
H290 Metal. (CAT: 1)
H314 Skin Corr. (CAT: 1A)
H318 Eye Damage. (CAT: 1)
H402 Aquatic Acute. (CAT: 3)

2.2 GHS Label elements, including precautionary statements:

GHS Labeling
Hazard pictogram



GHS05

Signal word

Danger

Hazardous Statements

H290 – May be corrosive to metals.
H314 – Causes severe burns and eye damage.
H318 – Causes serious eye damage.
H402 – Harmful to aquatic life.

Precautionary Statements

P201 – Obtain special instructions before use.
P202 – Do not handle until all safety precautions have been read and understood.
P234 – Keep only in original container.
P260 – Do not breathe dust/fume/gas/mist/vapors/spray.
P262 – Do not get in eyes, on skin, or on clothing.
P264 – Wash hands thoroughly after handling.
P273 – Avoid release to the environment.
P280 – Wear protective gloves/protective clothing/eye protection/face protection.
P301+330+331 – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+361+353 – IF ON SKIN (HAIR): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P394+340 – IF INHALED: Remove victim to fresh air & keep at rest in a position comfortable for breathing.
P305+351+338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present & easy to do – Continue rinsing.
P310 – Immediately call a POISON CENTER or doctor/physician.
P363 – Wash contaminated clothing before reuse.
P390 – Absorb spillage to prevent material damage.

COMPANY IDENTITY: ROOTO CORPORATION
PRODUCT IDENTITY: SULFURIC ACID 93%

SDS DATE: 05/13/2024
ORIGINAL: 05/01/2015

P404 - Store in a closed container.
P405 - Store locked up.
P501 - Dispose of contents/container to an approved waste disposal plant.

Other Hazards

Exposure may aggravate pre-existing eye, skin or respiratory conditions.

Unknown acute toxicity.

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MATERIAL	CAS#	EINECS#	WT%
Sulfuric Acid	7664-93-9	231-639-5	93
Water	7732-18-5	231-791-2	7

TRACE COMPONENTS: Trace ingredients (if any) are present in <1% concentration, (<0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standards (29 CFE 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CFR 4).

SECTION 4. FIRST AID MEASURES

4.1 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE & CHRONIC:

See Section 11 for symptoms/effects, acute & chronic.

4.2 GENERAL ADVICE:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists, refer to Section 8 for specific personal protective equipment

4.3 EYE CONTACT:

If this product enters the eyes, check for and remove any contact lenses. Open eyes while under gently running water. Use sufficient force to open eyelids. "Roll" eyes to expose more surface. Minimum flushing is for 15 minutes. Seek immediate medical attention.

4.4 SKIN CONTACT:

If the product contaminates the skin, immediately begin decontamination with running water. Minimum flushing is for 15 minutes. Remove contaminated clothing, taking care not to contaminate eyes. If skin becomes irritated and irritation persists, medical attention may be necessary. Wash contaminated clothing before reuse, discard contaminated clothing before reuse, discard contaminated shoes.

4.5 INHALATION:

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR). Seek immediate medical attention.

4.6 SWALLOWING:

If swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, give two glasses of water to drink. DO NOT INDUCE VOMITING. Never induce vomiting or give liquids to someone who is unconscious, having convulsions, or unable to swallow. Seek immediate medical attention.

4.7 RESCUERS: Victims of chemical exposure must be taken for medical attention. Rescuers should be taken for medical attention, if necessary. Take a copy of label and SDS to physician or health professional with victim.

4.8 NOTES TO PHYSICIAN:

There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Any material aspirated during vomiting may cause lung injury. Therefore, emesis should not be induced mechanically or pharmacologically. If it is considered necessary to evacuate the stomach contents, this should be done by means least likely to cause aspiration (such as: Gastric lavage after endotracheal intubation).

SECTION 5. FIRE FIGHTING MEASURES

5.1 FIRE & EXPLOSION PREVENTIVE MEASURES:

Isolate from alkalis, oxidizers, organics, extreme heat and open flames.

5.2 SUITABLE (& UNSUITABLE) EXTINGUISHING MEDIA:

Use extinguishing agent appropriate for surrounding fire.

5.3 SPECIAL PROTECTIVE EQUIPMENT & PRECAUTIONS FOR FIRE FIGHTERS:

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots).

COMPANY IDENTITY: ROOTO CORPORATION
PRODUCT IDENTITY: SULFURIC ACID 93%

SDS DATE: 05/13/2024
ORIGINAL: 05/01/2015

SECTION 5. FIRE FIGHTING MEASURES (CONTINUED)

5.4 SPECIFIC HAZARDS OF CHEMICAL & HAZARDOUS COMBUSTION PRODUCTS:

SLIGHTLY COMBUSTABLE

Reacts with most metals producing hydrogen which is extremely flammable & may explode. Keep container tightly closed. Isolate from oxidizers, alkalis, heat, & open flame. Applying to hot surfaces requires special precautions. Closed containers may explode if exposed to extreme heat. Continue all label precautions!

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 SPILL AND LEAK RESPONSE AND ENVIRONMENTAL PRECAUTIONS:

Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of a spill, clear the affected area, protect people, and respond with trained personnel. ELIMINATE all ignition sources (no smoking, flares, sparks, or flames in immediate area). Prevent additional discharge of material, if possible to do so without hazard. For large spills, implement cleanup procedures and, if in public area, advise authorities.

6.2 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, EMERGENCY PROCEDURES:

The proper personal protective equipment for incidental releases (such as: 1 Liter of the product released in a well-ventilated area), use impermeable gloves, they should be Level B: **triple-gloves (rubber gloves and nitrile gloves over latex gloves)**, chemical resistant suit and boots, hard-hat, and Self-Contained Breathing Apparatus specific for the material handled, goggles, face shield, and appropriate body protection. In the event of a large release, use impermeable gloves, specific for the material handle, chemically resistant suit and boots, and hard-hat. Self-Contained Breathing Apparatus or respirator may be required where engineering controls are not adequate or conditions for potential exposure exist. When respirators are required, select NIOSH/MSHA approved based on actual or potential airborne concentrations in accordance with latest OSHA and/or ANSI recommendations.

6.3 ENVIRONMENTAL PRECAUTIONS:

Stop spill at source. Construct temporary dikes of dirt, sand, or any appropriate readily available material to prevent spreading of the material. Close or cap valves and/or block or plug hole in leaking container and transfer to another container. Keep from entering storm sewers and ditches which lead to waterways, and if necessary, call the local fire or police department for immediate emergency assistance.

6.4 METHODS AND MATERIAL FOR CONTAINMENT & CLEAN-UP:

Absorb spilled liquid with polypads or other suitable absorbent materials. If necessary, neutralize using suitable buffering material, (acid with soda ash or base with phosphoric acid), and test area with litmus paper to confirm neutralization. Clean up with non-combustible absorbent (such as: sand, soil, and so on). Shovel up and place all spill residue in suitable containers. Dispose of at an appropriate waste disposal facility according to current applicable laws and regulations and product characteristics at time of disposal (see Section 13 – Disposal Considerations).

SECTION 7. HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING:

Isolate from oxidizers, alkalis, heat, & open flame. Use only with adequate ventilation. Do not get in eyes, on skin or clothing. Wear OSHA Standard full face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse. Continue all label precautions! NEVER pour water into this substance. When dissolving or diluting, always add it slowly to the water.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

Keep separated from strong oxidants, strong bases, combustible & reducing substances, metals, food & feedstuffs, incompatible materials. May be stored in stainless steel containers. See: Section 10, <Materials to Avoid>. Do not store above 49 C/120 F. Keep container tightly closed & upright when not in use to prevent leakage. Reacts with most metals producing hydrogen which is extremely flammable & may explode. When empty, drain completely, replace bungs securely.

7.3 NONBULK: CONTAINERS:

Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Material should be stored in secondary containers or in a diked area, as appropriate. Store container away from incompatible chemicals (see Section 10, Stability and Reactivity). Post warning and "NO SMOKING" signs in storage and use areas, as appropriate. Empty containers should be handled with care. Never store food, feed, or drinking water in container which held this product.

COMPANY IDENTITY: ROOTO CORPORATION
PRODUCT IDENTITY: SULFURIC ACID 93%

SDS DATE: 05/13/2024
ORIGINAL: 05/01/2015

SECTION 7. HANDLING AND STORAGE (CONTINUED)

7.4 BULK CONTAINERS:

All tanks and pipelines which contain this material must be labeled. Perform routine maintenance on tanks or pipelines which contain this product. Report all leaks immediately to the proper personnel.

7.5 TANK CAR SHIPMENTS:

Tank cars carrying this product should be loaded and unloaded in strict accordance with tank-car manufacturers recommendations and all established on-site safety procedures. Appropriate personal protective equipment must be used (see Section I, Engineering Controls and Personal Protective Equipment). All loading and unloading equipment must be inspected, prior to each use. Loading and unloading operations must be attended, at all times. Tank cars must be level, brakes must be set or wheels must be locked or blocked prior to loading or unloading. Tank car (for loading) or storage tanks (for unloading) must be verified to be correct for receiving this product and be properly prepared, prior to starting the transfer operations. Hoses must be verified to be in the correct positions, before starting transfer operations. A sample (if required) must be taken and verified (if required) prior to starting transfer operations. All lines must be blown-down and purged before disconnecting them from the tank car or vessel.

7.6 PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:

Follow practice indicated in Section 6 (Accidental Release Measures). Make certain application equipment is locked and tagged-out safely. Always use this product in areas where adequate ventilation is provided. Collect all rinsates and dispose of according to applicable Federal, State, Provincial, or local procedures.

7.7 EMPTY CONTAINER WARNING:

Empty container may contain residue and can be dangerous. Do not attempt to refill or clean container without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations.

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY BURST AND CAUSE INJURY OR DEATH.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 EXPOSURE LIMITS:

MATERIAL	CAS#	EINECS#	TWA (OSHA)	TLV (ACGIH)	IDLH (NIOSH)
Sulfuric Acid	7664-93-9	231-639-5	1.0 mg/m ³	1.0 mg/m ³	15 mg/m ³
Water	7732-18-5	231-791-2	None Known	None Known	

This product contains no EPA Hazardous Air Pollutants (HAP) in amounts > B.1%.

8.2 APPROPRIATE ENGINEERING CONTROLS:

RESPIRATORY EXPOSURE CONTROLS

Airborne concentrations should be kept to lowest levels possible. If vapor, dust or mist is generated and the occupational exposure limit of the product, or any component of the product, is exceeded, use appropriate NIOSH or MSHA approved air purifying or air-supplied respirator authorized in 29 CFR 1910.134, European Standard EN 149, or applicable State regulations, after determining the airborne concentration of the contaminant. Air supplied respirators should always be worn when airborne concentrations of the contaminant or oxygen content is unknown. Maintain airborne contaminant concentrations below exposure limits. If adequate ventilation is not available or there is potential for airborne exposure above the exposure limits, a respirator may be worn up to the respirator exposure limitations, check with respirator equipment manufacturer's recommendations/limitations. For particulates, a particulate respirator (NIOS Type BN95 or better filters) may be worn. If oil particles (such as: lubricants, cutting fluids, glycerin, and so on) are present, use a NIOSH Type R or P filter. For a higher level of protection, use positive pressure supplied air respiration protection or Self-Contained Breathing Apparatus or if oxygen levels are below 19.5% or are unknown.

EMERGENCY OR PLANNED ENTRY INTO UNKNOWN CONCENTRATIONS OR IDLH CONDITIONS

Positive pressure, full-face piece Self-Contained Breathing Apparatus; or positive pressure, full-face piece Self-Contained Breathing Apparatus with an auxiliary positive pressure Self-Contained Breathing Apparatus.

COMPANY IDENTITY: ROOTO CORPORATION
PRODUCT IDENTITY: SULFURIC ACID 93%

SDS DATE: 05/13/2024
ORIGINAL: 05/01/2015

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION (CONTINUED)

VENTILATION

LOCAL EXHAUST:	Necessary	MECHANICAL (GENERAL):	Necessary
SPECIAL:	None	OTHER:	None

Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

8.3 INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:

EYE PROTECTION:

Safety eyewear complying with an approve standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, chemical splash goggles should be worn, when a higher degree of protection is necessary, use splash goggles or safety glasses. Face-shields are recommended when the operation can generate splashes, sprays or mists.

HAND PROTECTION:

Use gloves chemically resistant to this material. Preferred examples: Butyl rubber, Chlorinated Polyethylene, Polyethylene, Ethyl vinyl alcohol laminate ("EVAL"), Polyvinyl alcohol ("PVA") Examples of acceptable glove barrier materials include: Natural rubber ("latex"), Neoprene, Nitrile/butadiene rubber ("nitrile") or ("NBR"), Polyvinyl chloride ("PVC") or "vinyl", Viton. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

BODY PROTECTION:

Use body protection appropriate for task. Cover-all, rubber aprons, or chemical protective clothing made from impervious materials are generally acceptable, depending on the task.

WORK & HYGIENIC PRACTICES:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using toilet facilities and at the end of the working period. Provide readily accessible eye wash stations & safety showers. Remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE:	Oily Liquid, Water-White to slightly yellow
ODOR:	None
ODOR THRESHOLD:	Not Available
PH (Neutrality):	< 1
MELTING POINT/FREEZING POINT:	-29C / -28 F
BOILING RANGE (IBP, Dry Point):	276 to 281 C / 528 to 538 F
FLASH POINT (TEST METHOD):	Not Applicable
EVAPORATION RATE (n-Butyl Acetate=1):	Not Applicable
FLAMMABILITY CLASSIFICATION:	Noncombustible
LOWER FLAMMABLE LIMIT IN AIR (%by vol):	18.8 (Lowest Component)
UPPER FLAMMABLE LIMIT IN AIR (%by vol):	Not Available
VAPOR PRESSURE (mm of HG) @2 B C	<0.3
VAPOR DENSITY (air=1):	3.4
GRAVITY @ 68 / 68 F / 28 / 28 C:	
DENSITY:	1.838
SPECIFIC GRAVITY (Water=1):	1.835
POUNDS/GALLON:	15.3
WATER SOLUBILITY:	Complete
PARTITION COEFFICIENT (n-Octane/Water):	Not Available
AUTO IGNITION TEMPERATURE:	Not Applicable
DECOMPOSITION TEMPERATURE:	Not Available
VOCs (>0.044 Lbs/Sq In):	0.0 Vol% / 0.0 g/L / 0.000 Lbs/Gal
TOTAL VOC'S (TVOC) *:	0.0 Vol% / 0.0 g/L / 0.000 Lbs/Gal
NONEXEMPT VOC'S (CVOC)*:	0.0 Vol% / 0.0 g/L / 0.000 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS):	0.0 Wt% / 0.0 g/L / 0.000 Lbs/Gal
NONEXEMPT VOC PARTIAL PRESSURE (mm fo Hg@20C):	0.0
VISCOSITY @ 100 C (ASTM0445) 514.0:	
VISCOSITY @ 28 C (ASTM D445):	Not Available

*Using CARB (California Air Resources Board Rules).

COMPANY IDENTITY: ROOTO CORPORATION
PRODUCT IDENTITY: SULFURIC ACE 93%

SDS DATE: 05/13/2024
ORIGINAL: 05/01/2015

SECTION 10. STABILITY & REACTIVITY

10.1 REACTIVITY & CHEMICAL STABILITY:

Stable under normal conditions, but Reacts with most metals producing hydrogen which is extremely flammable & may explode.

10.2 POSSIBILITY FO HAZARDOUS REACTIONS & CONDITIONS TO AVOID:

Isolate from sources of ignition, heat, & open flame. Reacts vigorously with water.

10.3 INCOMPATIBLE MATERIALS:

The substance is a strong acid, reacts violently with bases and is corrosive. Upon heating, irritation and toxic fumes are formed including sulfur oxides. The substance is a strong oxidant & reacts violently with combustible & reducing materials. Corrosive to most common metals, forming flammable/explosive gas (hydrogen). Sulfuric acid reacts violently with water & organic materials with much heat. Hazardous gases are evolved on contact with chemicals such as cyanides, sulfides, and carbides.

10.4 HAZARDOUS DECOMPOSITION PRODUCTS:

Upon heating, irritating and toxic fumes are formed including sulfur oxides.

10.5 HAZARDOUS POLYMERIZATION:

Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 ACUTE HAZARDS:

11.11 EYE & SKIN CONTACT:

Severe burns to skin, defatting, dermatitis. Animal testing indicates this material is corrosive to the eye. Severe burns to eyes, redness, tearing and blurred vision. Liquid can cause severe skin & eye burns. Wash thoroughly after handling.

11.12 INHALATION:

Severe reparatory tract irritation may occur. Vapor harmful.

11.13 SWALLOWING:

Harmful or fatal if swallowed.

11.2 SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED:

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Pre-existing disorders of any target organs mentioned in this Document can be aggravated by over-exposure by routes of entry to components of this product. Persons with these disorders should avoid use of this product.

11.3 CHRONIC HAZARDS:

11.31 CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:

PROVEN Carcinogen, Human, Group 1 (IARC), SUSPECTED Carcinogen, Human, Group A2 (ACGIH).

11.32 TARGET ORGANS: May cause damage to target organs, based on animal data.

11.33 IRRITANCY: Irritating to contaminated tissue.

11.34 SENSITIZATION: No component is known as a sensitizer.

11.35 MUTAGENICITY: No known reports of mutagenic effects in humans.

11.36 EMBRYOTOXICITY: No known reports of embryo toxic effects in humans.

11.37 TERATOGENICITY: No known reports of teratogenic effects in humans.

11.38 REPRODUCTIVE TOXICITY: No know reports of reproductive effects in humans.

COMPANY IDENTITY: ROOTO CORPORATION
PRODUCT IDENTITY: SULFURIC ACID 93%

SDS DATE: 05/13/2024
ORIGINAL: 05/01/2015

SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED):

A MUTAGEN is a chemical which cause permanent changes to genetic material (DNA) such that the changes will propagate across generational lines. An EMBRYOTOXIN is a chemical which causes damage to a developing embryo (such as: within the first 8 weeks of pregnancy in humans), but the damage does not propagate across generational lines. A TERATOGEN is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A REPRODUCTIVE TOXIN is any substance which interferes in any way with the reproductive process.

11.4 MAMMALIAN TOXICITY INFORMATION:

LD50 (Oral, Acute):	2140 mg/g (Rat)
LC50 / 2 hours:	510 mg/m ³ (Rat), 320 mg/m ³ (Mouse)

SECTION 12. ECOLOGICAL INFORMATION

12.1 ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

12.2 EFFECT OF MATERIAL ON PLANTS AND ANIMALS:

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's component on test animals.

12.3 EFFECT OF MATERIAL ON AQUATIC LIFE:

The substance is harmful to aquatic organisms.

Lese / 48 hours:	49 mg/L, Tap Water, 20C (Bluegill sunfish)
Lese / 48 hours:	100 – 330 mg/L, Aerated Water (Flounder)

12.4 MOBILITY IN SOIL

Mobility of this material has not been determined.

12.5 DEGRADABILITY

This product is completely biodegradable.

12.6 ACCUMULATION

Bioaccumulation of this product has not been determined.

SECTION 13. DISPOSAL CONSIDERATIONS

Processing, use or contamination may change the waster disposal requirements. Do Not dispose of on land, in surface water, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal.

ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES. EPA CHARACTERISTICS: D002

SECTION 14. TRANSPORT INFORMATION

MARINE POLLUTANT: NO

DOT/TOG SHIP NAME:	UN1830, Sulfuric acid, 8, PG-II
DRUM LABEL:	(CORROSIVE)
IATA / ICAO:	UN1830, Sulfuric acid, 8, PG-II
IMO / IMDG:	UN1830, Sulfuric acid, 8, PG-II
EMERGENCY RESPONSE GUIDEBOOK NUMBER:	137



COMPANY IDENTITY: ROOTO CORPORATION
PRODUCT IDENTITY: SULFURIC ACID 93%

SDS DATE: 05/13/2024
ORIGINAL: 05/01/2015

SECTION 15. REGULATORY INFORMATION

15.1 EPA REGULATION:

SARA SECTION 311/312 HAZARDS: Acute Health, Chronic Health, and Reactivity

All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notifications:

This product contains the indicated <*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

SARA TITLE III INGREDIENTS	CAS#	EINECS#	WT%	(REG. SECTION)	RQ (LBS)
*Sulfuric Acid	7644-93-9	231-639-5	93	(302, 31, 312, 313)	1000

15.2 STATE REGULATIONS:

CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT (PROPOSITION 65):

This product contains no chemicals known to the State of California to cause cancer or reproductive toxicity.

15.3 INTERNATIONAL REGULATIONS:

The identified components of this product are listed on the chemical inventories of the following countries:

Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS), Japan (METI/CSCL, MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC), Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

15.4 CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

D2B: Irritation to skin/eyes.

E: Corrosive Material.

This product was classified using the hazard criteria of the Controlled Products Regulations (CPR). This Document contains all information required by the CPR.

SECTION 16. OTHER INFORMATION

16.1 HAZARD RATINGS:

HEALTH (NFPA): 3, HEALTH (HMIS): 3, FLAMMABILITY: 0, PHYSICAL HAZARD: 2

(Personal Protection Rating to be supplied by user based on use conditions).

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

16.2 EMPLOYEE TRAINING:

See Section 2 for Risk & Safety Statements. Employees should be made aware of all hazards of this material (as stated in this SDS) before handling it.

16.3 SDS DATE: 08/01/2018

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.