

Product



www.king-products.com

Adhesives



SAKRETE Concrete Adhesive

Bond a variety of materials to existing concrete! Use to bond newly repaired surfaces or existing concrete and masonry surfaces. Can be used wit atch repairs to resurface concrete for various applications. Available in 946 mL and 3.78 L containers. As a bond coat, 946 mL will cover 5 m2 (50 ft2).*

946 mL #294-2803, 3,78 L #294-281;



SAKRETE Construction Adhesive

Bond a variety of materials with this adhesive! Use to bond concrete, stone, brick, wood, ceramitiles and more. Can also be used to fill cracks or ioints in concrete. Available in 300 mL tubes, which fill a space 6 mm ($\frac{1}{4}$ ") x 6 mm ($\frac{1}{4}$ ") x 9.7 m (32').*

Asphalt Repair Products

at 7.6 cm (3") thick.



SAKRETE Asphalt Repair

Repair or patch damaged asphalt! Use to patch asphalt driveways, walks, parking areas and potholes. Ideal for repairing black-top surfaces 2.5 cm (1") to 10 cm (4") thick, up to 0.4 m² (4 ft²). Available in 30 KG bags, which yield 0.2 m² (2 ft²)

Cements

#294-2936

KING Asphalt-20

Type N Masonry Cement

Type S Masonry Cement

#294-2951

Create a mortar for bricks and blocks to use on

walls not requiring high strength. Mix with sand to

produce a mortar. Available in 30 KG or 33.3 KG

Create a mortar for bricks and blocks to use on

requiring high strength. Mix with sand to produce

load-bearing walls, as well as on exterior walls

a mortar. Available in 30 KG or 33.3 KG bags

non-load-bearing walls, as well as on exterior veneer

Use this cold mix asphalt for temperatures as low as -20 °C (-4 °F). It offers good workability at low peratures and outstanding bond in damp ditions. Available in 22.7 KG bags, which yield 0.008 m³ (0.283 ft³).* Available in select areas.



#294-2878

#294-2886

Cleaners

Make custom concrete or cement-based mixes! General Use (Limestone) Portland Cements (GU and GUL) are intended for use around the home To be mixed with sand or stone. Available in 20 KG

SAKRETE Concrete & Asphalt Cleaner

SAKRETE Concrete & Mortar Dissolver

Available in 651 mL bottles

Clean dried concrete and mortar from tools o

surfaces! Use this safe, environmentally-friendly

dissolver to remove cured cement, concrete, mortar

or stucco from most surfaces. Dissolve cement off

steel, plastic, concrete, wood, glass, paint and more

Remove or lighten stains on concrete or asphalt

surfaces! Use this non-toxic cleaner that rinses


away stains with water. Available in 950 mL bottles

Concrete & Masonry Repair Products

Portland Cement



6 mm (¼") x 7.6 m (25') x 6 mm (¼").*



SAKRETE Non-Sag Sealant

#294-2829

x 3.6 m (12').*

#294-2845

Repair cracks or fill joints in horizontal, vertical or

overhead concrete surfaces! Use this high quality

Repair cracks or fill joints in horizontal concrete

surfaces! Use this high quality, one-component

sealant to form a flexible joint, Ideal for sealing

cracks in concrete driveways, patios, walkways

which fill a space 6 mm ($\frac{1}{4}$ ") x 13 mm ($\frac{1}{2}$ "

and basement floors. Available in 300 mL tubes

one-component sealant to form a flexible joir

Available in 300 mL tubes, which fill a space

6 mm (¼") x 13 mm (½") x 3.6 m (12').*

SAKRETE Self Leveling Sealant

SAKRETE Concrete Crack Filler

Use this pourable and flexible repair product, Ideal for filling cracks in concrete driveways, patios and walkways, Available in 950 mL bottles, 0.95 L fills a crack 10.6 m (35') x 13 mm (½") x 6 mm (¼").



depth is 14.3 cm (55/8").*

depth is 14.3 cm (55/8").*

#294-3223

#294-3215

SAKRETE Flo-Coat

Reiuvenate old concrete surfaces! Use this polymer-modified, flowable, resurfacing material as For resurfacing concrete walks, slabs, driveways ar patios. Compressive strength is 31 MPa (4,500 psi) after 28 days1 Available in 18 1 KG bags which yield 6.7 m² (72 ft²) at 2 mm (1/16") deep.*



SAKRETE fast-patch

Use this two-component epoxy compound that Patch concrete in just 20 minutes! Use this cures to an exceptionally strong, hard produc fast-setting, patch material designed for repairs Anchor (both vertically and horizontally) and bond :hat require a quick return-to-service time. Ideal for fast repairs to concrete sidewalks, curbs, driveway applications, grout dowel bars for concrete repairs or fill holes, pits and cracks, Available in 255 mL floors, steps, parking garages and more. Compressive strength is 50 MPa (7,250 psi) after 28 days¹ tubes, which yield 6 holes when anchor diameter is 1.6 cm (5/8"), hole diameter is 1.9 cm (3/4") and hole Available in 2 KG, 5 KG and 15 KG pails, 1 KG vields 200 cm² (30 in²) at 2.5 cm (1") thick.

SAKRETE Rapid Setting Anchoring Epoxy

bolts or other metal objects in concrete and

and bond applications, grout dowel bars for

which yield 6 holes when anchor diameter is

masonry! Anchor (both vertically and horizontally)

concrete repairs, bond to hardened concrete, or fill

holes, pits and cracks. Available in 255 mL tubes

1.6 cm (5%"), hole diameter is 1.9 cm (34") and hole

SAKRETE High Strength Anchoring Epoxy



SAKRETE top'n bond


2 KG #294-3132. 5 KG #294-2688. 15 KG #294-2696

polymer-modified, cement mixture with superior bond strength. Ideal for repairing, smoothing or resurfacing concrete slabs, driveways, sidewalks. steps, walls, or any worn, chipped or spalled concrete surface. Compressive strength is 27 MPa (4.000 psi) after 28 days¹. Available in 2 KG, 5 KG and 10 KG pails, and 20 KG bags, 1 KG vields 0.10 m² (1 ft²) at 0.6 cm (¹/₄") thick.*

2 KG #294-2993, 5 KG #294-2647, 10 KG #294-3173, 20 KG #294-2662



Complete your concrete project in just hours.



#294-3140

SAKRETE PSI 6000

this high-strength, crack-resistant, air-entrained concrete mix. Use to construct footings, sidewalks, slabs, steps and patios, or to set deck posts, fence posts and poles. Compressive strength is 42 MPa (6.000 psi) after 28 days¹. Available in 30 KG bags. which vield 0.014 m³ (½ ft³).*

sets and lamp posts. Compressive strength is

15 MPa (2.175 psi) after 28 days¹. Available i

30 KG bags, which vield 0.014 m³ (½ ft³)*. 2 bags

Overlay damaged concrete or create a bedding for

Ideal for applications from ½" (1.3 cm) to 2" (5 cm)

in thickness. Can also be used as a base for shower

stalls. Compressive strength is 35 MPa (5.000 psi)

produce a slab 1.2 m (4') x 91 cm (3') x 1.3 cm (½").*

after 28 days¹. Available in 30 KG bags, which

flagstone, slate or brick! Use this high quality

topping or bedding mixture of sand and cement.

Concrete Mixes



SAKRETE Concrete Mix

Fireguard Screens #294-3090

KING Fire Pit Blocks & Fireguard Screens

Build a low-cost, durable, concrete fire pit in just

minutes! Construct a fire pit that will last for yea

Ideal for building a fire pit or a BBQ for campsites

and backyards. Also use for tree rings, curbing

borders or planters. One block weighs 18 KG

B blocks are required for a basic fire pit, and

27 blocks are required for a full BBO.

Pour a concrete slab or set a post in your own strength and durability for new construction or repairs to existing concrete. Use to construct footings, sidewalks, slabs, steps and patios, or to set deck posts, fence posts and poles. Compressive strength is 27.5 MPa (4,000 psi) after 28 days1. Available in 30 KG bags. Two 30 KG bags produce a slab 30 cm (1') x 91 cm (3') x 10 cm (4").

Fire Pit Blocks & Firequard Screens



#294-3041


Use this fast-setting, high quality, concrete mix designed for same-day construction. Use to construct footings, sidewalks, slabs, steps and patios, or to set deck posts, fence posts and poles Compressive strength is 35 MPa (5,075 psi) after 28 days¹. Available in 30 KG bags, which yield 0.014 m³ (½ ft³).*



required per post.

SAKRETE Sand Mix

#294-3033





30 KG

Key Application

SAKRETE RAPID POST, 30 KG Key Application:

Key Application: High Strength Applications

Quick & Easy Calculations

Concrete Mixes



2 Bags = 3 ft² (0.28 m²)

Calculation: 2 Bags = 1 Post

(91 cm)

4 Bags = 6 ft2 (0.56 m2)

Number of 30 KG bags of



6", 8", 10", 12" Diameters

Deck Supports, Fences, Posts

4.5 Bags = 10" Diameter Tub

3.0 Bags = 8" Diameter Tube

Key Applications:

6.5 Bags = 12" Diameter Tube

1.5 Bags = 6" Diameter Tube

Concrete Waterproofing Products Form Tubes



KING Xvpex high'n drv

Vaterproof concrete surfaces! Use this surface-applied chemical treatment for aterproofing bare concrete surfaces such as sement walls, floors, tunnels, storage tanks, cisterns, ponds or swimming pools, Available in 5 KG and 11 KG pails, 1 KG vields 1,25 m²



SAKRETE brush'n seal

Create a protective coating and decorative finish or concrete or brick! Use this dual-purpose, noisture sealant. Ideal for waterproofing and aling basement walls, foundations and swimming pools. Available in 5 KG pails.



Stop water leaks that result from breaks in concrete! Use this quick-setting, non-shrink, hydraulic cement. Stop active water leaks rough breaks in basement walls or floors. tunnels, storage tanks, pools, pits, cisterns, construction faults and holes. Compressiv strength is 17 MPa (2.500 psi) after 7 days. Available in 2 KG, 5 KG and 15 KG pails. 1 KG vields 556 cm³ (34 in³).*

5 KG #294-2761, 11 KG #294-3165

1 KG vields 0.93 m² (10 ft²).

SAKRETE plug-tite



2 KG #294-2720 5 KG #294-2738 15 KG #294-2753

The Footing Tube

SquareFoot

SAKRETE Builders' Tubes

Eliminate frost that occurs from lifting concrete

piers! Use this tube to support decks, cottages and

additions. Ideal as a casting form for concrete piers

to support decks, porches, one-storey cottages and

additions, lamp posts, pole barns, point load beams

Use this uniquely designed, concrete footing form

for residential, commercial and industrial applica-

tions. Install this strong and flexible footing form

simply, quickly and cheaply. Available in 3 sizes to

various builders' tubes. Concrete vield is 0.06 m³

(2.0 ft³) for SF-22, 0.13 m³ (4.5 ft³) for SF-28, and

and fence posts. Available in 8" tube and 10"/12"

tube, and can accompany a base.

0.20 m³ (7.0 ft³) for SF-32.*

Produce round concrete supports! Use these pre-fabricated, fibre tubes for below-ground placement, Ideal for constructing concrete columns for footings, piers, deck supports, fences, basket ball posts, backyard play areas, mail boxes and lamp posts. Also use for storage, shipping and for displays Available in 6". 8". 10" or 12" diameters, and 8' or 12' lengths.†



KING PermaSand (Polymeric)

Landscape Products

Fill joints between interlocking pavers and slabs! Use this quick-setting, polymer sand. Fill joints between interlocking pavers, stone, bricks and slabs. Use around pools, patios, pedestrian walks, driveways, parking areas and roadways. Available in Brown or Grey. Available in 25 KG bags, which vield 4.6 m² (50 ft²) to 9.3 m² (100 ft²).*



#294-3199

Increase Winter traction on ice or snow! Use this dried, high-grit sand on walkways or under tires. Use for traction on all outdoor pavements such as driveways, interlocking payers, loading docks, sidewalks, steps, roadways or under tires. Bag may be used for flood control or ballast for holding down signs, goals or backboards. Available in 23 KG bags.



(3/8") ioint, vield 33 bricks.*



Ice Melting & Traction Products

Melt ice and snow in temperatures as cold as -7 °C (20 °F)! Use this crushed salt in cold weather, on all outdoor pavements such as driveways, interlocking pavers, loading docks, sidewalks, steps or roadway

Grouts



Melt ice and snow while providing traction! Use this mixture of de-icing salt and multi-purpose sand. Use on all outdoor pavements such as driveways, interlocking pavers, loading docks, sidewalks, steps,

SAKRETE flow-stone



#294-3116

plates or columns! Use this non-shrink, non-metallic

Mortar, Parging & Masonry Mixes

Build or repair walls, chimneys, planters or outdoor grills! Use this pre-blended. Type N Mortar cultured stone to vertical surfaces, or bed granite designed for laying clay, concrete or stone masonry pavers and slabs on horizontal surfaces! Use this bricks. For load-bearing walls requiring low mortar for both interior and exterior applications compressive strength or for non-load-bearing walls Compressive strength is 20 MPa (2,900 psi) after Compressive strength is 5.0 MPa (725 psi) after 28 28 days¹, Available in 20 KG bags, which cover days¹, Available in 30 KG bags, which with a 10 mm 1.25 m² (13.5 ft²) at 10 mm (3/8") thick.*



ioints! Use this innovative and flexible material for concrete expansion and isolation joints. Use on slabs, drives, sidewalks, isolation joints, highways, runways and parking garages. Packaged in 50' lengths. Fills a space 15.25 m (50') long x 10 cm (4") wide.*

#294-2985



SAKRETE Mortar Mix. Available in 700 g plastic jars.


which yield 7 x 30 KG bags.*

SAKRETE Backer Rod





SAKRETE ShapeCrete





SAKRETE Countertop Magic

Add SAKRETE Countertop Magic to SAKRETE

Use this shape-able concrete that can be rolled

Build castles with this natural beach sand! Use this high quality, sandbox-friendly sand. Ideal for sand boxes, playgrounds and displays, Available in 20 KC bags. 5 bags fill an area 1.0 m (3') x 1.0 m (3') x

KING Play Sand

SAKRETE Jointing Sand

(50 ft²) to 9.3 m² (100 ft²).

SAKRETE Multi-Purpose Sand

(0.625 ft³).*

#294-3017

Fill joints between interlocking stones or field stone!

Use this washed, flame-dried sand. For filling joints

between interlocking pavers, stone, bricks, and

slabs. Available in 25 KG bags, which vield 4.6 m

a wide variety of projects. For landscaping, soil

conditioner, displays, Winter traction on roads, icy

sidewalks, greasy areas, or to mix with cement to

when loosely compacted, yield 0.0175 m³

Sands & Gravels



KING Pea Gravel

Landscape around your house or repair a flat roof! Use this %", natural, round stone in decorative landscaping applications, Ideal for around patios, decks, gardens, play areas, pathways, dog runs, pools and ponds. Available in 30 KG bags, which when loosely compacted, vield 0.021 m³ (0.67 ft³).*

Create a drainage base for weeping tile! Use this

For landscaping around patios, under decks, along

pathways and in dog runs. It may also be used with

cement and sand to make custom concrete mixes.

natural crushed stone that is ½" in diameter.

For French drains, driveways and walkways,

Available in 30 KG bags, which when loosely

compacted, vield 0.021 m³ (0.67 ft³).*



KING ¼" Gravel

around patios, under decks, along pathways and in dog runs. It may also be used with cement and sand to make custom concrete mixes. Available in 30 KG bags, which when loosely compacted, yield




KING 0-¾" Gravel Fill driveways, walkways, pathways or dog-runs!



ranging from 0 to ¾" in diameter. For landscaping around patios, under decks, along pathways and in dog runs. Available in 30 KG bags, which wher loosely compacted, yield 0.021 m³ (0.67 ft³).* Available in select areas.

KING Limestone Screenings Create a level base for interlocking brick and





KING ¾" Gravel

KING ½" Gravel



#294-3207

and walkways! Use this natural crushed stone that is 34" in diameter. For French drains, driveways and walkways. For landscaping around patios, under decks, along pathways and in dog runs. It may also be used with cement and sand to make custom concrete mixes. Available in 30 KG bags, which when loosely compacted, yield 0.021 m³ (0.67 ft³).*

* Yield is approximate.

Branding and packaging varies by geographical region

ask your KING Account Manager for details. ¹Only 28 day compressive strength is listed. For complete

information, refer to www.king-products.com.

SAKRETE Mortar Mix. Type S

#294-3058

SAKRETE Parging Mix

SAKRETE Mortar Mix. Type N

Construct foundation walls, retaining walls

manholes or sewers! Use this pre-blended, Type S Mortar designed for laying concrete blocks, hard brick or stone. For load-bearing walls requiring high compressive strength. Compressive strength is 8.5 MPa (1230 psi) after 28 days¹. Available in 30 KG bags, which with a 10 mm (3/8") joint, yield 12 blocks or 33 bricks.*



SAKRETE Non-Shrink Grout Conduct high-strength grouting of heavy machinery.

structural cement. Designed for grouting machinery base plates, column sole plates, anchor bolts, dowels and hand rails. Can also be used to repair precast units or to infill pipes and sleeves. Available in 25 KG bags, which yield 0.0127 m³ (0.45 ft³) in plastic state #294-2621 or 0.0132 m³ (0.47 ft³) in fluid state.*

Parge concrete blocks or poured concrete! Use for parging smooth and leveling imperfections on

concrete blocks or poured concrete walls, above and below grade. Compressive strength is 12.5 MP (1.800 psi) after 12 days. Available in 25 KG bags. THE PARTY OF PROPERTY AND THE PARTY OF THE P which vield 3.9 m² (42 ft²) at a 3 mm (1/4") thick.* precast units and copings, curtain wall joints, log construction, windows and doors, Packaged in 20' lengths. Fills a space 6 m (20') x 2 cm (34").*

Easily install a temporary seal in wide joints and cracks! Use this highly-flexible and compressible non-absorptive, rope-like, back-up material.

Commonly used in horizontal and vertical glazing installations for expansion joints, pavement joints

and molded, pushed and poured, into any shape imaginable! Use this easy-to-use, high-performance, shape-able concrete, Available in 9.1 KG pails, which vield an object 61 cm (2') x 61 cm (2') x 1.25 cm