



Speedi-Boot helps builders meet ENERGY STAR Homes guidelines.

# SPEEDI-BOOT™

THE NEW STANDARD IN VENT BOOT INSTALLATION





RESIDENTIAL



COMMERCIAL



VERTICAL ARMS



HORIZONTAL ARMS



**CEILING** Speedi-Boot's adjustable sliding brackets simply slide out to the required length of span and install with nails (pre-attached) or screws. The foam gasket and drywall mud ring allow for an improved air seal.

**WALL** Speedi-Boot attaches to walls in horizontal or vertical positions for efficient air vent placement. Grille guides and a steel frame assure a solid backing for grille or register installation.

**FLOOR** Speedi-Boot is made of rigid steel. Its foam gasket seals the floor to the Speedi-Boot improving air-seal integrity. Corner screw holes provide for direct fastening to the sub-floor.

**SPEEDI-BOOT COMES IN MANY SIZES AND BOOT STYLES AND FITS MOST APPLICATIONS.**

**Typical Model Number nomenclature-SBH-4106 NB**

- SBH** Speedi-Boot Hanger
- 4106** 4"x10" Register Opening, 6" Round Duct Collar
- SB** Straight Boot
- FB** Forty Five Degree Boot
- NB** Ninety Degree Boot
- EB** End Boot
- SRA** Square to Round Adapter
- WS** Wall Stack - Oval



Model	4x8	4x10	4x12	4x14	6x10	6x12	6x14	8x8	8x10	8x14	10x10	12x12	14x14	14x24	16x16	16x20	20x20	20x25	20x30
SBH	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
Styles	SB-FB-NB-EB	SB-FB-NB-EB	SB-FB-NB-EB-WS	SB-FB-NB-EB	SB-FB-NB-EB-WS	SB-FB-NB-EB-WS	SB-FB-NB-EB	SRA	SB-FB-NB-EB	SB-NB-	SRA	SRA	SRA	SRA	SRA	SRA	SRA	SRA	SRA
Collars																			
4	x																		
5	x	x																	
6		x	x	x	x	x	x	x	x	x	x								
7		x	x	x	x	x	x	x	x	x	x								
8			x	x	x	x	x	x	x	x	x	x							
9									x	x	x	x							
10											x	x	x						
12												x	x	x	x	x	x	x	x
14													x	x	x	x	x	x	x
16															x	x	x	x	x
18																	x	x	x
20																	x	x	x

Snap lock tool required for hanger only models: Malco SL-1

**FEATURES**

**BENEFITS**

**Labor Savings**

- Simple 2 minute installation
- Faster project completion
- One trip up the ladder

**Air Tight Foam Gasket**

Improved energy efficiency and indoor air quality

**Drywall Mud Ring**

Eliminates boot deformation and accidental covering by drywall

**16" - 24" Arm Extension Capability**

- Fits most universal ceiling, wall or floor boot sizes
- Precise installation in either horizontal or vertical position

**Dust and Debris Cover**

- Prevents construction dust and debris from entering HVAC system
- Perform duct pressure testing with ease

**Rigid Galvanized Steel Frame**


- Easy grille and register installations
- Pre-drilled pilot holes for easy trimout
- Eliminates loose or sagging registers

**Wood or Metal Stud Applications**

Remodel, new residential and commercial uses

# SPEEDI-BOOT™

Speedi-Boot is  
Credited for LEED 5.1  
Environmentally Preferred  
Products and Meets  
IEQ 3.1 Construction  
IAQ Management Plan  
During Construction.



Speedi-Boot helps builders  
meet ENERGY STAR Homes guidelines.

**earth**  
advantage

Earth Advantage  
certified products use  
less energy  
and fewer resources,  
improve indoor air quality  
and protect the  
environment.



#### DRYWALL MUD RING

The drywall/sheetrock mud ring creates a cut-to-fit edge that eliminates deformation or accidental covering of the boot.

#### DUST COVER

Speedi-Boot's integrated dust cover protects HVAC systems and homeowners from construction dust and debris.



Applied Applications International, Inc.

500 Colorado Street / Kelso, WA 98626 / toll-free (866) 794-7900