

BRUSH CLEANER

TECHNICAL DATA SHEET

709



# SUNNYSIDE BRUSH CLEANER

## DESCRIPTION

Sunnyside Brush Cleaner restores dried, hardened brushes. Effective on all paints and varnishes.

## ITEM NUMBERS & SIZES

Pint	Quart	1-Gallon	2.5-Gal.	5-Gal.	55-Gal.
70916	70932	709G1			

## HAZARDOUS INGREDIENTS

Ingredient	CAS#	Percent
Acetone	67-64-1	
Ethyl Acetate	141-78-6	
Methanol	67-56-1	
Aliphatic Naphtha	64742-89-8	
Toluene	108-88-3	
2-Butoxyethanol	111-76-2	

## PHYSICAL PROPERTIES

Typical Properties	Results
GRAVITY, (60 °F)	
API	
SPECIFIC	0.898
DENSITY (Lb./GAL)	7.48
DISTILLATION RANGE ° F.	104 (IBP)
FREEZING POINT, ° F (° C)	
KAURI BUTANOL (Kb) VALUE	
ANILINE POINT, ° F	
FLASH POINT, T.C.C. ° F	39
FLAMMABLE LIMITS IN AIR, % BY VOLUME	
LOWER, AT 100 ° F (38 ° C)	N.E.
UPPER, AT 200 ° F (93 ° C)	
AUTOIGNITION TEMPERATURE, ° F (° C)	
COLOR, Pt-Co	N.A.
DOCTOR TEST	
CORROSION, 3 HRS. @ 212 ° F	
NON-VOLATILES, g/100ml	
ACIDITY(A:S ACETIC ACID)	N.A.
ALKALINITY (AS NH3, WT%)	N.A.
EVAPORATION RATE	Slower than ether
APPEARANCE	Clear, water-white
ODOR	Petroleum Odor
VAPOR PRESSURE, mm Hg @ 20 ° C	
REFRACTIVE INDEX, @ 20 ° C	
SULFUR CONTENT, PPM	
PURITY, by G.C., Wt%	
WATER CONTENT, Wt%	0.1 Max.
WATER MISCIBILITY	
DOT SHIPPING NAME	Flammable, Liquid, Toxic NOS
DOT CLASSIFICATION	Hazard Class 3
SHIPPING Wt. at 20 ° C	7.48
V.O.C. (g/L)	696

These properties are representative of typical inspections. They do not constitute product specifications. Consult MSDS sheet for additional information.

## SAFETY INFORMATION

**HEALTH:** 2  
**FIRE:** 3  
**REACTIVITY:** 1

## PRODUCT APPLICATION

To clean hardened brushes, suspend in metal can, allowing only the bristles to contact the cleaner. Work the brush enough to allow deep penetration of the cleaner. When the brush begins to soften, a metal comb or wire brush will help remove the dried paint. When the brush is sufficiently free of paint, rinse in water and wrap in paper to retain shape. To clean freshly used brushes, work the bristles with cleaner until they are free of paint, the rinse in water and wrap in paper.

## ASTM Applied

D-278	
D-1298	■
D-86	■
D-1133	
D-611	
D-56	■

D-1255	
D-1209	■
D-484	
D-130	
D-1353	
D-1613	
D-1614	

D-1296	■
--------	---

D-1218	
D-1266	

D-1364	
D-1722	

See MSDS sheet for additional Health, Safety, Handling and Regulatory Information available on our website at [www.sunnysidecorp.com/msds.html](http://www.sunnysidecorp.com/msds.html)