

## ODORLESS PAINT THINNER

705



## SUNNYSIDE ODORLESS PAINT THINNER

## DESCRIPTION

Sunnyside Odorless Paint Thinner is a clear, colorless solvent, with virtually no odor. It is primarily used with odorless coatings, and is excellent for use in hospitals, nursing homes or wherever an odorless thinner is required.

## ITEM NUMERS &amp; SIZES

Pint	Quart	1-Gallon	2.5-Gal.	5-Gal.	55-Gal.
	70532	705G1		705G5	70555

## HAZARDOUS INGREDIENTS

Ingredient	CAS#	Percent
Isoparaffinic Hydrocarbon	64742-48-9	100%

## PHYSICAL PROPERTIES

Typical Properties	Results
GRAVITY, (60 °F)	
API	54.2
SPECIFIC	0.762
DENSITY (Lb./GAL)	6.34
DISTILLATION RANGE, ° F.	354-372
FREEZING POINT, ° F (° C)	
KAURI BUTANOL (Kb) VALUE	27
ANILINE POINT, ° F	185
FLASH POINT, T.C.C. ° F	120
FLAMMABLE LIMITS IN AIR, % BY VOLUME	
LOWER, AT 100° F (38° C)	0.7
UPPER, AT 200° F (93° C)	5.4
AUTOIGNITION TEMPERATURE, ° F (° C)	689
COLOR, SAYBOLT	+30
DOCTOR TEST	NEGATIVE
CORROSION, 3 HRS. @ 212 ° F	1A
NON-VOLATILES, g/100ml	Nil
ACIDITY	NEUTRAL
ALKALINITY (AS NH <sub>3</sub> , WT%)	
EVAPORATION RATE	Slower than ether
APPEARANCE	Clear, water-white
ODOR	Odorless
VAPOR PRESSURE, mm Hg @ 20 ° C	1
REFRACTIVE INDEX, @ 20 ° C	
SULFUR CONTENT, PPM	Nil
PURITY, by G.C., Wt%	
WATER CONTENT, Wt%	
WATER MISCIBILITY	Negligible
DOT SHIPPING NAME	Petroleum Distillates, N.O.S.
DOT CLASSIFICATION	Combustible Liquid - CIPG III
Shipping Wt./Gal. @ 20 ° C.	6.34
V.O.C. (g/L)	761

These properties are representative of typical inspections. They do not constitute product specifications. Consult MSDS sheet for additional information.

## SAFETY INFORMATION

HEALTH:	1
FIRE:	2
REACTIVITY:	0

## PRODUCT APPLICATION

This product is recommended for thinning odorless coatings. Follow the paint manufacturer's instructions for the proper amount of paint thinner; do not use more than recommended. Add gradually and stir until desired consistency is obtained. Do not use as a thinner for latex paint or other water based coatings, lacquer or shellac. For fresh oil based coatings, agitate brush or roller in Odorless Paint Thinner until all visible residue is dissolved. Then rinse, using fresh Odorless Paint Thinner. Press out excess and lay flat to dry.

## TEST METHOD

ASTM	Applied
D-278	■
D-1298	■
D-86	■
D-1133	■
D-611	■
D-56	■
D-1255	■
D-156	■
D-484	■
D-130	■
D-1353	■
D-847	■
D-1614	■
D-1296	■
D-1218	■
D-1266	■
D-1364	■
D-1722	■

See MSDS sheet for additional Health, Safety, Handling and Regulatory Information available on our website at [www.sunnysidecorp.com/msds.html](http://www.sunnysidecorp.com/msds.html)