

DUCKBACK® Anti-Skid Additive

6310



General Description

DUCKBACK® ANTI-SKID ADDITIVE can be added to paints and coatings to create a slip resistant surface.

Recommended Substrates

For Interior & Exterior Use. Perfect for sidewalks, driveways, pool sides, decks, docks, ramps, stairs, and more.

Tinting & Base Color Information

Ready to use. Do not tint.

SC 6310

Features / Benefits

100% Walnut Shells
Meets ADA slip resistant standards when used with Deck & Dock Elastomeric Coating
40/60 Grit
Interior and Exterior Use

Product Application

APPLICATION:

Mix one package of Anti-Skid Additive to 1 gallon of paint or other coating to create a slip resistant surface. For interior and exterior use. If there is not enough open space in a gallon can to accept the entire package then remove some of the paint before adding anti-skid, or mix the two in a larger container. Stir thoroughly to mix and evenly distribute the granules throughout the coating. If applying more than 1 coat of paint, add Anti-Skid Additive only to the final coat, or according to product label instructions.

CONTENTS:

100% Ground Walnut Shells, 40/60 grit.

Conformance

OTC Approved:	N/A
SCAQMD Approved:	N/A
LADCO Approved:	N/A
CARB Approved:	N/A
Biodegradable:	No
ASTM Standard:	N/A
Master Painters Institute (MPI):	N/A

Packaging

0.4 Pound Container - 8.44 fl. oz. / 181 g

