



Pacer Technology Super Glue's Future Glue Brush-On (14204, 15099, 15111) is a quick-setting adhesive that works on oily & dirty surfaces to bond materials, such as:

- Jewelry
- Metal
- Leather
- Ceramic
- Most Plastics
- Rubber
- Aluminum
- China
- Porcelain
- Hard & soft wood
- Pottery

NOTE: Not for use with Teflon, polyethylene, polypropylene, certain silicone rubber types, glass, rear view mirrors or parts that are subjected to great shock or continuous immersion in water.

PROPERTIES:

Initial color: Clear, transparent

Final color: Clear

Set time: 10-30 seconds

Full Strength: 24 hours

Operating Temperature Range: -65⁰ to 180⁰F
 (-54⁰ to 82⁰C)

USE INSTRUCTIONS: **NOTE:** For best results, surfaces should be clean and dry.

1. Protect clothing and work surfaces (metal foil works well). Use in a well-ventilated area. Carefully follow tube-opening directions on package. Unscrew cap while keeping tube pointed away from face.
2. Apply to one surface, using 1 drop per square inch of surface. Assemble parts and hold together with pressure for 15 seconds or until set.
3. Wipe top of nozzle if adhesive has accumulated before recapping tube securely after use.

STORAGE AND SHELF LIFE: Store upright in a cool area away from sunlight or heat sources. Stored under these conditions, a one-year shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS

Contains cyanoacrylate. CAUTION: Eye Irritant. Bonds skin & eyes in seconds. Use with adequate ventilation. Avoid contact with clothing as can cause burn. In case of eye contact, flush with water for 15 minutes; get medical attention for eye or internal contact. To remove from skin, soak in acetone nail polish remover & gently peel adhesive off with fingernail; water exposure will wear off residual adhesive in a few days (do not use polish remover around eye area). **KEEP OUT OF REACH OF CHILDREN.**

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ www.supergluecorp.com . In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or (909) 987-0550.

Rev 1 – 2016 kr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.