

Introducing
GEN II



THE
**ULTIMATE
FASTENERS**

#18x 5/16" HEX HEAD

STRUCTURAL LAG

YUKON™



Large Washer Hex Head

Strong Structural Lag screw with 5/16" Hex Head for a powerful torque transmission and easy installation. The built-in washer underneath the head provides great holding power and works well for heavy duty applications.



Twin Blades™

(patent pending) This set of knurls cuts fast to dramatically reduce friction and heat on the shank, while reducing load on the drill. They also provide better performance by removing debris faster than a standard fastener's knurl.



Fast Start Tip

With sharp threads all the way to the tip, the fastener has an immediate grip for a fast start. The inset thread cut drastically reduces the splitting effect and minimizes the driving torque needed to engage the wood.

The advanced, Heavy Duty Structural Lag Screw with **ZYTEC™ GX** corrosion protection coating for typical typical high-corrosive, exterior, and interior environments. Great for any size job or project.



Available in 50ct and 250ct.
All Packaging Includes Hex Driver.

WWW.SCREW-PRODUCTS.COM

9401 Bujacich Rd. Bldg 1B, Gig Harbor, WA 98332
Toll-Free 1-877-844-8880

Weights and counts subject to change without notice.

THE ULTIMATE FASTENERS

FOLLOW US



#SCREWPRODUCTSINC

Jun 1, 2020



THE ULTIMATE FASTENERS

#18x 5/16" HEX HEAD

STRUCTURAL LAG



TYPICAL EXTERIOR USE

ZYTEC™ GX Coating: For general outdoor use. Compatible with most above ground pressure treated lumber. For ground contact treated lumber, areas within one mile of saltwater, near swimming pools, exposure to corrosive chemicals, or other areas where corrosion is more like to occur, use proper grade **Stainless Steel**. Always follow timber manufacturer's recommendations for fasteners.

Common Applications

- Commercial & residential
- Landscaping Timbers
- Heavy duty lumber
- LVL (Laminated Veneer Lumber)
- Deck framing
- Ledgers
- Posts
- Beams
- And Much more!

Sizes Available: #18 x 4" to #18 x 11"

General Info	
Type of Screw	Hex Head Structural Wood Screw
Material	Heat Treated, Hardened Steel
Coating	ZYTEC™ GX
Head Style	5/16" Hex Head
Point Type	Modified Type 17
Construction #18	
Head diameter (inch)	0.630"
Minor thread diameter	0.205"
Major thread diameter	0.315"
Shaft diameter	0.226"
Drive Size	5/16" HEX
Product Range #18	
Length	Thread
4"	2"
5"	2-3/4"
6"	2-3/4"
7"	2-3/4"
9"	2-3/4"
11"	2-3/4"



WWW.SCREW-PRODUCTS.COM

9401 Bujacich Rd. Bldg 1B, Gig Harbor, WA 98332
Toll-Free 1-877-844-8880

Weights and counts subject to change without notice.

THE ULTIMATE FASTENERS

FOLLOW US



#SCREWPRODUCTSINC

Jun 1, 2020