Strong-Drive®
SDWS **TIMBER SS** Screw

Structural Wood and Engineered Wood Connections Including Docks, Piers and Boardwalks


The SDWS Timber SS screw is a 0.276"-diameter Type 316 stainless-steel fastener suitable for marine and coastal applications where severe-corrosion resistance is a necessity. The SDWS Timber SS screw has a SawTooth™ point and flat washer head that make it the ideal choice for use on docks, wharves, piers, boardwalks and ledgers.

Features:

- 0.276" shank diameter for heavy-duty structural applicatons
- SawTooth™ point design for fast starts and no predrilling
- Ideal replacement for spikes, lag bolts and lag screws
- No predrilling, no counterboring required for most applications
- Large flat head with nibs can drive flush to surface — no protrusions
- Large, deep T50 6-lobe recess for a secure drive (replacement driver bit — BIT50T-125-RC1)

Codes/Standards: N/A

US Patent 9,523,383



Type 316 Stainless Steel

Size Dia. x L (in.)	Thread Length (in.)	Flagged Fasteners		Retail Clamshell		Carton		Bucket	
		Fast. per Pack	Model No.	Fast per Pack	Model No.	Fast. per Pack	Model No.	Fast. per Pack	Model No.
0.276 x 3	2	1	SDWS27300SS-RP1	10	SDWS27300SS-RC10	30	SDWS27300SS-R30	—	—
0.276 x 4	3	1	SDWS27400SS-RP1	10	SDWS27400SS-RC10	30	SDWS27400SS-R30	350	SDWS27400SS
0.276 x 5	3	1	SDWS27500SS-RP1	10	SDWS27500SS-RC10	30	SDWS27500SS-R30	300	SDWS27500SS
0.276 x 6	3	1	SDWS27600SS-RP1	10	SDWS27600SS-RC10	30	SDWS27600SS-R30	300	SDWS27600SS
0.276 x 8	3	1	SDWS27800SS-RP1	10	SDWS27800SS-RC10	30	SDWS27800SS-R30	200	SDWS27800SS
0.276 x 10	3	1	SDWS271000SS-RP1	10	SDWS271000SSRC10	30	SDWS271000SS-R30	—	—
0.276 x 12	3	1	SDWS271200SS-RP1	—	—	30	SDWS271200SS-R30	—	—

Flagged fasteners per master carton: 40.

C-F-2019 ©2019 SIMPSON STRONG-TIE COMPANY INC.