## *Strong-Drive®*
## DWP **WOOD SS** Screw

*Decking, Docks and Boardwalks; Load-rated General Exterior Applications*

The Strong-Drive DWP Wood SS screw is a powerful, load-rated fastening solution for deck, dock and general exterior applications where extra corrosion protection and load specifications are required. The #12 and #14 Strong-Drive DWP Wood SS flat-head screws are structural fasteners that have been tested in accordance with ICC-ES acceptance criteria AC233 and are load rated for shear, pull-through and withdrawal resistance. With its specially designed sharp-point and unique box-threads, the DWP WOOD SS is a great solution for exterior structural connections, such as on docks, boardwalks and decks near water or where they will be exposed to high or severe corrosion. Choose Type 316 stainless steel for seaside and coastal environments.


### Features:

- Unique "box" thread design with raised-ridge technology greatly reduces driving torque, which allows you to drive more screws on a single battery charge
- Specially designed sharp point penetrates hard wood products with ease
- Use with wood, engineered wood and polymer materials
- 6-lobe drive provides a secure bit fit resulting in an easy drive and long bit life
- Choose Type 316 stainless steel for seaside applications

**For Technical Data and Loads**, see Technical Supplement

### Flat Head


### Type 316 Stainless Steel




| Size | Length (in.) | Head Dia. (in.) | Bit Size | Apporx. Count per lb. | 1 lb. Model No. | 5 lb. Model No. | Deck Pack | | Bucket | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | Count | Model No. | Count | Model No. |
| #12 | 2½ | 0.44 | T27 | 56 | T12250WP1 | T12250WP5 | — | — | 1,750 | T12250WPB |
| #12 | 3 | 0.44 | T27 | 48 | T12300WP1 | T12300WP5 | — | — | 1,500 | T12300WPB |
| #12 | 3½ | 0.44 | T27 | 42 | T12350WP1 | T12350WP5 | — | — | 1,000 | T12350WPB |
| #12 | 4 | 0.44 | T27 | 36 | T12400WP1 | T12400WP5 | 100 | T12400WPP | 750 | T12400WPB |
| #12 | 4½ | 0.44 | T27 | 32 | T12450WP1 | T12450WP5 | — | — | 750 | T12450WPB |
| #12 | 5 | 0.44 | T27 | 29 | T12500WP1 | T12500WP5 | — | — | 500 | T12500WPB |
| #12 | 6 | 0.44 | T27 | 24 | T12600WP1 | T12600WP5 | — | — | 600 | T12600WPB |
| #14 | 3 | 0.46 | T27 | 36 | T14300WP1 | T14300WP5 | — | — | 1,000 | T14300WPB |
| #14 | 3½ | 0.46 | T27 | 33 | T14350WP1 | T14350WP5 | — | — | 750 | T14350WPB |
| #14 | 4 | 0.46 | T27 | 26 | — | T14400WP5 | 100 | T14400WPP | 700 | T14400WPB |
| #14 | 5 | 0.46 | T27 | 21 | T14500WP1 | T14500WP5 | — | — | 500 | T14500WPB |
| #14 | 6 | 0.46 | T27 | 18 | T14600WP1 | T14600WP5 | — | — | 500 | T14600WPB |

### Flat Head

### Type 305 Stainless Steel




| Size | Length (in.) | Head Dia. (in.) | Bit Size | Apporx. Count per lb. | 1 lb. Model No. | 5 lb. Model No. | Deck Pack | | Bucket | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | Count | Model No. | Count | Model No. |
| #12 | 2½ | 0.44 | T27 | 56 | — | S12250WP5 | — | — | 1,750 | S12250WPB |
| #12 | 3 | 0.44 | T27 | 48 | S12300WP1 | S12300WP5 | — | — | 1,500 | S12300WPB |
| #12 | 3½ | 0.44 | T27 | 42 | S12350WP1 | S12350WP5 | — | — | 1,000 | S12350WPB |
| #12 | 4 | 0.44 | T27 | 36 | S12400WP1 | S12400WP5 | 100 | S12400WPP | 800 | S12400WPB |
| #12 | 4½ | 0.44 | T27 | 32 | S12450WP1 | S12450WP5 | — | — | 750 | S12450WPB |
| #12 | 5 | 0.44 | T27 | 29 | S12500WP1 | S12500WP5 | — | — | 500 | S12500WPB |
| #14 | 4 | 0.46 | T27 | 26 | — | S14400WP5 | — | — | 700 | S14400WPB |

6-lobe bit replacements: T27 uses BIT27T-2.

C-F-2019 ©2019 SIMPSON STRONG-TIE COMPANY INC.