

Exterior Nails


Roofing Nail — Annular Ring Shank

Features:

- Large, flat head provides extra bearing surface to firmly secure roofing material
- Annular ring shank increases withdrawal resistance to provide a secure attachment to wood members and plywood roof decks
- Longer lengths ideal for installing curved Spanish roof tiles and thicker slate
- Aluminum nails also available with a screw shank; call Simpson Strong-Tie for details (800) 999-5099


Installation Tips:

- For slate roofs, determine the correct nail length by doubling the slate thickness and adding one inch



Type 316 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.	
—	3/4	10	0.131	3/8	0.375	281	T7510ARN1	T7510ARN5	T7510ARNB
2d	1	10	0.131	3/8	0.375	212	T210ARN1	T210ARN5	T210ARNB
3d	1 1/4	10	0.131	3/8	0.375	166	T310ARN1	T310ARN5	T310ARNB
3d	1 1/4	11	0.120	1/2	0.344	199	T311ARN1	T311ARN5	T311ARNB
4d	1 1/2	10	0.131	3/8	0.375	139	T410ARN1	T410ARN5	T410ARNB
4d	1 1/2	11	0.120	1/2	0.344	170	T411ARN1	T411ARN5	T411ARNB
5d	1 3/4	10	0.131	3/8	0.375	126	T510ARN1	T510ARN5	T510ARNB
6d	2	10	0.131	3/8	0.375	105	T610ARN1	T610ARN5	T610ARNB
6d	2	11	0.120	1/2	0.344	136	—	—	T611ARNB
8d	2 1/2	10	0.131	3/8	0.375	91	T810ARN1	T810ARN5	T810ARNB
10d	3	10	0.131	3/8	0.375	78	T1010ARN1	T1010ARN5	T1010ARNB



Type 304 Stainless Steel


Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.	
—	3/4	10	0.131	3/8	0.375	281	S7510ARN1	S7510ARN5	S7510ARNB
2d	1	10	0.131	3/8	0.375	212	S210ARN1	S210ARN5	S210ARNB
3d	1 1/4	10	0.131	3/8	0.375	166	S310ARN1	S310ARN5	S310ARNB
3d	1 1/4	11	0.120	3/8	0.375	199	S311ARN1	S311ARN5	S311ARNB
4d	1 1/2	10	0.131	3/8	0.375	139	S410ARN1	S410ARN5	S410ARNB
4d	1 1/2	11	0.120	3/8	0.375	170	S411ARN1	S411ARN5	S411ARNB
5d	1 3/4	10	0.131	3/8	0.375	126	S510ARN1	S510ARN5	S510ARNB
5d	1 3/4	11	0.120	3/8	0.375	149	S511ARN1	S511ARN5	S511ARNB
6d	2	10	0.131	3/8	0.375	105	S610ARN1	S610ARN5	S610ARNB
6d	2	11	0.120	3/8	0.375	136	S611ARN1	S611ARN5	S611ARNB
8d	2 1/2	10	0.131	3/8	0.375	91	S810ARN1	S810ARN5	S810ARNB
10d	3	10	0.131	3/8	0.375	78	S1010ARN1	S1010ARN5	S1010ARNB

These products are subject to quantities on hand or may require special ordering and are subject to minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.

Exterior Nails


Roofing Nail — Annular Ring Shank (cont.)

Copper



Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)		Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
—	¾	11	0.120	¾	0.375	302	C7511ARN1	C7511ARN5	C7511ARNB
2d	1	10	0.131	7/16	0.438	187	C210ARN1	C210ARN5	C210ARNB
2d	1	11	0.120	¾	0.375	229	C211ARN1	C211ARN5	C211ARNB
3d	1¼	10	0.131	7/16	0.438	147	C310ARN1	C310ARN5	C310ARNB
3d	1¼	11	0.120	¾	0.375	187	C311ARN1	C311ARN5	C311ARNB
4d	1½	10	0.131	7/16	0.438	123	C410ARN1	C410ARN5	C410ARNB
4d	1½	11	0.120	¾	0.375	155	C411ARN1	C411ARN5	C411ARNB
5d	1¾	10	0.131	7/16	0.438	112	C510ARN1	C510ARN5	C510ARNB
5d	1¾	11	0.120	¾	0.375	139	C511ARN1	C511ARN5	C511ARNB
6d	2	10	0.131	7/16	0.438	93	C610ARN1	C610ARN5	C610ARNB
6d	2	11	0.120	¾	0.375	124	C611ARN1	C611ARN5	C611ARNB
8d	2½	10	0.131	7/16	0.438	81	C810ARN1	C810ARN5	C810ARNB
8d	2½	11	0.120	¾	0.375	108	—	—	C811ARNB
10d	3	10	0.131	7/16	0.438	67	C1010ARN1	C1010ARN5	C1010ARNB

Aluminum



Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)		Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
2d	1	11	0.120	¾	0.375	810	—	A211ARN5	A211ARNB
3d	1¼	11	0.120	¾	0.375	686	A311ARN1	A311ARN5	A311ARNB
4d	1½	11	0.120	¾	0.375	577	—	—	A411ARNB
3d	1¼	9	0.148	7/16	0.438	440	—	—	A39ARNB