The ML angle combines strength and versatility through the use of Strong-Drive SDS Heavy-Duty Connector screws. Fastener holes are staggered to minimize wood splitting and opposing hole pattern allows for back-to-back installation without fastener interference.

Material: 12 gauge

Finish: MLZ — ZMAX® coating; MLSS — stainless steel.


See Corrosion Information, pp. 13-15.


Installation:

C-C-2019 @2019 SIMPSON STRONG-TIE COMPANY INC.

- Use all specified fasteners; see General Notes
- ¼" x 1½" Strong-Drive SDS Heavy-Duty Connector screws are not provided with the angle
- Use stainless-steel fasteners with stainless connectors

Codes: See p. 12 for Code Reference Key Chart





0

0

0

0

0

ML28Z



0

0


0


These products are available with additional corrosion protection. For more information, see p. 15.


	Model No.	H (in.)	Connector Quantity	SDS Fasteners (Total)	DF/SP Allowable Loads				SPF/HF Allowable Loads				Code
					(100)	(115)	(125)	(160)	(100)	(115)	(125)	(160)	Ref.
	ML23Z	3	1	(4) 1/4" x 1 1/2"	405	405	405	405	310	310	310	310	IBC
			2	(8) 1/4" x 1 1/2"	865	865	865	865	660	660	660	660	
	ML24Z	4	1	(6) 1/4" x 1 1/2"	595	595	595	595	450	450	450	450	IBC, FL
			2	(12) 1/4" x 1 1/2"	1,500	1,635	1,635	1,635	1,080	1,240	1,240	1,240	
	ML26Z	6	1	(8) 1/4" x 1 1/2"	1,000	1,075	1,075	1,075	720	830	900	935	
			2	(16) 1/4" x 1 1/2"	2,000	2,145	2,145	2,145	1,440	1,625	1,625	1,625	
	ML28Z	8	1	(10) 1/4" x 1 1/2"	1,250	1,280	1,280	1,280	900	970	970	970	IBC
			2	(20) 1/4" x 1 1/2"	2,500	2,665	2,665	2,665	1,800	2,020	2,020	2,020	
	ML210Z	10	1	(12) 1/4" x 11/2"	1,285	1,285	1,285	1,285	970	970	970	970	
			2	(24) 1/4" x 1 1/2"	2,930	2,930	2,930	2,930	2,160	2,220	2,220	2,220	



2. Fasteners: SDS screws are Simpson Strong-Tie® Strong-Drive® screws. See pp. 21–22 for fastener information.







ML210Z

