Collated Exterior Wood Screws






Deck·**Drive**™ DSV WOOD Screw

Preservative-Treated Decking and Exterior Wood-to-Wood Applications

The Deck-Drive™ DSV Wood screw is a powerful fastening solution for preservative-treated decking applications. With its underhead nibs and fast-start tip, the DSV is ideally suited to be driven and countersunk into today's wood deck boards. The shank is designed to withstand the swelling and shrinkage that is common with fast-growth lumber. Available in hand-drive and in collated strips for use in our Quik Drive® auto-feed screw driving system, DSV screws are also offered in a variety of sizes to fasten fascia

Features:

- Low-torque threads
- Ribbed-head design countersinks easily and provides a clean, finished appearance
- · High-low tip provides fast starts
- Optimized threads for dimensional lumber
- Quik Guard®coating provides corrosion resistance for exterior and certain preservative-treated wood applications
- Meets the performance requirements of AC257 exposure conditions 1 and 3
- · Colors to blend in with most woods
- · This screw is also available in bulk for hand-drive installation; see p. 78 for details



Quik Guard® Coating — Tan

| Size | Length (in.) | 500 ct. Model No. | 750 ct. Model No. | 1,000 ct. Model No. | 1,500 ct. Model No. | 2,000 ct. Model No. | PR0 300S | PR0 250 | PR0 200S |
|------|-----------------|----------------------|----------------------|------------------------|------------------------|------------------------|-------------|------------|-------------|
| # 8 | 1 1/4 | _ | HCKDSVT114S | _ | _ | DSVT114S | | | ✓ |
| #8 | 1% | _ | HCKDSVT158S | _ | _ | DSVT158S | | ✓ | ✓ |
| #10 | 2 | _ | HCKDSVT2S | _ | DSVT2S | _ | ✓ | ✓ | ✓ |
| #10 | 21/2 | HCKDSVT212S | _ | DSVT212S | _ | _ | ✓ | ✓ | |
| #10 | 3 | HCKDSVT3S | _ | DSVT3S | _ | _ | ✓ | | |





Quik Guard® Coating — Red

| Size | Length (in.) | 500 ct. Model No. | 750 ct. Model No. | 1,000 ct. Model No. | 1,500 ct. Model No. | 2,000 ct. Model No. | PR0 300S | PR0 250 | PR0 200S |
|------|-----------------|----------------------|----------------------|------------------------|------------------------|------------------------|-------------|------------|-------------|
| #8 | 11⁄4 | | HCKDSVR114S | | | DSVR114S | | | ✓ |
| #8 | 1 % | | HCKDSVR158S | | | DSVR158S | | ✓ | ✓ |
| #10 | 2 | | HCKDSVR2S | | DSVR2S | | ✓ | ✓ | ✓ |
| #10 | 21/2 | HCKDSVR212S | | DSVR212S | | | ✓ | ✓ | |
| #10 | 3 | HCKDSVR3S | | DSVR3S | | | ✓ | | |





| Quik Guard® Coating — Gray ———————————————————————————————————— | | | | | | | | | | |
|---|------|-----------------|----------------------|----------------------|------------------------|------------------------|------------------------|-------------|------------|-------------|
| | Size | Length (in.) | 500 ct. Model No. | 750 ct. Model No. | 1,000 ct. Model No. | 1,500 ct. Model No. | 2,000 ct. Model No. | PR0 300S | PR0 250 | PR0 200S |
| | #10 | 21/2 | | | DSVG212S | | | ✓ | ✓ | |
| | #10 | 3 | | | DSVG3S | | | ✓ | | |

