

## Interior Wood Screws

### Strong-Drive® WSNTL SUBFLOOR Screw

#### Subfloor and Sheathing Projects

The ICC-ES ESR-1472 code-listed Strong-Drive® WSNTL Subfloor screw has a unique thread pattern that allows for quick and seemingly effortless installations. With lateral, shear and withdrawal values that exceed those of 10d common nails, the holding power of the WSNTL screw eliminates the gaps between the joist and subfloor that cause floor squeaks. The WSNTL Subfloor screw countersinks easily and backs out smoothly, allowing for easy future access to floor cavities.

#### Features:

- Deep recessed square drive holds bits tight, reducing cam-outs
- Twin-lead thread for quick installation
- Nibbed flat head for easy countersinking
- Yellow zinc coating for interior applications
- This screw is also available collated for the Quik Drive® system; see pp. 268–269 for details

**Codes/Standards:** ICC-ES ESR-1472


**For Technical Data and Loads,** see p. 366

#### Yellow Zinc Coating

Length (in.)	Size	Coating	Head Dia. (in.)	Drive Type	Retail Pack		Contractor Pack	
					Fasteners per Pack	Model No.	Fasteners per Pack	Model No.
2	#8	Yellow zinc	0.33	#3 square	100	WSNTL2R100	500	WSNTL2R500
2½	#8	Yellow zinc	0.33	#3 square	80	WSNTL212R80	400	WSNTL212R400
3	#8	Yellow zinc	0.33	#3 square	60	WSNTL3R60	300	WSNTL3R300

Fastener penetration into supporting member must be at least 1¾".

Replacement driver bit: BIT3S-2-RC3.



### Wafer-Head Screw

#### Common Application:

General wood-to-wood fastening


#### Features:

- Wafer head
- Deep #2 Phillips drive reduces cam-out and makes driving easier
- Sharp point for fast starts
- Clear zinc electro-galvanized finish; for information on corrosion, materials and coatings, see pp. 17–21

**For Technical Data and Loads,** see p. 339

#### Clear Zinc Coating

Size	Length (in.)	Head Diameter (in.)	Carton Quantity	Model No.
#8	1¼	0.42	100	SD8x1.25-R



### MTH Underlayment Screw

#### Underlayment Fastening Applications

#### Prevents Squeaks by Holding Underlayment Tight

The MTH Underlayment screw is designed for fast and secure underlayment to subfloor installations. Unlike nails, the MTH Underlayment screw has an intricate thread pattern designed to prevent squeaking by holding underlayment tight to the subfloor and thus preventing pull-out. Its compact trim-head allows for a flush surface and prevents floor coverings from settling in countersink recesses.

#### Features:

- Deep recessed square drive holds bits tight, reducing cam-outs
- High-low thread for easy driving and holding underlayment tight
- Specially-designed sharp point for fast starts
- Trim-Head with nibs for easy countersinking
- Available collated for Quik Drive® system; see p. 271 for details

#### Gray Phosphate

Length (in.)	Size	Coating	Head Dia. (in.)	Drive Type	Retail Pack		Contractor Pack	
					Fasteners per Pack	Model No.	Fasteners Per Pack	Model No.
1¼	#7	Gray phosphate	0.27	#2 square	250	MTH114R250	1,200	MTH114R1200

Replacement driver bit: BIT2S-2-RC3.

