

# Exterior Wood Screws

## Deck-Drive™ DSV WOOD Screw

### Preservative-Treated Decking and Exterior Wood-to-Wood Applications


The Deck-Drive® DSV Wood screw is a powerful fastening solution for preservative-treated decking applications. With its under-head nibs and fast-start tip, the DSV is ideally suited to be driven and countersunk into today's wood deck boards. The shank is designed to withstand the swelling and shrinkage that is common with fast-growth lumber. Available in hand-drive and in collated strips for use in our Quik Drive® auto-feed screw driving system, DSV screws are also offered in a variety of sizes to fasten fascia and trim.

#### Features:

- Low-torque threads allow up to 35% more screws to be driven on a battery charge
- Ribbed-head design countersinks easily and provides a clean, finished appearance
- High-low tip provides fast starts
- Optimized threads for dimensional lumber
- Quik Guard coating provides corrosion resistance for exterior and certain preservative-treated wood applications
- Painted to blend with wood decking
- T-25 6-lobe driver bit included (replacement driver bit – BIT25T-2)
- Meets performance requirements of AC257 exposure conditions 1 and 3


This screw is also available collated for the Quik Drive® system. See p. 256 for details.

U.S. Patent 6,074,149



### Quik Guard® Coating – Tan

Size	Length (in.)	Head Dia. (in.)	Approx. Count Per Pound	1 lb. Model No.	5 lb. Model No.	350 ct. Model No.	Mini-Bulk	
							Model No.	Count
#8	1¼	0.33	194	DSVT114R1LB	DSVT114R5LB	DSVT114R350	DSVT114MB	1,750
#8	1½	0.33	159	DSVT158R1LB	DSVT158R5LB	DSVT158R350	DSVT158MB	1,750
#10	2	0.33	113	DSVT2R1LB	DSVT2R5LB	DSVT2R350	DSVT2MB	1,750
#10	2½	0.33	91	DSVT212R1LB	DSVT212R5LB	DSVT212R350	DSVT212MB	1,750
#10	3	0.33	76	DSVT3R1LB	DSVT3R5LB	DSVT3R350	DSVT3MB	1,750
#10	3½	0.33	66	DSVT312R1LB	DSVT312R5LB	DSVT312R350	DSVT312MB	1,000
#10	4	0.33	59	DSVT4R1LB	DSVT4R5LB	DSVT4R350	DSVT4MB	1,000



### Quik Guard® Coating – Red

Size	Length (in.)	Head Dia. (in.)	Approx. Count Per Pound	1 lb. Model No.	5 lb. Model No.	350 ct. Model No.	Mini-Bulk	
							Model No.	Count
#8	1¼	0.33	194	DSVR114R1LB	DSVR114R5LB	DSVR114R350	DSVR114MB	1,750
#8	1½	0.33	159	DSVR158R1LB	DSVR158R5LB	DSVR158R350	DSVR158MB	1,750
#10	2	0.33	113	DSVR2R1LB	DSVR2R5LB	DSVR2R350	DSVR2MB	1,750
#10	2½	0.33	91	DSVR212R1LB	DSVR212R5LB	DSVR212R350	DSVR212MB	1,750
#10	3	0.33	76	DSVR3R1LB	DSVR3R5LB	DSVR3R350	DSVR3MB	1,750
#10	3½	0.33	66	DSVR312R1LB	DSVR312R5LB	DSVR312R350	DSVR312MB	1,000
#10	4	0.33	59	DSVR4R1LB	DSVR4R5LB	DSVR4R350	DSVR4MB	1,000