

Collated Interior Wood Screws



SIMPSON

Strong-Tie®

WSHL Subfloor Screw

Common Applications:

Subfloor to wood

Features:

- Ribbed flat head with nibs for easy countersinking
- #2 square drive (driver bit in each box; replacement bit model BIT2S)
- High-low threads
- Sharp point
- Gray phosphate coating
- Curved collation
- 1:1 replacement for 8d common nails when used with floor sheathing $1\frac{1}{32}$ – $2\frac{3}{32}$ " thick



Gray Phosphate Coating

Length (in.)	Shank Size	Carton Quantity	Model No.	PRO 200S	PRO 250	PRO 300S
1 3/4	#7	2,000	WSHL134S7	✓	✓	✓

DWC Drywall Screw

Common Applications:

Drywall to wood

Features:

- Bugle head
- #2 Phillips (driver bit in each box; replacement bit model BIT2P)
- Coarse threads
- Sharp point
- Curved collation

Codes/Standards: ASTM C1002 Type W



Gray Phosphate Coating

Length (in.)	Shank Size	Retail Pack		Contractor Pack		PRO 200	PRO 250DW
		Fasteners Per Pack	Model No.	Fasteners Per Pack	Model No.		
1	#6	—	—	2,500	DWC1PS	✓	
1 1/4	#6	1,000	HCKDWC114PS	2,500	DWC114PS	✓	
1 5/8	#6	1,000	HCKDWC158PS	2,500	DWC158PS	✓	
2	#6	—	—	2,000	DWC2PS	✓	✓
2 1/2	#8	—	—	1,500	DWC212PS		✓