Collated Metal Screws




DWF Drywall-to-CFS Screw

Common Applications:
Drywall to cold-formed steel (Recommended thicknesses: 33, 27 and 18 mil / 20, 22 and 25 ga.)

Features:
- Bugle head
- #2 Phillips (driver bit in each box; replacement bit model BIT2P)
- Fine threads
- Sharp point
- Gray phosphate coating
- Curved collation

Codes/Standards: ASTM C1002-04 Type S compliant

For Technical Data and Loads, see p. 376



Gray Phosphate Coating

Length (in.)	Shank Size	Carton Quantity	Model No.	PRO200
1¼	#6	2,500	DWF114PS	✓
1⅝	#6	2,500	DWF158PS	✓


DWFSD Drywall-to-CFS Screw

Common Applications:
Drywall to cold-formed steel (Recommended max. steel thicknesses: 43 mil / 18 ga.)

Features:
- Bugle head
- #2 Phillips (driver bit in each box; replacement bit model BIT2P)
- Fine threads
- #2 drill point
- Curved collation


Codes/Standards: ASTM C954 compliant

For Technical Data and Loads, see p. 376



Quik Guard®

Length (in.)	Shank Size	Threads Per Inch	Box Quantity	Model No.	PRO 200S	PRO 200
1¼	#6	20	2,500	DWFSDQ114PS	✓	✓



Yellow Zinc Coating

Length (in.)	Shank Size	Threads Per Inch	Box Quantity	Model No.	PRO 200S	PRO 250DW	PRO 200
1¼	#6	20	2,500	DWFSD114PS	✓		✓
1⅝	#6	20	2,500	DWFSD158PS	✓		✓
1⅞	#6	20	2,000	DWFSD178PS	✓	✓	✓
2⅜	#8	20	1,500	DWFSD238PS		✓	

C-F-2017 ©2017 SIMPSON STRONG-TIE COMPANY INC.