

Exterior Nails

Strong-Drive® SCNR RING-SHANK CONNECTOR Nail

For Simpson Strong-Tie® Connectors

Strong-Drive SCNR Ring-Shank Connector nails are the best choice for achieving full load values in stainless steel connectors. Choose Type 316 stainless-steel nails when using stainless-steel connectors.

Features:

- Head ID stamp for easy identification
- Type 316 stainless steel for use with stainless-steel connectors
- Use stainless-steel ring-shank nails for full connector loads


See p. 131 for collated Strong-Drive SCNR Ring-Shank Connector nails.

For Technical Data and Loads, see Technical Supplement



Type 316 Stainless Steel

Diameter x Length (in.)	Gauge	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	Retail Pack Count	Retail Pack	Mini-Bulk Count	Mini-Bulk	Bulk Count	Bulk Model No.
0.131 x 1½	10	0.28	150	SSNA8	150	SSNA8D	750	SSNA8D5	3,750	SSNA8DB
0.131 x 2½	10	0.28	90	SSA8D	90	SSA8DD	450	SSA8D5	2,250	SSA8DB
0.148 x 1½	9	0.31	120	SSNA10	120	SSNA10D	600	SSNA10D5	3,000	SSNA10DB
0.148 x 3	9	0.31	50	SSA10D	50	SSA10DD	250	SSA10D5	1,250	SSA10DB
0.162 x 3½	8	0.34	40	SSA16D	40	SSA16DD	200	SSA16D5	1,000	SSA16DB




Hot-Dip Galvanized – Class D

Diameter x Length (in.)	Gauge	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	1 lb. Box Model No.	Approx. 5 lb. Count	5 lb. Box Model No.	Approx. 25 lb. Count	25 lb. Box Model No.
0.250 x 2½	3½	0.50	27			N54AHDG — Sold by the pound			



Bright

Diameter x Length (in.)	Gauge	Head Diameter (in.)	Approx. Count per lb.	1 lb. Model No.	1 lb. Box Model No.	Approx. 5 lb. Count	5 lb. Box Model No.	Approx. 25 lb. Count	25 lb. Box Model No.
0.250 x 2½	3½	0.50	27			N54A — Sold by the pound			



Bright nails are not for use in exterior or preservative-treated wood applications.