# C-F-2019 @ 2019 SIMPSON STRONG-TIE COMPANY INC

## **Exterior Screws**



# EB-TY® Premium Hidden Deck-Fastening System™

The EB-TY Premium Hidden Deck-Fastening System is the ideal solution that blends strength with ease of installation in a fastener that won't detract from the deck's finished appearance. Simpson Strong-Tie has redesigned the award-winning EB-TY Hidden Deck-Fastening System by integrating a Type 300 series stainless-steel reinforcing plate that adds stiffness to hold boards in place securely, yet maintains flexibility when seasonal contraction and expansion occur. Combine this innovative new design with our EB-GUIDE predrilling tool, and you have a system that not only provides hidden strength, but is also easy to install.

#### Metal Reinforcement

- · Provides holding and pullover resistance
- Type 300 series stainless-steel plate ensures lasting durability in demanding environments
- Prevents over-driving of the screw, helping to ensure consistent, quality installations

#### **Angled-Screw Attachment**

- Ensures direct attachment of the board to the joist
- Keeps the board from "walking" or sliding
- · Allows tighter spacing

#### Covers the Joist

- Protection from direct exposure to sun and rain
- Visually more appealing after installation

US Patents: 6,402,415; 7,578,105

For more information and access to the EB-TY Premium instructional video, visit strongtie.com/ebtypremium.



# **Exterior Screws**

# SIMPSON Strong-Tie

### EB-TY® Premium

Size (in.)	Screw Material (Trim Head)	EB-TY Premium Qty.	Screw Qty.	Ipê Plug Qty.	Model No.		
362" Board Spacing — use for 34" to 11½" air-dried decking							
#7 x 2 1⁄4	Type 305	100	115	6	EB332WDR100		
#7 x 2 1⁄4	Type 305	175	190	12	EB332WDR175		
#7 x 2 1⁄4	Type 305	275	300	20	EB332WDR275		
#7 x 2 1⁄4	Type 316	175	190	12	EB332WD316R175		
#7 x 1%	Type 316	275	190	12	EB332WD316R275		
3/16" Board Spacing — use for 3/4" to 11/2" kiln-dried decking							
#7 x 2 1⁄4	Type 305	100	115	6	EB316WDR100		
#7 x 2 1⁄4	Type 305	175	190	12	EB316WDR175		
#7 x 2 1⁄4	Type 305	275	300	20	EB316WDR275		
#7 x 2 1⁄4	Type 316	175	190	12	EB316WD316R175		
#7 x 15%	Type 316	275	190	12	EB316WD316R275		
1/4" Board Spacing — use for 3/4" to 11/2" kiln-dried decking							
#7 x 2 1⁄4	Type 305	100	115	6	EB14WDR100		
#7 x 2 1⁄4	Type 305	175	190	12	EB14WDR175		
#7 x 2 1⁄4	Type 305	275	300	20	EB14WDR275		
#7 x 2 1⁄4	Type 316	175	190	12	EB14WD316R175		
#7 x 1%	Type 316	275	190	12	EB14WD316R275		



EB332W Series



EB316W Series



EB14W Series

- 1. EB332WP, EB14WP, EB316WP series with 1%" screws are designed for roof decks installed on 1" sleepers.
- Model numbers corresponding to kits with 100 and 175 count EB-TY Premium include one drill bit, T-15 driver bit a
  nd EB-GUIDE tool. Quantities of 275 count come with two drill bits, driver bits and EB-GUIDE tools.
- 3. Kiln-dried decking has a moisture content of generally 19% or less. Air-dried decking is generally greater than 19% moisture content.

# Replacement Parts

Description	Quantity	Model No.
#7 x 21/4" Trim-Head Screw, Type 316	20	T07225FT20BK
#7 x 15/8" Trim-Head Screw, Type 316	20	T07162FT20BK
Replacement T15 6-Lobe Driver Bit	3	BIT15T-2-RC3
1/8" Quick-Release Wood Drill Bit	3	WDB18QR3-R3
lpê Wood Plug %"	100	WDPLUG-100
EB-GUIDE Predrill Tool	1	EB-GUIDE

# lpê Wood Plugs

#### **Features**

- Made of high-quality lpê and tapered for ease of use
- For use on decks using the EB-TY® system (first boards, aprons, etc.); also stairs and railings

Plug Diameter (in.)	Plug Length (in.)	Count Quantity	Model No.
3/8	7/16	100	WDPLUG-100
3/8	7/16	2,000	WDPLUG2M

