



**PREMIUM LUBRICANTS &
SPECIALTY FLUIDS**

FOR SALES WITHIN THE UNITED STATES

Contact Smitty's Supply at **1-800-256-7575** and you will be connected with your regional sales manager.

Orders may also be placed by emailing **nationalorders@smittysinc.net**

Visit www.Smittysinc.net for additional product information including forms for new customers.

For Route Sales In the United States

Contact **1-800-256-7575** or
E-mail: **orders@smittysinc.net**

NEW CUSTOMERS

Visit www.Smittysinc.net and select the new customer button link under Contact. Please fill out the form and e-mail it back to:

sales@smittysinc.net or Fax: **1-985-747-8168**

TECHNICAL INFORMATION

Super S Product Data Sheets and Safety Data Sheets are available for download at:
www.smittysinc.net

For additional information please reach out to the Smitty's Supply technical department:

technical@smittysinc.net

FOR INTERNATIONAL SALES

Orders can be placed by calling **1-800-256-7575**, or by e-mailing:
nationalorders@smittysinc.net

PROMOTIONS

Sign up for the latest Super S promotions and the Super S Engine Protection Plan at:
www.smittysinc.net

VISIT SMITTY'S SUPPLY, INC

We welcome customers to tour our 14+ acre, ISO-certified facility, and to learn about the extensive Super S product line.

To Schedule A Tour, Please call:

1-800-256-7575

Our facility is located at:

Smittys Supply, Inc.
63399 Highway 51 North
Roseland, LA 70456





PREMIUM LUBRICANTS & SPECIALTY FLUIDS

ABOUT SMITTY'S SUPPLY AND 5 THE SUPER S BRAND

PASSENGER CAR MOTOR OIL..... 6

Super S SuperSyn Full Synthetic Motor Oil
Super S Euro SuperSyn Full Synthetic Motor Oil
Super S Multi-Flo Motor Oil
Super S Multi-Flo High Mileage Motor Oil
Super S dexos1™ Motor Oil
Super S Non-Detergent Motor Oil

HEAVY DUTY ENGINE OILS 12

Super S FG-1000 Heavy Duty Motor Oil
Super S SuperSyn Fleet HD Diesel Engine Oil 15W-40
Super S FG-2000 Heavy Duty Synthetic Blend Motor Oil

TRANSMISSION FLUIDS 14

Super S SuperSyn DEXRON®-VI Multi-Vehicle
Full Synthetic ATF
Super S Multi-Purpose D/M ATF
Super S Multi-Vehicle Synthetic Blend ATF
Super S MERCON® V ATF
Super S Type F ATF
Super S ATF 4
Super S SuperSyn Premium Full Synthetic CVT Fluid
Super S SuperSyn Trans-Fluid 50 API MT-1
Manual Transmission Fluid
Super S Type A ATF

PACKAGE FEATURE 17

GEAR OILS 18

Super S GL-1 Gear Oil
Super S GL-4 Extreme Pressure Gear Oil
Super S GL-5 Multi-Purpose Gear Oil
Super S GL-5 Limited Slip Gear Oil
Super S GL-5 Red Tac High Performance Gear Oil
Super S SuperSyn 75W-90 Synthetic Gear Oil
Super S SuperSyn 75W-140 Limited Slip Synthetic Gear Oil
Super S SuperSyn 80W-140 Synthetic Gear Oil
Super S EP Gear Compound
Super S Limited Slip Additive for GL-5 Gear Oils
Super S Marine Outboard Lower Unit Gear Lube

HYDRAULIC FLUIDS 21

Super S Premium Universal Tractor
Hydraulic Fluid

Super S Super Trac® 303 Tractor Hydraulic Fluid
Super S Anti-Wear Hydraulic Fluid
Super S R & O Hydraulic Oil
Super S SuperDraulic™ AW Hydraulic Fluid
Super S Super Trac® TO-4 Fluids
Super S Mining Hydraulic Oil

GREASE 25

Super S Multi-Purpose #2 (MP2) Lithium Grease
Super S Hi-Temp Red #2 EP Lithium Grease
Super S Super CS EP2 Synthetic Grease
Super S Super Blue EP2 Hi-Temp Grease
Super S Super Moly EP2 Grease
Super S Marine EP Synthetic Grease
Super S Super MP2 Graphite Grease
Super S "000" Red Lithium Grease
Super S "00" Cotton Picker Spindle Grease
Super S Cotton Picker Spindle Cleaner

INDUSTRIAL OILS 28

Super S Premium R & O Turbine Oil
Super S Cherry Picker Oil
Super S Sawguide Oil
Super S Quench Oil
Super S Drip Oil
Super S Low Ash Gas Engine Oil
Super S Rock Drill Oil
Super S Rotary Pist/Vac Pump Oil
Super S Transformer Oil
Super S Concrete Form Oil
Super S Heat Transfer Oil

ANTIFREEZE 30

Super S Universal Antifreeze and Coolant
Super S 50/50 prediluted Universal
Antifreeze and Coolant
Super S Full Strength Antifreeze & Coolant
Super S 50/50 Antifreeze & Coolant
Super S Extended Life Antifreeze & Coolant
Super S 50/50 Prediluted Extended Life
Antifreeze & Coolant
Super S Extended Life Heavy Duty Truck
Antifreeze and Coolant
Super S Extended Life 50/50 Heavy Duty
Truck Antifreeze and Coolant
Super S Fleet Antifreeze & Coolant
Super S 50/50 Prediluted Fleet

PREMIUM LUBRICANTS & SPECIALTY FLUIDS

2-CYCLE, 4-CYCLE OIL & TREATMENTS 32

Super S SuperFuel 50:1 2-Cycle Oil & Fuel
 Super S SuperFuel 4-Cycle Fuel
 Super S 2-Cycle Mixing Oil
 Super S SuperSyn Full Synthetic Universal 2-Cycle Engine Oil
 Super S SuperSyn 2-Cycle Full Synthetic Engine Oil with Ethanol & Fuel Stabilizer
 Super S SuperSyn Synthetic Outboard 2-Cycle Marine Oil
 Super S TC-W3 Premium Outboard Multi-Purpose 2-Cycle Oil
 Super S Fuel Stabilizer 2 & 4-Cycle Treatment
 Super S 4-Stroke LawnMower Oil
 Super S Snow Thrower 4-Cycle 5W-30 Engine Oil
 Super S Synthetic Snow Thrower 4-Cycle 5W-30 Engine Oil
 Super S 4-Stroke Motorcycle/ATV Engine Oil
 Super S Ethanol Treatment

CHEMICALS 36

Super S Flat Tire Fix - Cone
 Super S Non-Flammable Brake Parts Cleaner
 Super S Non-Chlorinated Brake Parts Cleaner
 Super S Starting Fluid
 Super S Engine Degreaser
 Super S Flat Tire Fix - Hose
 Super S Air Tool Oil & Jack Oil
 Super S Penetrating Oil
 Super S Choke/Carburetor Cleaner
 Super S De-Icer

TREATMENTS..... 38

Super S Octane Booster
 Super S Oil Treatment
 Super S Fuel Injector Treatment
 Super S Power Steering Sealer
 Super S Motor Flush
 Super S Fuel Stabilizer & Ethanol Treatment
 Super S Transmission Sealer
 Super S Motor Sealer
 Super S Diesel Conditioner & Anti-Gel
 Super S Carb & Fuel Injector Cleaner
 Super S Gas Treatment
 Super S Lead Substitute

CLEANING PRODUCTS..... 40

Super S Super Power Purple Degreaser
 Super S Super Power Car Wash
 Super S Super Power Truck Wash
 Super S Super Power Auto Wash & Wax
 Super S Super Power Tire Shine

Super S Super Power Real White
 SEA-WASH® 11 Cleaner & Dispersant
 SEA-WASH® 8 Non-Flammable Neutral pH7 Cleaner
 SEA-WASH® Citrus Cleaner
 SEA-WASH® WC-10 Cleaner & Dispersant
 SEA-WASH® Super 7 Neutral pH - 100% Concentrate
 SEA-WASH® 2000 Multi-Purpose odor remover & cleaner Neutral pH- 100% Concentrate
 SEA-WASH® Sea-Clear Glass Cleaner
 Super S Aluminum Brightner
 Super S Windshield Washer Concentrate
 Super S Extreme Winter Windshield Washer Fluid - 20°
 Super S Windshield Washer Fluid +32°
 Super S Summer Windshield Washer Fluid +21°
 Super S Winter Windshield Washer Fluid - 0°
 Super S Bug Wash Windshield Washer Fluid +32°

SPECIALTY FLUIDS..... 46

Super S DEF
 Super S Bar & Chain Oil
 Super S Supertac Extreme Tac Bar & Chain Oil
 Super S Premium Power Steering Fluid
 Super S Power Steering Fluid
 Super S DOT 3 Brake Fluid
 Super S DOT 4 Brake Fluid
 Super S DOT 5 Brake Fluid
 Super S Solvent 140
 Super S Mineral Spirits
 Super S K-1 Kerosene
 Super S Oil Stabilizer
 Super S Superdry Industrial Absorbent
 Super S Charcoal Lighter Fluid

CUSTOM PLUS 50

Custom Plus™ Synthetic Blend Motor Oil
 Custom Plus™ Multi-Purpose D/M ATF
 Custom Plus™ Synthetic Blend All Fleet Heavy Duty Motor Oil
 Custom Plus™ Non-Detergent Motor Oil
 Custom Plus™ Synthetic Gear Oil
 Custom Plus™ 80W-140 Synthetic Gear Oil

LICENSES & APPROVALS..... 53

SUPER S SATISFACTION 54





ABOUT SMITTY'S SUPPLY



SMITTY'S SUPPLY, INC. IS A ONE OF A KIND SOLUTION FOR LUBRICANT MANUFACTURING AND DISTRIBUTION.

We provide our customers with a variety of diverse services and turn-key solutions through our ISO Certified facility. Our team of over 450 dedicated employees fully coordinate product development through blending, packaging and distribution to decrease overall time and expense for both bulk and consumer brands.

- Smitty's Supply, Inc. was founded in 1969 and now distributes product to all 50 states and over 50 countries.
- Our expansive facility produced over 65 million gallons of finished product in 2015 and is capable of producing millions more.
- In addition to an extensive private label program, we distribute most major brands including Shell, Pennzoil, Quaker State, Chevron, Castrol and Super S.

WHY SUPER S?

SUPER S is the most complete product line in the industry.

Keep Inventories Manageable

We offer retailers the opportunity to pull in major sellers like Super S Multi-Flo along with specialty items to fill truckloads, cut cost and build greater shelf presence. This has lead to the Super S brand appearing on shelves across all 50 states.

ISO-Certified Facility - A Proven Track Record For Quality.

Smitty's Supply is an ISO 9001:2015 facility, which strives to meet the quality needs of all our customers.



Super S Satisfaction Lubricant Warranty and 10 Year/300,000 Mile Limited Warranty Program for Consumers

The SUPER S SATISFACTION Lubricant Warranty is part of the Consumer Care Program. It's a customer satisfaction program and Lubricant Warranty to guarantee the quality of the fluids and the packaging on all of our products.

Super S has added the Super S Engine Protection Limited Warranty Program for drivers. Drivers may be covered against certain oil-related engine problems for 300,000 miles or 10 years, whichever comes first. Visit www.Smittysinc.net to sign up and to view full details.



SuperSyn™





SUPER S PASSENGER CAR MOTOR OILS

SUPER S SUPERSYN FULL SYNTHETIC MOTOR OIL

Super S SuperSyn is a 100% full synthetic motor oil engineered with the latest lubricant technology to provide the ultimate in engine protection and performance. Engineered for gasoline engines to provide superior protection against engine wear, formation of sludge and extreme high temperatures which can cause conventional oils to break down. Compatible with all conventional and synthetic oils.

0W-40, 5W-20, 10W-30 Meets or exceeds:

API SN-RC • ILSAC GF-5



HOLDS UP IN EXTREME TEMPERATURES



SUPER S EURO SUPERSYN FULL SYNTHETIC MOTOR OIL

Super S Euro SuperSyn Full Synthetic Motor Oil provides among the highest levels of performance and protection offered in passenger car motor oils (PCMOs) by using superior additive technology and 100% synthetic base oils. They meet or exceed specifications for wear control, piston deposits, cleanliness, varnish, sludge, oxidation control, emission system and seal compatibility.

5W-30 Meets or exceeds:

European classifications: ACEA A3/B4-12, A5/B5-12, BMW Longlife-01, MB P229.3/ P229.5, VW 501.01, VW 502.00/505.00 and is suitable for use in Opel GM-LL B-025. It also meets or exceeds American Petroleum Institute (API) SL service classification.

5W-40 Meets or exceeds:

European classifications: ACEA A3/B4-12, BMW Longlife-01, MB P229.5, VW 501.01, VW 502.00/505.00, Porsche A40 and is suitable for use in Opel GM-LL B-025 and Renault 0700, 0710. It also meets or exceeds American Petroleum Institute (API) SN service classification.



PRODUCT	PACKAGING	PART #
0W-40	6/1 Qt	SUS401
	6 Gal	SUS 60401
5W20	6/1 Qt	SUS 391
	6 Gal	SUS 60391
	55 Gal	SUS 392
5W40	6/1 Qt	SUS 397
	3/1 Gal	SUS 397-3
	55 Gal	SUS 399
10W-30	6/1 Qt	SUS 350
	6 Gal	SUS 60350
	55 Gal	SUS 353

PRODUCT	PACKAGING	PART #
5W-30	6/1 Qt	SUS 395
	6 Gal	SUS 60395
	55 Gal	SUS 395-55
5W40	6/1 Qt	SUS 396
	6 Gal	SUS 60396
	55 Gal	SUS 396-55
	TOTE	SUS 396TOTE

Multi Flo[®]

Synthetic Blend



SUPER S PASSENGER CAR MOTOR OILS

SUPER S MULTI-FLO MOTOR OIL

Super S Multi-Flo Motor Oils are formulated to provide the highest levels of performance and protection in passenger car motor oils (PCMO). They meet the latest fuel economy standards while exceeding the car manufacturer's ILSAC GF-5 standards for wear control, piston deposits, cleanliness, varnish, sludge, oxidation control, emission system and seal compatibility.

Super S Multi-Flo motor oils are synthetic blends in grades 5W-20, 5W-30, 10W-30, 10W-40 and 20W-50. Super S Multi-Flo 5W-20, 5W-30, 10W-30, are API licensed SN-RC, resource conserving, with ILSAC GF-5 certification.

Super S Multi-Flo SN Motor Oils in grades SAE 30 and SAE 40 are formulated with conventional motor oils. They are licensed by API for the SN Service Category.

5W-20, 5W-30, 10W-30 Meets or exceeds:

API SN-RC • ILSAC GF-5

10W-40, 20W-50, SAE 30, SAE 40 Meets or exceeds:

API SN

DELIVERS 3XS BETTER WEAR PROTECTION



IN COMPARISON TO ILSAC
GF-5 STANDARD

PRODUCT	PACKAGING	PART #
5W-20	12/1 Qt	SUS 121
Synthetic	3/5 Qt Value Packs	SUS 12105-3
	6 Gal	SUS 6121
Blend	55 Gal	SUS 121-55
5W-30	12/1 Qt	SUS 93
Synthetic	3/1 Gal	SUS 93-3
Blend	3/5 Qt Value Packs	SUS 9305-3
	6 Gal	SUS 693
	55 Gal	SUS 93-55
10W-30	12/1 Qt	SUS 50
Synthetic	3/1 Gal	SUS 50-3
Blend	3/5 Qt Value Packs	SUS 5005-3
	6 Gal	SUS 650
	5 Gal	SUS 76
	55 Gal	SUS 59
10W-40	12/1 Qt	SUS 51
Synthetic	3/1 Gal	SUS 51-3
Blend	3/5 Qt Value Packs	SUS 5105-3
	6 Gal	SUS 651
	55 Gal	SUS 60
20W-50	12/1 Qt	SUS 48
Synthetic	3/1 Gal	SUS 48-3
Blend	3/5 Qt Value Packs	SUS 4805-3
	6 Gal	SUS 648
	55 Gal	SUS 48-55
SAE 30	12/1 Qt	SUS 49
	55 Gal	SUS 64
SAE 40	12/1 Qt	SUS 98

Super S



SUPER S MULTI-FLO HIGH MILEAGE MOTOR OIL

Super S Multi-Flo High Mileage Motor Oil is specially formulated to help extend the life of higher mileage engines. The high mileage additive is strengthened with seal conditioning agents and extra detergents to target problems such as oil leaks, oil consumption and sludge build-up. Multi-Flo High Mileage Motor Oil meets the latest economy standards while exceeding the industry standards for wear control, piston deposits, cleanliness, sludge, oxidation control, emission systems and seal compatibility.

Multi-Flo High Mileage Motor Oil meets or exceeds the latest American Petroleum Institute (API) SN "Resource Conserving" and car manufacturers' ILSAC GF-5 classifications as well as all previous service classifications.

Meets or exceeds:

API SN-RC • ILSAC GF-5

PRODUCT	PACKAGING	PART #
5W-20	3/5 Qt	SUS 1584
	6 Gal	SUS 61584
5W-30	12/1 Qt	SUS 1581
	3/5 Qt	SUS 1585
10W-30	6 Gal	SUS 61581
	12/1 Qt	SUS 1580
10W-40	3/5 Qt	SUS 1586
	6 Gal	SUS 61580
	12/1 Qt	SUS 1582
	6 Gal	SUS 61582

**HIGH MILEAGE
MOTOR OIL**

FOR
ENGINES OVER

75000 MILES.



SUPER S PASSENGER CAR MOTOR OILS

SUPER S DEXOS1™ MOTOR OIL

Super S dexos1™ motor oil is approved and licensed by General Motors for warranty service for all 2011 model year and newer GM gasoline engine cars and trucks. Super S dexos1™ supersedes the GM6094M, GM4718M and GM-LL-A-025 specifications for 2010 and older GM vehicles and is now the only motor oil GM recommends for those vehicles. It is also licensed by API (American Petroleum Institute) for the ILSAC GF-5 Certification and API-SN Service Category with “Resource Conserving” Performance.

Super S dexos1™ Motor Oil is formulated to meet the latest fuel economy standards while exceeding the dexos1™ specifications for wear control, piston deposits, cleanliness, varnish, sludge, oxidation control, emission system and seal compatibility. These specifications are far more stringent than ILSAC GF-5 specification.

Super S dexos1™ Motor Oil is manufactured to our Advanced Quality Assurance standards of quality control that exceed industry standards. Every batch is laboratory tested from base stocks and additives to finished lubricant to consistently deliver an exceptional level of performance and protection.

Meets or exceeds:

API SN-RC • ILSAC GF-5



PRODUCT	PACKAGING	PART #
0W-20	6/1 Qt	SUS 791
	6 Gal	SUS 6791
	55 Gal	SUS 791-55
5W-30	6/1 Qt	SUS 793
	3/5 Qt	SUS 79305
	6 Gal	SUS 6793
	55 Gal	SUS 793-55

FOR GM MODELS





SUPER S NON-DETERGENT MOTOR OIL

Super S Non-Detergent Motor Oils are manufactured with 100% virgin base oil and fortified with an anti-foaming additive for engine lubrication at an economical price. Super S Non-Detergent Motor Oils are for engines that do not require a high-detergent motor oil. They may be used where equipment suppliers call for a non-detergent motor oil with API SB requirements.

Meets requirements of:

API SB

PRODUCT	PACKAGING	PART #
SAE 10	12/1 Qt	SUS 84
	3/1 Gal	SUS 84-3
	5 Gal	SUS 7
SAE 20	12/1 Qt	SUS 85
	55 Gal	SUS 85-55
SAE 30	12/1 Qt	SUS 41
	2 Gal	SUS 41-2
	5 Gal	SUS 10
	55 Gal	SUS 16
SAE 40	12/1 Qt	SUS 45
	3/1 Gal	SUS 45-3
	3/5 Qt	SUS 4505-3
	5 Gal	SUS 11
	55 Gal	SUS 11-55
SAE 50	12/1 Qt	SUS 86
	3/1 Gal	SUS 86-3
	3/5 Qt	SUS 8605-3
	5 Gal	SUS 86-5
	55 Gal	SUS 86-55





SUPER S HEAVY DUTY MOTOR OILS

SUPER S FG-1000 HEAVY DUTY MOTOR OIL

Super S FG-1000 Heavy Duty Engine Oils are heavy duty engine oils formulated to meet the needs of older engines operating in severe service for both on and off highway conditions. The detergent formulation helps maintain engine cleanliness while the heavy duty additive package provides wear protection and deposit control, helping to prolong engine life.

Meets the requirements of:

Suitable for use in vehicles requiring API CF2, CF, CE, CDII, CD and SJ, SH, SG

SUPER S SUPERSYN FLEET HD DIESEL ENGINE OIL 15W-40

Super S SuperSyn Synthetic Fleet HD is a heavy-duty diesel engine oil formulated especially to meet the latest engine requirements. Super S SuperSyn Fleet HD Diesel Engine Oil protects against sludge build-up in engines and provides extra protection against high temperatures. It is recommended for both new and older diesel and gasoline powered engines when monitored extended drain intervals are desired. It is formulated to meet the latest engine requirements.

Meets the requirements of:

API CJ-4, CI-4 Plus/SN



PRODUCT	PACKAGING	PART #
SAE 10	5 Gal	SUS 130
	55 Gal	SUS 131
SAE 30	12/1 Qt	SUS 96
	3/1 Gal	SUS 157-3
	5 Gal	SUS 73
	55 Gal	SUS 57
SAE 40	12/1 Qt	SUS 97
	3/1 Gal	SUS 158-3
	5 Gal	SUS 74
	55 Gal	SUS 58
SAE 50	12/1 Qt	SUS 134
	3/1 Gal	SUS 134-3
	5 Gal	SUS 132
	55 Gal	SUS 133

PRODUCT	PACKAGING	PART #
15W-40	3/1 Gal	SUS 295-3
	55 Gal	SUS 297



API SERVICE CK-4

Super S



SUPER S FG-2000 CK-4 HEAVY DUTY SYNTHETIC BLEND MOTOR OIL

is recommended for all types of service in truck and automotive diesel and gasoline engines, including those with diesel particulate filters. It provides excellent engine protection, extends engine life and controls oil consumption.

GUARANTEED to meet or exceed the American Petroleum Institute (API) CK-4, CJ-4, CI-4 Plus, CH-4 classification as well as the performance requirements of Mack EOS-4.5, Volvo VDS-4.5, ACEA E7/E9, Cummins CES 20086, Renault VI RLD-4, Caterpillar (ECF-3), and Ford WSS-W2C171-F. Renault VI RLD-3, Caterpillar (ECF-3)

- **HIGHER PERFORMANCE LEVELS**
- **IMPROVED FUEL ECONOMY**
- **EXCELLENT WEAR CONTROL**
- **OUTSTANDING OXIDATION PROTECTION**

PRODUCT	PACKAGING	PART #
15W-40	3/1 Gal	SUS 95
Synthetic	5 Gal	SUS 95-5
Blend	55 Gal	SUS 95-55
	Tote	SUS 95 Tote
10W-30	3/1 Gal	SUS 99
Synthetic	5 Gal	SUS 99-5
Blend	55 Gal	SUS 99-55-2



SUPER S FG-2000 CJ-4 HEAVY DUTY SYNTHETIC BLEND MOTOR OIL

Super S FG-2000 Heavy Duty Synthetic Blend Motor Oil CJ-4 is the latest generation premium heavy-duty engine oil that meets or exceeds the service requirements of virtually all diesel engine manufacturers; both 2007 emission compliant and older engines, as well as new engines using SCR and EGR systems for 2010 emission compliance. It is suitable for virtually all on-highway and off-highway service applications.

15W-40 Meets requirements of:

All Heavy Duty Diesel Engines and EGR Designed Engines, API CJ-4/SN
Mack EO-O Premium Plus, Volvo VDS-4, ACEA E9-08, Cummins CES 20081, DC 228.31
Detroit Fluids Specification DDC 93K218, Renault VI RLD-3, Caterpillar (ECF-3), MB 228.31

10W-30 Meets requirements of:

All Heavy Duty Diesel Engines and EGR Designed Engines API CJ-4/SN
Mack EO-O Premium Plus, Volvo VDS-4, ACEA E9-08, Cummins CES 20081,

PRODUCT	PACKAGING	PART #
15W-40	12/1 Qt	SUS 94
Synthetic	3/1 Gal	SUS 95-3
Blend	3/5 Qt	SUS 9505-3
	2 Gal	SUS 95-2
	5 Gal	SUS 75CJ4
	6 Gal	SUS 60094
	55 Gal	SUS 56CJ4
10W-30		
Synthetic	55 Gal	SUS 99-55
Blend		



SUPER S TRANSMISSION FLUIDS

SUPER S SUPERSYN DEXRON®-VI MULTI-VEHICLE FULL SYNTHETIC ATF

Super S SUPERSYN DEXRON®-VI Multi-Vehicle Full Synthetic ATF was specifically developed for GM automatic transmissions manufactured beginning with the 2006 model year. It is the only GM approved and licensed product for all GM vehicles requiring DEXRON® ATF.

It is a low viscosity, full synthetic ATF formulated with a premium additive package to provide superior performance, protection and service life as compared to conventional ATFs. It flows better at extremely low temperatures, reducing premature wear at start-up, and provides superior protection and performance at high temperatures, and under extreme loads and severe operating conditions.



PRODUCT	PACKAGING	PART #
DEXRON	12/1 Qt	SUS 3228
VI ATF	6 Gal	SUS 63228
	55 Gal	SUS 3228-55

SUPER S MULTI-PURPOSE D/M ATF

Meets the GM DEXRON® IIIH specification, and may be used in a broad range of domestic and foreign transmissions where DEXRON® IIIG, DEXRON® IIE, DEXRON® II, DEXRON®, MERCON®, or Type A Suffix A transmission fluid is specified. It also meets the performance requirements of Allison C-3, C-4, Chrysler ATF-Plus, CAT TO-2 and anti-wear hydraulic fluid. It is used in cars, light and heavy duty trucks, commercial vehicles, buses, on- and off-highway vehicles and power steering systems.

PRODUCT	PACKAGING	PART #
M/P ATF	12/1 Qt	SUS 26
	3/1 Gal	SUS 126-3
	5 Gal	SUS 6
	55 Gal	SUS 44



SUPER S MULTI-VEHICLE SYNTHETIC BLEND ATF

Super S Multi-Vehicle Synthetic Blend ATF is designed to meet the performance requirements of a broad range of automatic and power shift transmissions and should provide trouble-free performance in most American-made and many foreign-made vehicles. It is made with a blend of conventional and synthetic base stocks to provide better performance and protection at start-up and in cold weather, and to provide better high temperature and anti-wear protection, especially for heavy hauling and more demanding service.



PRODUCT	PACKAGING	PART #
M/V	12/1 Qt	SUS 226-12
S/B ATF	55 Gal	SUS 226



SUPER S MERCON® V ATF

Super S MERCON® V ATF meets the performance requirements for Ford's MERCON® and MERCON® V service fill specifications. It also meets GM DEXRON® III and Allison C-4 specifications.

PRODUCT	PACKAGING	PART #
MERCON V	12/1 Qt	SUS 225
	55 Gal	SUS 225-55

SUPER S TYPE F ATF

Super S Type F ATF is used in all Ford transmissions made until 1977 and some pre-1982 transmissions. It meets the requirements of Ford specification M2C33-F and may be used wherever the manufacturer recommends a Type F ATF.



PRODUCT	PACKAGING	PART #
TYPE F	12/1 Qt	SUS 27
ATF	55 Gal	SUS 27-55



SUPER S ATF 4

Super S ATF 4 is specially formulated from high VI base stocks. Designed to be a "Fill for Life" fluid under normal driving conditions. ATF 4 is fully compatible with all transmission applications where 7176, ATF+2 or ATF+3 and Type 9662 Automatic Transmission Fluid is specified.

PRODUCT	PACKAGING	PART #
ATF 4	12/1 Qt	SUS 224
	55 Gal	SUS 224-55

SUPER S TRANSMISSION FLUIDS



SUPER S SUPERSYN PREMIUM FULL SYNTHETIC CVT FLUID

Super S SuperSyn Premium Full Synthetic CVT Fluid is a full synthetic transmission fluid specifically designed to provide outstanding performance in North American vehicles equipped with belt-driven Continuously Variable Transmissions. Modern CVTs, Continuously Variable Transmissions, are very different from automatic transmissions in design, materials and operation. They require a specialized fluid with friction and viscosity characteristics contrary to those of automatic transmissions. Slipping, loss of performance and long-term damage may potentially result from the use of the wrong fluid.

PRODUCT	PACKAGING	PART #
CVT Fluid	12/1 Qt	SUS 229
	6 Gal	SUS 6229
	55 Gal	SUS 229-55

SUPER S SUPERSYN TRANS-FLUID 50 API MT-1 MANUAL TRANSMISSION FLUID

Super S SuperSyn Trans-Fluid 50 API MT-1 Manual Transmission Fluid is a full synthetic, heavy duty SAE 50 manual transmission fluid formulated with premium quality synthetic base stocks and high performance additives for API MT-1 non-EP extended drain service. Super S SuperSyn Trans-Fluid 50 remains fluid at extremely low temperatures for cold weather shifting and to help eliminate premature wear (especially at start-up), and it maintains lubricity and film strength at high temperatures.

Applications include commercial vehicles and heavy duty trucks, most heavy duty manual transmissions and synchromesh gear boxes.

PRODUCT	PACKAGING	PART #
Trans. Fluid 50	35 lb	SUS 219
	110 lb	SUS 219-16
	400 lb	SUS 219-55



SUPER S TYPE A ATF

Super S Type A ATF is formulated primarily for add-on (top-off) purposes and for high consumption transmissions. Not for full service fill. Not intended for use in transmissions made after 1957.

PRODUCT	PACKAGING	PART #
TYPE A ATF	12/1 Qt	SUS 42
	3/1 Gal	SUS 42-3
	5 Gal	SUS 42-5
	55 Gal	SUS 42-55

PACKAGE FEATURE



SPACE SAVER

Now Available In

42 BOXES/PALLET

Super S Multi-Flo Synthetic Blend Engine Oil
5W-20, 5W-30, 10W-30, 10W-40, 20W-50

Super S Multi-Flo High Mileage Engine Oil
5W-20, 5W-30, 10W-30, 10W-40

Super S SuperSyn Full Synthetic Engine Oil
0W-40, 5W-20, 10W-30

Super S SuperSyn Full Synthetic dexos1® Engine Oil
dexos1® 0W-20, 5W-30

Super S SuperSyn EURO Engine Oil
5W-30, 5W-40

Super S FG-2000 15W-40 Heavy Duty

Super S SuperSyn Multi-Vehicle DEX VI ATF

The Total Package

- Increase Lubricant Offerings to Customers
- Space Saving Design

Environmentally Friendly

- SuperS SPACE SAVER craft carton is recyclable
- Plastic Liner provides 89% Less Landfill waste than equivalent 24 bottle

OTHER PRODUCTS ARE AVAILABLE. Contact Your Smitty's Sales Rep for Rack Availability, Pricing, Terms & Conditions.

(800) 256-7575 • www.SMITTYSINC.net



SUPER S GEAR OILS

SUPER S GL-1 GEAR OIL

Super S GL-1 Gear Oils are straight mineral gear oils blended from mid Viscosity Index base stocks and are intended for mild service in a broad range of automotive, manual transmission and industrial gear and bearing applications operating under conditions of low unit pressure and minimum sliding velocities. They

may contain oxidation, rust and corrosion inhibitors, anti-foam agents and pour point depressants. Super S GL-1 gear oils do not contain friction modifiers or extreme pressure additives.



PRODUCT	PACKAGING	PART #
SAE 90	12/1 Qt	SUS 21-12
	3/1 Gal	SUS 21-3
	35 lb Pail	SUS 8
	400 lb Drum	SUS 39
SAE 140	12/1 Qt	SUS 22-12
	3/1 Gal	SUS 22-3
	35 lb Pail	SUS 9
	400 lb Drum	SUS 9-55

SUPER S GL-4 EXTREME PRESSURE GEAR OIL

Super S GL-4 Heavy duty gear lubricants are formulated with sulfur-phosphorus EP additives to provide anti-wear and anti-scuff performance for use in automobiles, trucks and heavy equipment calling for GL-4 gear oils, especially gears subject to shock loading. They provide excellent performance in high load operations and in extreme temperatures, and also provide oxidation stability, corrosion resistance, and anti-foam protection. Meets the performance requirements of API GL-4, MIL-L-2105 and SAE J-2360.

PRODUCT	PACKAGING	PART #
SAE 90	3/1 Gal	SUS 91-3
	35 lb Pail	SUS 91
SAE 140	12/1 Qt	SUS 92-3
	3/1 Gal	SUS 92-1-3
	35 lb Pail	SUS 92





SUPER S GL-5 MULTI-PURPOSE GEAR OIL

Super S GL-5 Multi-Purpose Gear Oils are high performance, heavy duty, EP (extreme pressure) gear lubricants formulated to withstand severe service and severe environments in cars, trucks and heavy equipment. They provide excellent wear resistance, load carrying capability and oxidation stability, while protecting against rust, corrosion and foaming. Applications include conventional and high performance differentials.



PRODUCT	PACKAGING	PART #
SAE 80W-90	12/1 Qt	SUS 17
	3/1 Gal	SUS 82-3
	35 lb Pail	SUS 52
	110 lb Keg	SUS 87
	400 lb Drum	SUS 53
SAE 85W-140	12/1 Qt	SUS 25
	3/1 Gal	SUS 83-3
	35 lb Pail	SUS 54
	110 lb Keg	SUS 88
	400 lb Drum	SUS 55

SUPER S GL-5 LIMITED SLIP GEAR OIL

Super S GL-5 Limited Slip Gear Oil are the same as GL-5, but with additives for Limited Slip differentials.

PRODUCT	PACKAGING	PART #
80W-90LS	35 lb Pail	SUS 52LS
	110 lb Keg	SUS 87LS
	400 lb Drum	SUS 53LS

SUPER S GL-5 RED TAC HIGH PERFORMANCE GEAR OIL

Same as GL-5 gear oil, but formulated with high VI (viscosity index) thermally stable base stocks and a highly effective sulphur-phosphorus extreme pressure, anti-wear, anti-scurf, anti-weld additive system with a red tackifier to provide greater adhesion to gears and leak detection.

PRODUCT	PACKAGING	PART #
85W-140	35 lb Pail	SUS 54RT
	400 lb Drum	SUS 55RT

SUPER S SUPERSYN 75W-90 SYNTHETIC GEAR OIL

Super S SuperSyn 75W-90 Synthetic Gear Oil is a full synthetic heavy duty gear lubricant that provides extended drain service, improved fuel efficiency, and is designed to meet the service demands of automobile, light truck and the latest heavy duty manual transmissions, axles and drive units that call for API GL-5/MT-1. SuperSyn 75W-90 Gear Oil is formulated for extreme pressure, severe service, and is thermally stable with a low pour point for all season use even at sub-zero temperatures.



PRODUCT	PACKAGING	PART #
Syn 75W-90	12/1 Qt	SUS 217
	35 lb	SUS 217-5
	110 lb	SUS 217-16
	400 lb	SUS 217-55
Syn 75W-90 Limited Slip	35 lb	SUS 217-5LS

SUPER S SUPERSYN 75W-140 LIMITED SLIP SYNTHETIC

Super S SuperSyn 75W-140 Limited Slip Synthetic is a multi-purpose full synthetic automotive gear lubricant designed to meet the performance requirements of many modern passenger vehicles in all types of operating conditions. It provides excellent performance in Limited Slip applications, reducing chatter, slipping and noise while improving traction.

Super S SuperSyn 75W-140LS is typically used in differentials, final drives, transfer cases and rear axles in modern, high performance vehicles such as SUVs, vans and light duty trucks where an API GL-4 or GL-5 is recommended. It's improved frictional properties improve fuel economy and reduce operating costs.



PRODUCT	PACKAGING	PART #
Syn 75W-140 Limited Slip	12/1 Qt	SUS 216
	35 lb	SUS 216-5
	110 lb	SUS 216-16
	400 lb	SUS 216-55

SUPER S GEAR OILS

SUPER S SUPERSYN 80W-140 SYNTHETIC GEAR OIL

A full synthetic heavy duty gear lubricant developed for heavy duty differentials calling for GL-5 service. Applications also include rear wheel bearings and universal joints, automobile, light and heavy duty truck transfer cases, heavy construction and farm equipment, industrial gear units and manual transmissions.

PRODUCT	PACKAGING	PART #
Syn 80W-140	35 lb	SUS 218-5
	110 lb	SUS 218-16
	400 lb	SUS 218-55

SUPER S EP GEAR COMPOUND

Super S EP Gear Compounds are heavy duty EP (extreme pressure) gear lubricants (GL-4) formulated for use in industrial gear sets, bearings, circulating systems and gear reducers. They protect gears and bearings by providing excellent load carrying capability, water de-mulsibility, oxidation stability and corrosion resistance. Provides excellent performance in high load and/or extreme temperature operations.

PRODUCT	PACKAGING	PART #
ISO 68	Bulk	SUS 13911
ISO 150	400 lb	SUS 151
	Bulk	SUS 151BULK
ISO 220	35 lb	SUS 152-5
	400 lb	SUS 152
ISO 320	400 lb	SUS 153
ISO 460	35 lb	SUS 154-5

SUPER S LIMITED SLIP ADDITIVE FOR GL-5 GEAR OILS

For Limited Slip, Posi-Traction and Locking differentials, add up to 2 ounces per quart of either conventional or synthetic GL-5 gear oil. Prevents differentials from chattering and slipping, reduces differential noises, and improves gear oil performance. Suitable for GM 1052358, Ford M2C118-A, Chrysler 4318060 and most imports. Not for use in JEEP Quadra-Trac or Quadra-Drive.



PRODUCT	PACKAGING	PART #
LS Additive	12/10 oz	SUS S 159



SUPER S MARINE OUTBOARD LOWER UNIT GEAR LUBE

Super S Marine Outboard Lower Unit Gear Lube is a special API Service GL-5 80W-90 marine grade formulation designed to withstand high amounts of water contamination. It is fortified with stable extreme pressure (EP) additives and corrosion inhibitors to protect gears and bearings subject to water seepage. Anti-foam agents maintain lubrication even under the severe churning action experienced in lower unit.

PRODUCT	PACKAGING	PART #
Lower Unit Gear Lube	12/10 oz	SUS 178

SUPER S HYDRAULIC FLUIDS

SUPER S PREMIUM UNIVERSAL TRACTOR HYDRAULIC FLUID

Super S Premium Universal Tractor Hydraulic Fluid is a premium multi-functional fluid used as a hydraulic medium and as a transmission, differential, power steering, power brake, power take-off (PTO), and implement drive fluid.

FEATURES / BENEFITS

- Superior detergent/dispersant package keeps system cleaner for longer life
- Lubricates the transmission, differential and final drive gears in tractors and implements
- Provides extreme pressure (EP) and anti-wear protection
- Protects against rust, corrosion, foaming and oxidation
- Prevents seal and pump deterioration
- Protects tractor transmission, axles and hydraulic pumps
- Eliminates brake chatter
- Controlled frictional characteristics permit the wet brakes to hold properly and allows smooth engagement of power take-off (PTO) clutches.

PRODUCT	PACKAGING	PART #
Premium	3/1 Gal	SUS 236-3
Universal	3/2 Gal	SUS 236-2
Tractor	5 Gal	SUS 236
	55 Gal	SUS 236-55

Premium Universal Tractor Hydraulic Fluid has been field-tested and is suitable for use where any of the following fluids are recommended:

Allis Chalmers PF-821XL	John Deere J20, J20A
Caterpillar T0-2	(Hy-Gard), J20C, J14B,
Denison HF-O	J14C, J21A
Deutz HTF	303, Quatrol
Ford /New Holland	Kubota UDT, UDT Super
M2C41-B, M2C48-B	Massey Ferguson,
M2C53-C, M2C77-A	M-1110, M-1127, M-1129
M2C86-B, ESN-M2C134	(Permatran)
M2C134-B, M2C134-C	Oliver Type 55
M2C134-D	Renk Doromat ATF
International Harvester	Steiger Hydraulic Trans
Hy-Tran, spec. B-6	Fluid
JI Case/David Brown	Sunstrand HMS-103
JIC-143, 144, 145, 185	Versatile Gear/Hydraulic
MS-1204, 1205	Trans Fluid
MS-1209, MS-1210 (TCH)	White Q1722, Q1826
	MS-1206 (Powergard PTF)



SUPER TRAC

SUPER S HYDRAULIC FLUIDS

SUPER S SUPER TRAC® 303 TRACTOR HYDRAULIC FLUID

Super S Super Trac® 303 Tractor Hydraulic Fluid is designed to lubricate the transmission, differential and final drive gears in tractors and implements. It is a multi-functional fluid used as a hydraulic medium, and as a power steering, power brake, power take-off (PTO), and implement drive fluid.

Super S Super Trac® 303 Tractor Hydraulic Fluid is designed for use as a replacement fluid for the hydraulic, wet brake, and transmission requirements of equipment manufacturers where a product of this quality is recommended.

Super S Super Trac® 303 Tractor Hydraulic Fluid is recommended for ambient temperatures between +32 degrees Fahrenheit and +104 degrees Fahrenheit. For ambient temperatures outside this range or where a premium tractor hydraulic/transmission oil is required, please use Super S Premium Universal Tractor Hydraulic Fluid.

Misapplication may cause severe performance problems. Super S 303 Tractor Hydraulic Fluid has not been recommended by any OEM for model years later than 1974. For equipment built after 1974 requiring multi-functional fluid, use Super S Premium Universal Tractor Hydraulic Fluid (J20C).

PRODUCT	PACKAGING	PART #
Super	3/1 Gal	SUS 24-3
Trac	3/2 Gal	SUS 24-2
303	5 Gal	SUS 35
	55 Gal	SUS 12





SUPER S ANTI-WEAR HYDRAULIC FLUID

Super S AW Hydraulic Fluid is a general purpose anti-wear, rust, corrosion and oxidation inhibited oil that provides excellent water separation and demulsibility. It is specially formulated to suppress foaming while also allowing rapid air release, improving hydraulic system performance and helping to prevent pump cavitation. Oxidation inhibitors provide control of sludge and varnish deposits, and increase service life. It is suitable for use where service requirements are light to moderate, and heavy-duty wear or long-term service is not critical, and is available in viscosity grades ISO VG22 to ISO VG100. When used in the proper grade, it will provide excellent service in hydraulic systems and air compressors, industrial bearings, hoists and machine tools, and circulating, splash, bath and ring lube systems for bearings and gears.



SUPER S R & O HYDRAULIC OIL

A general purpose hydraulic oil that protects against rust, oxidation, corrosion and foaming in a wide variety of applications where service is light to moderate and anti-wear or extreme pressure properties are not required. Standard viscosity grade is ISO 32, with an ISO 68 option.



PRODUCT	PACKAGING	PART #
ISO 22	5 Gal	SUS 222
	55 Gal	SUS 222-55
ISO 32	3/1 Gal	SUS 36-3
	5 Gal	SUS 36
	55 Gal	SUS 37
ISO 46	3/1 Gal	SUS 38-3
	5 Gal	SUS 38
	55 Gal	SUS 63
ISO 68	3/1 Gal	SUS 40-3
	5 Gal	SUS 40
	55 Gal	SUS 43
ISO 100	5 Gal	SUS 100
	55 Gal	SUS 100-55

PRODUCT	PACKAGING	PART #
ISO 32	3/1 Gal	SUS 23-3
	5 Gal	SUS 1
	55 Gal	SUS 3
	Tote	SUS 3 Tote
ISO 68	5 Gal	SUS 2
	55 Gal	SUS 2-55



SUPER S HYDRAULIC FLUIDS

SUPER S SUPERDRAULIC™ AW HYDRAULIC FLUID

Super S SuperDraulic™ Premium AW Hydraulic Fluid is an extended drain, heavy-duty anti-wear hydraulic oil formulated with high VI paraffinic base oils and an advanced additive package to provide superior oxidation and thermal stability for (ASTM D-943) 5000+ hour service. It provides excellent water separation and demulsibility, and is specially formulated to suppress foaming while also allowing rapid air release, improving hydraulic system performance and helping to prevent pump cavitation. It protects system components from rust and corrosion. Extended service performance is realized with advanced oxidation inhibitors that minimize sludge and varnish deposits, and superior base oils that resist breakdown and maintain properties at higher operating temperatures.

SUPER S SUPER TRAC® TO-4 FLUIDS

Super S Super Trac® TO-4 Fluids meet the requirements of Caterpillar TO-4, and Komatsu Micro-Clutch. They are heavy duty lubricants formulated for use in transmission and final drives requiring Caterpillar TO-4 or Allison C-4 fluids, formulated with highly refined base oils, detergents, dispersants, oxidation and corrosion inhibitors, anti-wear and EP (extreme pressure) agents, and a foam suppressant. Super Trac TO-4 Fluids can also be used in wet brakes, hydrostatic transmissions, torque converters, and hydraulic systems calling for TO-4 or C-4 Fluids.

SUPER S MINING HYDRAULIC OIL

Super S Mining Hydraulic Oil is blended from well-refined base stocks to provide anti-wear lubricating properties primarily in mining applications. It is formulated with select additives to provide anti-rust and anti-oxidation performance. To meet requirements of the mining industry, this product is packaged in square metal cans.



PRODUCT	PACKAGING	PART #
ISO 32	5 Gal	SUS 161
	55 Gal	SUS 162
ISO 46	5 Gal	SUS 164
	55 Gal	SUS 163
ISO 68	5 Gal	SUS 166
	55 Gal	SUS 167
ISO 100	55 Gal	SUS 169

(Products are also available in Totes & Bulk)

PRODUCT	PACKAGING	PART #
SAE 10	5 Gal	SUS 140
	55 Gal	SUS 141
SAE 30	5 Gal	SUS 142
	55 Gal	SUS 143
SAE 50	5 Gal	SUS 144
	55 Gal	SUS 145

PRODUCT	PACKAGING	PART #
ISO 68	35 lb Pail	SUS 40M
ISO 100	35 lb Pail	SUS 100M
ISO 150	35 lb Pail	SUS 150M



SUPER S GREASE

SUPER S MULTI-PURPOSE #2 (MP2) LITHIUM GREASE

A NLGI#2 lithium based, water resistant grease for automotive and light to medium trucks, farm and industrial applications. It is recommended for automotive chassis lubrication points, ball joints and universal joints. It resists softening at high operating temperatures, seals out dirt and moisture contamination, is formulated with rust and oxidation inhibitors, and offers good stability over its operating range. Super S MP2 provides excellent water resistance, is shear stable and provides good anti-wear protection. Meets requirements of NLGI GB.



SUPER S HI-TEMP RED #2 EP LITHIUM GREASE

A premium NLGI#2 extreme pressure (EP), multi-purpose, lithium complex grease that provides outstanding high temperature performance and excellent lubrication over a wide temperature range and a variety of services including heavy duty fleet, automotive, farm and industrial applications.

Super S Hi-Temp Red provides excellent water resistance, rust and corrosion protection, and oxidation resistance. It provides wear protection under extreme loads, resists separation, and resists softening due to heat. The Lithium Complex thickener gives it a dropping point in excess of 500 °F. Meets requirements of NLGI GC-LB.



PRODUCT	PACKAGING	PART #
Multi Purpose	18/3 oz	SUS 66-03
	10/14 oz	SUS 66-10
	50/14 oz	SUS 66
	12/1 lb	SUS 66-1
	35 lb	SUS 68
MP2 RED	120 lb	SUS 69
	400 lb	SUS 79
	50/14 oz	SUS 66-14
	12/1 lb	SUS 66-12
	35 lb	SUS 66-35
MP2 AMBER	120 lb	SUS 66-120
	400 lb	SUS 66-400
	50/14 oz	SUS 68-14
	12/1 lb	SUS 68-12
	35 lb	SUS 68-35
	120 lb	SUS 68-121

PRODUCT	PACKAGING	PART #
Hi-Temp Red	10/14 oz	SUS 67-10
	50/14 oz	SUS 67
	12/1 lb	SUS 77
	6/4 lb	SUS 67-4
	35 lb	SUS 71
	120 lb	SUS 70
	400lb	SUS 78

SUPER S GREASE

SUPER S SUPER CS EP2 SYNTHETIC GREASE

Among the highest performance of multi-purpose greases, it is formulated with premium high VI (Viscosity Index) oils, performance additives and a Calcium Sulfonate extreme pressure (EP), synthetic based thickener. It is world renowned for its unequalled corrosion properties as well as its Extreme Pressure properties and shear stability. It is specifically formulated for severe service, extreme environment and marine applications, and off-road machinery. It exceeds the requirements of all NLGI EP2 grease applications. Meets requirements of NLGI GC-LB.



PRODUCT	PACKAGING	PART #
CS EP2	50/14 oz	SUS 202
	35 lb	SUS 202-35
	120 lb	SUS 202-120
	400 lb	SUS 202-400



SUPER S SUPER BLUE EP2 HI-TEMP GREASE

A high performance, extreme pressure (EP), multi-purpose grease formulated for demanding high temperature applications - dropping point exceeds 500°F. Super Blue EP2 reduces friction with a unique formulation that adheres to metallic surfaces (versus plating out) to reduce the highly localized heating and wear of metal surfaces. It is fortified with extra EP additives to withstand extreme loading and shock loads. Exceeds the latest equipment requirements. Meets requirements of NLGI GC-LB.

PRODUCT	PACKAGING	PART #
Blue EP2	50/14 oz	SUS 201
	35 lb	SUS 201-35
	120 lb	SUS 201-120
	400 lb	SUS 201-400

SUPER S SUPER MOLY EP2 GREASE

A high performance NLGI#2 multi-purpose grease provides additional wear protection under extreme/severe loads with enhanced extreme pressure (EP) and film properties, and outstanding high temperature performance with a dropping point in excess of 500°F. It is fortified with molybdenum disulfide which reduces the coefficient of friction, protects against localized heating and wear of metal surfaces and provides exceptional film strength, making it especially good for shock loads and low speed, heavy load applications such as in heavy construction and earth moving equipment. Meets requirements of NLGI GC-LB.



PRODUCT	PACKAGING	PART #
Moly EP2	50/14 oz	SUS 203
	35 lb	SUS 203-35
	120 lb	SUS 203-120



SUPER S MARINE EP SYNTHETIC GREASE

A high performance Synthetic Extreme Pressure (EP) NLGI Grade #2 Calcium Sulfonate grease developed for Marine and other applications needing severe service properties and/or a high resistance to washout, water, moisture, rust and corrosion, including saltwater. It demonstrates exceptional anti-wear and extreme pressure properties, oxidation and shear stability, and provides outstanding low and high temperature performance. It will help to maximize component life. Meets requirements of NLGI GC-LB.



PRODUCT	PACKAGING	PART #
Marine	18/3 oz	SUS 205-03
	50/14 oz	SUS 205



SUPER S SUPER MP2 GRAPHITE GREASE

A graphite fortified multi-purpose NLGI #2 lithium grease that exhibits good mechanical stability, rust inhibition and water resistance. Use where a heavy grease with solid lubricants is required. Super MP2 Graphite Grease has broad application and may be more suitable for use in many cases than dry powered graphite or basic household oils. Meets requirements of NLGI GA-LA.

PRODUCT	PACKAGING	PART #
MP2 Graphite	50/14 oz	SUS 204

SUPER S “000” RED LITHIUM GREASE

An economical, light duty lithium thickened NLGI “000” grease for general use, including applications where lubricant retention is a problem. Fluid at lower temperatures, pourable at room temperature, 000 grease is shear stable, has moderate EP properties, and provides good water resistance.

PRODUCT	PACKAGING	PART #
“000” Red Lithium	35 lb	SUS 120
	400 lb	SUS 120-400

SUPER S “00” COTTON PICKER SPINDLE GREASE

A smooth textured, corrosion preventive NLGI 00 lithium grease based upon the best time-tested formulations specifically developed for lubricating modern cotton picker spindle assemblies. It is manufactured with a special low viscosity, low pour point base oil to provide low friction, excellent penetration, full protection and efficient operation in both hot and cold weather.



PRODUCT	PACKAGING	PART #
“00”	12/1 Qt	SUS 111
	35 lb	SUS 114
	120 lb	SUS 116
	400 lb	SUS 117

SUPER S COTTON PICKER SPINDLE CLEANER

A top quality oil emulsion based upon the time-tested formulation specifically developed for cleaning modern cotton picker spindles. Super S Spindle Cleaner is a water soluble oil-based liquid that mixes well with water of any hardness and cleans dirt, plant materials, and other foreign contaminants from cotton picker spindles. It applies a protective film as it washes the spindle and is compatible with spindle grease. It won't wash spindle grease out of the critical areas it's lubricating, but will still coat those parts to protect them. It also keeps moisture pads from drying out and hardening, and helps to keep doffers in good condition.

Super S Spindle Cleaner guards against wear and pitting, and protects against rust, oxidation and corrosion.

PRODUCT	PACKAGING	PART #
Spindle Cleaner	5 Gal	SUS 123
	55 Gal	SUS 124



SUPER S INDUSTRIAL OILS

SUPER S PREMIUM R & O TURBINE OIL

A premium rust and oxidation inhibited formulation of paraffinic base oils blended with a carefully balanced additive system to achieve a combination of excellent water demulsibility, oxidation stability, and air release. Super S Premium R&O Turbine Oils are designed for long life service protecting against system rusting caused by water contamination, and against sludge and deposits caused by oil oxidation. Available in viscosity grades ISO VG22 to ISO VG320.

PRODUCT	PACKAGING	PART #
Turbine 32	5 Gal	SUS 61
	55 Gal	SUS 62
Turbine 46	5 Gal	SUS 15
	55 Gal	SUS 47
Turbine 68	5 Gal	SUS 13
	55 Gal	SUS 14

SUPER S CHERRY PICKER OIL

Super S Cherry Picker Oil surpasses the minimum dielectric strength specification of 25kV making it suitable for use in high voltage electric service vehicles.

Super S Cherry Picker Oil is a premium high dielectric strength, high VI (viscosity index) anti-wear hydraulic oil developed for dependable performance in mobile, marine and industrial equipment, aerial platforms (man lifts) and bucket trucks, and emergency and electric service vehicles.

PRODUCT	PACKAGING	PART #
CPicker 22	5 Gal	SUS 230
CPicker 32	5 Gal	SUS 232
	55 Gal	SUS 232-55

SUPER S SAWGUIDE OIL

Super S Saw Guide Oil is formulated with premium base stocks and additive with tackifier for excellent rust and corrosion protection. The premium fluid creates a boundary layer between the blade and guide reducing friction and heat while protecting critical components of the operation.

PRODUCT	PACKAGING	PART #
Sawguide Oil 100	55 Gal	SUS 194

SUPER S QUENCH OIL

Super S Quench Oils are formulated with paraffinic base oils and a specially additive designed for use during the heat treating of steel. This formulation results in excellent wetting ability and outstanding cooling capacity during the quench process.

PRODUCT	PACKAGING	PART #
Quench Oil	Bulk	SUS 193 Bulk



SUPER S DRIP OIL

Super S Drip Oils utilize premium paraffinic base stocks and are clear, to a slight straw color. They are recommended for use on vertical shaft driven pumps equipped with a drip oiler. They are free of harmful additives, and their high viscosity index allows consistent flow with temperature variation.



SUPER S LOW ASH GAS ENGINE OIL

Super S Low Ash Gas Engine Oils are premium, low ash engine oils recommended for high output four –cycle engines. Formulated from high VI base stocks and additive package, they provide superior levels of detergency and deposit control for the demanding requirements of these engines. Additionally they contain antiwear additive and antioxidants leading to long service life.

SUPER S ASHLESS GAS ENGINE OIL

Super S Ashless Gas Engine Oils are premium ashless engine oils proven to be an exceptional performer during years of field service throughout North America in 2-stroke and selected 4-stroke engines. It is based on an exclusive ashless formulation to help prevent combustion chamber deposits, exhaust port blockage and spark plug fouling.

SUPER S ROCK DRILL OIL

Super S Rock Drill Oils are extreme pressure lubricants designed for the lubrication of air powered tools, such as jack hammers, rock drills, pneumatic construction and mining equipment under both wet and dry conditions. Super S Rock Drill Oils have outstanding stability, adhesiveness, and excellent load-carrying capacity. They contain rust and oxidation inhibitors, EP additives, and a tackifier agent that protects the critical components of the tools. Super S Rock Drill Oils are non-corrosive to both ferrous and nonferrous metals.

SUPER S ROTARY PIST/VAC PUMP OIL

Super S Rotary Piston Vacuum Oil is formulated with high quality base oils, resulting in a low vapor pressure, chemically stable fluid, that is unreactive with most gases and materials. It is recommended for use in most vacuum pumps where high vacuums are required.

SUPER S TRANSFORMER OIL

Super S Transformer Oil is an electrical insulating oil produced from severely hydroprocessed naphthenic base oils to meet the specifications defined in ASTM D 3487. They do not contain corrosive sulfur or polychlorinated biphenyls (PCBs). The specialized formula insures high electrical resistance, while the low viscosity and pour point provides excellent conductive heat transfer. It is formulated with an oxidation inhibitor to minimize formation of acids and sludge in service to minimize oil deterioration and extend the operating life of the immersed components. Super S Transformer Oil can be used in transformers, oil-immersed switches, oil-immersed circuit breakers, LTC's, and oil filled capacitors.

SUPER S CONCRETE FORM OIL

Super S Concrete Form Oil is used to prevent bonding between concrete surface and forms, both wood and steel. Because bonding is eliminated, stripping is easier resulting in extended form life. The oil also provides protection from rust on steel forms. Super S Concrete Form Release Oil is non-staining for most types of aggregates.

SUPER S HEAT TRANSFER OIL

Super S Heat Transfer Oils are blended from high quality base stocks. They should be used whenever the application requires excellent product stability, oxidation and heat transfer properties are required.

PRODUCT	PACKAGING	PART #
Drip Oil	3/2 Gal	SUS 196
	5 Gal	SUS 36 DO
	55 Gal	SUS 37 DO

PRODUCT	PACKAGING	PART #
Low Ash SAE 30	Bulk	SUS 184 Bulk
Low Ash SAE 40	55 Gal	SUS 183-55
	Bulk	SUS 183 Bulk
15W-40	Bulk	SUS 209 Bulk

PRODUCT	PACKAGING	PART #
Ashless SAE 30	Bulk	SUS 207 Bulk
Ashless SAE 40	55 Gal	SUS 200-55
	Bulk	SUS 208 Bulk

PRODUCT	PACKAGING	PART #
ISO 68	55 Gal	SUS 190
ISO 100	5 Gal	SUS 309
	55 Gal	SUS 310

PRODUCT	PACKAGING	PART #
Rotary/ Vac Pump	5 Gal	SUS 89

PRODUCT	PACKAGING	PART #
Transformer	55 Gal	SUS 235-55

PRODUCT	PACKAGING	PART #
Concrete Form Oil	55 Gal	SUS 195

PRODUCT	PACKAGING	PART #
ISO 32	Bulk	SUS 182 Bulk
ISO 46	Bulk	SUS 146 Bulk

ANTIFREEZE & COOLANT



SUPER S UNIVERSAL ANTIFREEZE AND COOLANT

Super S Universal Antifreeze and Coolant is recommended for most conventional automotive and diesel engines and is compatible with all premium quality cooling system products regardless of make, model or original antifreeze color including green, yellow, orange, fuchsia, blue or red.

PRODUCT	PACKAGING	PART #
Universal	6/1 Gal	SUS 285
AF (Yellow)	55 Gal	SUS 285-55



SUPER S 50/50 PREDILUTED UNIVERSAL ANTIFREEZE AND COOLANT

Super S 50/50 Prediluted Universal Antifreeze and Coolant meets the same specifications and gives the same protection as Super S Universal Antifreeze and Coolant. It is mixed with a 50% water concentration for ease of application and cleanliness.

PRODUCT	PACKAGING	PART #
Universal	6/1 Gal	SUS 286
50/50 (Yellow)	55 Gal	SUS 285-50

SUPER S FULL STRENGTH ANTIFREEZE & COOLANT

Super S Antifreeze/Coolant is an ethylene glycol base antifreeze containing inhibitors providing protection from freezing, overheating, rust and corrosion when used as recommended. It protects all cooling system metal surfaces including aluminum. It will not damage auto finishes or rubber parts.

PRODUCT	PACKAGING	PART #
Antifreeze (Green)	12/1 Qt	SUS 165
	6/1 Gal	SUS 65
	55 Gal	SUS 72

SUPER S 50/50 ANTIFREEZE & COOLANT

Super S 50/50 Antifreeze & Coolant meets the same specifications and gives the same protection as Super S Antifreeze. It is mixed with a 50% water concentration for ease of application and cleanliness.

PRODUCT	PACKAGING	PART #
Premix 50/50 (Green)	12/1 Qt	SUS 80-12
	6/1 Gal	SUS 80
	55 Gal	SUS 80-55





SUPER S EXTENDED LIFE ANTIFREEZE & COOLANT

Super S Extended Life Antifreeze & Coolant is a new generation of antifreeze technology that can be used to upgrade any automobile or light truck cooling system to a remarkable 150,000 miles—5 years of protection. Extended Life Antifreeze is compatible with conventional antifreeze, but may reduce its characteristics to conventional antifreeze levels and is not recommended by manufacturers. Super S Extended Life Antifreeze should be mixed to a 50% water concentration.

PRODUCT	PACKAGING	PART #
Extended Life (Orange)	6/1 Gal	SUS 265
	55 Gal	SUS 266



SUPER S 50/50 PREDILUTED EXTENDED LIFE ANTIFREEZE & COOLANT

Super S 50/50 Prediluted Extended Life Antifreeze & Coolant meets the same specifications and gives the same protection as Super S Extended Life Antifreeze & Coolant. It is mixed with a 50% water concentration for ease of application and cleanliness.

PRODUCT	PACKAGING	PART #
50/50 AF (Orange)	6/1 Gal	SUS 267
	55 Gal	SUS 266-50



SUPER S EXTENDED LIFE HEAVY DUTY TRUCK ANTIFREEZE AND COOLANT

Super S Extended Life Heavy Duty Truck Antifreeze and Coolant is a heavy duty diesel formula and contains advanced supplemental cooling additives (SCA) which protect your complete cooling system while improving performance, reducing maintenance and lowering overall costs.

PRODUCT	PACKAGING	PART #
Extended Life HD (Red)	6/1 Gal	SUS 289
	55 Gal	SUS 289-55



SUPER S EXTENDED LIFE 50/50 HEAVY DUTY TRUCK ANTIFREEZE AND COOLANT

Super S Extended Life 50/50 Heavy Duty Truck Antifreeze and Coolant meets the same specifications and gives the same protection as Super S Extended Life Heavy Duty Truck Antifreeze and Coolant. It is mixed with a 50% water concentration for ease of application and cleanliness.

PRODUCT	PACKAGING	PART #
Extended Life HD 50/50 (Red)	6/1 Gal	SUS 290
	55 Gal	SUS 290-55

SUPER S FLEET ANTIFREEZE & COOLANT

Super S Fleet Antifreeze & Coolant is formulated to provide optimum protection against freezing, boil over, cavitations, erosion, corrosion, and scale for all heavy-duty cooling system applications. It is SCA pre-charged, therefore it requires no SCA at initial fill, and insures proper chemistry at every top-off. Special anti-scale additives eliminate the need for de-ionized water.

SUPER S 50/50 PREDILUTED FLEET ANTIFREEZE & COOLANT

Super S 50/50 Prediluted Fleet Antifreeze & Coolant meets the same specifications and gives the same protection as Super S Fleet Antifreeze & Coolant. It is mixed with a 50% water concentration for ease of application and cleanliness.

PRODUCT	PACKAGING	PART #
Fleet AF (Green)	6/1 Gal	SUS 275
	55 Gal	SUS 276

PRODUCT	PACKAGING	PART #
Fleet 50/50 AF (Green)	55 Gal	SUS 276-50

Super S Antifreeze is formulated with bitterants for the protection of humans, pets and wildlife.

SUPER S 2-CYCLE, 4-CYCLE OIL & TREATMENTS



SUPER S SUPERFUEL 40:1 & 50:1

2-CYCLE OIL & FUEL is made with premium synthetic oil and high octane fuel to provide the performance and protection that outdoor power equipment users have been wanting. *(Also Available in Gallons!)*

SUPER S SUPERFUEL 4-CYCLE FUEL

is made with premium high octane fuel to provide the performance and protection that outdoor power equipment users have been wanting. Does not oxidize like typical gasoline. Super S Super Fuel contains no ethanol preventing downtime and repairs to your internal engine parts.

(Also Available in Gallons!)

PRODUCT	PACKAGING	PART #
40:1 2-Cycle Oil & Fuel	32oz	SUS S204
	Gal	SUS S205
50:1 2-Cycle Oil & Fuel	32oz	SUS S200
	Gal	SUS S201
4-Cycle Fuel Ready to Use	32oz	SUS S202
	Gal	SUS S203

SUPER S 2-CYCLE MIXING OIL

Super S Universal 2-Cycle Engine Oil is formulated with high quality base oils and additives designed to provide excellent anti-scuff, anti-wear, rust and corrosion protection. It burns clean and protects all bearings during high RPM use.



PRODUCT	PACKAGING	PART #
Univ. 2 Cycle	48/3.2 oz	SUS 81
	18/3.2 oz	SUS 81-18
	24/3.2 oz	SUS 81-6
	(4-6 PACK)	
Mixing Oil	24/8 oz	SUS 18
	4/16 oz	SUS 18-16C
	24/16 oz	SUS 18-16

Suitable for Use in:

- Air-cooled 2 cycle engines
- Engines calling for API TC performance
- Homelite
- Poulan
- Stihl
- Husqvarna
- Pioneer
- McCulloch

SUPER S SUPERSYN FULL SYNTHETIC UNIVERSAL 2-CYCLE ENGINE OIL

Super S SuperSyn Full Synthetic Universal 2-Cycle Engine Oil is a premium quality, high performance formulation of 100% synthetic base oils and a sophisticated additive package that meets or exceeds the performance, protection and service requirements for ashless, high flash 2-cycle engine oil for use in modern, high performance water cooled and air cooled two stroke cycle engines.



PRODUCT	PACKAGING	PART #
2-Cycle Engine Oil	12/3.2 oz	SUS 18-32

SUPER S SUPERSYN 2-CYCLE FULL SYNTHETIC ENGINE OIL WITH ETHANOL & FUEL STABILIZER

Super S SuperSyn 2-Cycle Full Synthetic Engine Oil with Ethanol & Fuel Stabilizer is formulated to protect engines and fuel systems against deposits, rust and corrosion. It is used to treat fuel for long term storage and can be used in gas cans, tanks, cars, trucks, boats, ATVs, snow mobiles, lawn mowers, snow blowers, chain saws, generators, and most 2- or 4-stroke gasoline-fueled engines.



PRODUCT	PACKAGING	PART #
2-Cycle w/Treatment	12/2.6 oz	SUS 18-26



SUPER S SUPERSYN SYNTHETIC OUTBOARD 2-CYCLE MARINE OIL

Super S SuperSyn Outboard 2-Cycle Marine Oil is a full synthetic, high-flash, ashless 2-cycle engine oil formulated to meet the requirements of most modern 2-cycle outboard and snowmobile high RPM engines. It is formulated for use in both premix and oil injected systems. SuperSyn Outboard is especially designed for exceptional performance in marine applications. It meets the warranty and service recommendations of most leading 2-cycle outboard motor manufacturers where TC-W3 oil is specified. SuperSyn Outboard is certified by the National Marine Manufacturers Association (NMMA) as an approved NMMA TC-W3 lubricant. It reduces wear, ring sticking, piston burning, spark plug fouling and port blocking.

PRODUCT	PACKAGING	PART #
Syn. Outboard	24/16 oz	SUS 277-16
2 Cycle	12/1 Qt	SUS 277
	3/1 Gal	SUS 277-3
	55 Gal	SUS 277-55

SUPER S TC-W3 PREMIUM OUTBOARD MULTI-PURPOSE 2-CYCLE OIL

A high performance, 2-cycle engine oil meeting or exceeding the warranty requirements of all leading manufacturers. 2-cycle products include chain saws, lawn mowers, motorcycles, string trimmers, as well as outboard engines made by Johnson/Evinrude, Mercury Marine, Yamaha, Suzuki, Nissan, Force/U.S. Marine, Mariner, Sears, and all other manufacturers requiring TC-W3 oil. It protects against piston scuffing and ring sticking as well as keeping spark plugs and exhaust parts clean. It is also suitable for use in oil injected systems requiring a TC-W3 oil.

PRODUCT	PACKAGING	PART #
TC-W3	24/16 oz	SUS 175
Outboard	12/1 Qt	SUS 176
	3/1 Gal	SUS 177-3
	55 Gal	SUS 179





SUPER S 2-CYCLE, 4-CYCLE OIL & TREATMENTS

SUPER S FUEL STABILIZER 2 & 4-CYCLE TREATMENT

Super S Fuel Stabilizer 2 & 4-Cycle Treatment utilizes a combination of additives to protect against deposits, rust and corrosion in engines, and protects against gum and varnish formation in fuel systems. It can be used in 2- and 4-cycle engines, such as automobiles, trucks, lawn mowers, chain saws, and generators. Super S Fuel Stabilizer helps keep stored fuel fresh and ready to use when needed.



PRODUCT	PACKAGING	PART #
Fuel Stabilizer	24/2.6 oz	SUS S182
	12/12 oz	SUS S183

SUPER S 4-STROKE LAWNMOWER OIL

Super S Heavy Duty 4-Stroke Lawnmower Oil is a premium formulation for use in all four stroke engines. Providing protection by lubricating, cooling, cleaning, and sealing internal moving parts. For use in outdoor power equipment such as lawnmowers, tractors, generators, tillers, pumps and edgers. Formulated to meet or exceed performance where API SJ is recommended.



PRODUCT	PACKAGING	PART #
SAE 30	24/20 oz	SUS 377
	8/48 oz	SUS 379
10W-30	12/1 Qt	SUS 378



SUPER S SNOW THROWER 4-CYCLE 5W-30 ENGINE OIL

Super S Snow Thrower 4-cycle 5W-30 Engine Oil is formulated for use in four cycle engines operating below 32°F, such as 2-stage snow throwers. Its formula protects the engine through lubricating, cooling, and sealing internal parts while allowing the snow thrower to operate in colder temperatures.

PRODUCT	PACKAGING	PART #
Snow Thrower 5W-30	12/1 Qt	SUS 380

SUPER S SYNTHETIC SNOW THROWER 4-CYCLE 5W-30 ENGINE OIL

Super S Synthetic Snow Thrower 4-Cycle SAE 5W-30 Engine Oil is a premium formulation for use in four-cycle engines in below freezing temperatures. It protects the engine by lubricating, cleaning deposits and sealing internal moving parts. It helps prevent wear and tear of the machinery. Pours smoothly in even the coldest of temperatures. For use in snow throwers, lawnmowers, tractors, and other outdoor power equipment. Formulated to meet or exceed performance where API SJ is recommended.



PRODUCT	PACKAGING	PART #
Synthetic Snow Thrower 5W-30	12/1 Qt	SUS 381

SUPER S 4-STROKE MOTORCYCLE/ATV ENGINE OIL

Super S 4-Stroke Motorcycle/ATV Engine Oil is designed specifically for High RPM and High Temperature applications to provide maximum performance and protection for 4-stroke engines used in Motorcycles, ATVs and similar vehicles. It meets or exceeds the warranty requirements for all 4-stroke engines which recommend JASO (Japanese Automotive Standards Organization) MA/MA2 and/or API (American Petroleum Institute) SG, SH, SJ or SL service classification.



PRODUCT	PACKAGING	PART #
20W-50	12/1 Qt	SUS 125
10W-40	12/1 Qt	SUS 127
EXPORT		
20W-50	12/0.8 L	SUS 129
10W-40	12/0.8 L	SUS 128



SUPER S ETHANOL TREATMENT

Super S Ethanol Treatment is a combination of additives designed to protect engines and fuel systems against deposits, rust and corrosion. Use for both immediate protection and long term storage on E-10, E-15 & E-85 fuels. Each bottle treats up to 21 Gallons. May be used with other Super S fuel additives.

PRODUCT	PACKAGING	PART #
Fuel Stabilizer	6/6 oz	SUS S110

SUPER S CHEMICALS



SUPER S FLAT TIRE FIX - CONE

Non-flammable, high pressure formulas helps to seal and inflate tires on passenger cars and light trucks.

Flat Tire Fix-Cone 12/12 oz SUS S325



SUPER S STARTING FLUID

Helps start stubborn engines fast in cold weather and minimizes wear on batteries. For gasoline or diesel engines.

Starting Fluid 12/10.7 oz SUS S328

SUPER S NON-FLAMMABLE BRAKE PARTS CLEANER

A powerful solvent blend that easily removes brake fluid, grease, oil and dirt from brake parts.

NF B/P Cleaner 12/18 oz SUS S107



SUPER S ENGINE DEGREASER

A water-based formula which combines the cleaning and degreasing of solvents, detergents and water into one powerful product that is low in VOCs.

Engine Degreaser 12/16 oz SUS S106



SUPER S NON-CHLORINATED BRAKE PARTS CLEANER

A concentrated solvent that easily removes brake fluid, grease, oily dirt and contaminants from lining, pads and drums, cylinders and springs without disassembling the unit.

NC B/P Cleaner 12/15 oz SUS S102



SUPER S FLAT TIRE FIX - HOSE

Non-flammable, high pressure formulas helps to seal and inflate tires on passenger cars and light trucks.

Flat Tire Fix-Hose 12/16 oz SUS S324



SUPER S AIR TOOL OIL & JACK OIL

Air Tool Oil Designed for the upkeep of rotary and piston-type air tools.

Jack Oil For hydraulic jacks, service jacks and refillable shock absorbers. It blends with all original fluids.

Air Tool Oil	12/12 oz	SUS S148
Jack Oil	12/12 oz	SUS S146
	12/1 Qt	SUS S145



SUPER S PENETRATING OIL

A multi-purpose product formulated to lubricate, penetrate, displace moisture and prevent corrosion. Loosens and frees rusty parts.

Penetrating Oil	12/11 oz	SUS S104
------------------------	----------	----------

SUPER S CHOKE/CARBURETOR CLEANER

A powerful combination of concentrated solvents formulated to remove dirt, gum and varnish deposits that tend to build up. Cleans carburetor, choke and PCV valve.

Choke/ Carb Cleaner	12/12 oz	SUS S101
--------------------------------	----------	----------



SUPER S DE-ICER

Removes frost and ice on contact. Ideal for windshield, windows, locks and mirrors. Harmless to car finishes.

De-Icer	12/12 oz	SUS S332
----------------	----------	----------



SUPER S TREATMENTS

SUPER S OCTANE BOOSTER

Restores power and removes deposits that cause hesitation and stalling.

Octane Booster	6/12 oz	SUS S118
----------------	---------	----------



SUPER S OIL TREATMENT

A high efficiency lubricant that improves engine performance.

It coats engine parts with a tough slippery film that resists heat and pressure. It keeps engine parts clean, improves viscosity, stops engine smoke and extends engine life. Helps stop oil burning.

Oil Treatment	6/15 oz	SUS S105
---------------	---------	----------



SUPER S FUEL INJECTOR TREATMENT

A super concentrated high strength detergent that provides enough cleaning power to restore carburetor and fuel injector to like new condition.

Fuel Injector Treatment	6/12 oz	SUS S113
-------------------------	---------	----------



SUPER S POWER STEERING SEALER

Stops and prevents leaks occurring in the power steering fluid reservoir.

Power Steering Sealer	6/12 oz	SUS S150
-----------------------	---------	----------



SUPER S MOTOR FLUSH

Frees sticky valves and rings in only 5 minutes.

Motor Flush	6/12 oz	SUS S147
	Drum	SUS 725
	Tote	SUS 726



SUPER S FUEL STABILIZER & ETHANOL TREATMENT

For All Gasoline Engines - Auto, Marine, Motorcycle, ATV, 2- & 4-cycle engines

- Treats fuel for Ethanol related problems
- Keeps fuel fresh and improves performance
- Prevents fuel deterioration
- Protects fuel system against gum, varnish, rust & corrosion
- Use to winterize fuel system and engine

Fuel Stabilizer/ Ethanol Treatment	6/12 oz	SUS S109
---------------------------------------	---------	----------



SUPER S TRANSMISSION SEALER

Conditions and seals automatic transmissions.

Transmission Sealer	6/12 oz	SUS S151
---------------------	---------	----------



SUPER S MOTOR SEALER

Stops oil leaks, including main seals.

Motor Sealer	6/12 oz	SUS S149
--------------	---------	----------



SUPER S DIESEL CONDITIONER & ANTI-GEL

Improves flow, disperses water and prevents gelling.

Diesel Conditioner	6/12 oz	SUS S156
-----------------------	---------	----------



SUPER S CARB & FUEL INJECTOR CLEANER

Restores lost power

- Increases gas mileage
- Reduces hesitation, rough idle and stalling

Carb/Injector Cleaner	6/12 oz	SUS S103
--------------------------	---------	----------



SUPER S GAS TREATMENT

A powerful cleaner that restores carburetors and fuel injectors to like new condition. It dissolves gum and varnish, protects against corrosion, prevents fuel freeze-up and is registered with the EPA in accordance with regulations for fuel and fuel additives.

Gas Treatment	6/12 oz	SUS S108
---------------	---------	----------



SUPER S LEAD SUBSTITUTE

A lead-free formula to protect engine values.

Lead Substitute	6/12 oz	SUS S154
-----------------	---------	----------



SUPER POWER

The Most Cleaning Power
You Can Fit In A Bottle



SUPER S CLEANING PRODUCTS

SUPER S SUPER POWER PURPLE DEGREASER

Super S Super Power Purple De-greaser Removes dirt, grease, oil and tar. The industrial strength formula may be diluted to get the right strength for a multitude of applications. This powerful cleaner de-greaser easily separates, entraps and removes grease, dirt, oil and grime from almost every type of surface. It dilutes up to 1:20 with water.



SUPER S SUPER POWER CAR WASH

- Formulated Especially For Hand Automobile Washing
- Utilizes Advanced Surfactant Technology
- Leaves a Great Shine
- Cuts through more dirt and grime
- Easily removes hard to clean bug residue
- Will never dull paint
- Great for all vehicles, especially those with exotic sensitive finishes
- Highly concentrated for greater economy

PRODUCT	PACKAGING	PART #
Super Power	6/1 Qt	SUS S115
	3/1 Gal	SUS S120
	3/2 Gal	SUS S122
	5 Gal	SUS S125
	55 Gal	SUS S155

PRODUCT	PACKAGING	PART #
Car Wash	6/1 Qt	SUS 750
	3/1 Gal	SUS 751
	5 Gal	SUS 760



SUPER S SUPER POWER TRUCK WASH

- Formulated Especially For Hand Automobile Washing
- Utilizes Advanced Surfactant Technology
- Leaves a Great Shine
- Cuts through more dirt and grime
- Easily removes hard to clean bug residue
- Will never dull paint
- Great for all vehicles, especially those with exotic sensitive finishes
- Highly concentrated for greater economy

PRODUCT	PACKAGING	PART #
Truck Wash	6/1 Qt	SUS 752
	3/1 Gal	SUS 753
	5 Gal	SUS 761



SUPER S SUPER POWER AUTO WASH & WAX

- Formulated Especially For Hand Automobile Washing
- Utilizes Advanced Surfactant Technology
- Leaves a Great Shine
- Cuts through more dirt and grime
- Easily removes hard to clean bug residue
- Will never dull paint
- Great for all vehicles, especially those with exotic sensitive finishes
- Highly concentrated for greater economy

PRODUCT	PACKAGING	PART #
Auto Wash & Wax	6/1 Qt	SUS 754
	3/1 Gal	SUS 755
	5 Gal	SUS 762



SUPER S SUPER POWER TIRE SHINE

Super Power Tire Shine provides exceptional cleaning to tires, resulting in a shiny, black new tire look. Super S Tire Shine was formulated to provide an extra layer of protection allowing extended shine.

PRODUCT	PACKAGING	PART #
Tire Shine	6/1 Qt	SUS 758
	4/1 Gal	SUS 759
	5 Gal	SUS 764



SUPER S SUPER POWER REAL WHITE

Super Power Real White is designed to clean and whiten tire white walls and lettering. Its formula helps restore the white luster of the white walls, and allows them to look their best over an extended period of time.

PRODUCT	PACKAGING	PART #
Real White	6/1 Qt	SUS 756
	4/1 Gal	SUS 757
	5 Gal	SUS 763

SUPER S CLEANING PRODUCTS

SEA-WASH® 11 CLEANER & DISPERSANT

SEA-WASH® 11 Cleaner & Dispersant is a revolutionary new concept in chemical cleaners for all phases of cleaning, dispersing, emulsifying, and herding of petroleum-based products. SEA-WASH® 11 is an industrial strength, highly concentrated, environmental safe cleaner. The product cleans mold, mildew, water-line scum, creosote, carbon dust, drilling muds, and cosmoline.



PRODUCT	PACKAGING	PART #
Sea-Wash 11	6/1 Qt	SWA.DGRSR.0032.022
	4/1 Gal	SWA.DGRSR.0001.003
	5 Gal	SWA.DGRSR.1005.013
	55 Gal	SWA.DGRSR.1055.014

SEA-WASH® 8 NON-FLAMMABLE NEUTRAL pH7 CLEANER

SEA-WASH® 8 NON-FLAMMABLE Neutral pH7 Cleaner is our most recently developed aqueous based cleaning solution designed specifically for use in metal parts cleaning equipment. This formulation safely and efficiently cleans dirt, mold, algae, oil, grease, and other soils from the surface of all metals, plastics, and other materials. Although metal will be exposed to the elements after the paint is removed, SEA-WASH 8® will prevent the metal from rusting. Aqueous based parts cleaning solutions are commonly heated to enhance cleaning ability, but SEA-WASH 8® has been designed to clean efficiently with or without heating. SEA-WASH 8® contributes to an inexpensive conversion from solvent to aqueous cleaning solution. SEA-WASH 8® is in the ph-7 range and will stay ph-7 range when diluted with water. SEA-WASH 8® is biodegradable, non-toxic, non-hazardous, and non-flammable.

PRODUCT	PACKAGING	PART #
Sea-Wash 8	12/1 Qt	SWA.CLEAN.0032.016
	4/1 Gal	SWA.CLEAN.0001.009
	5 Gal	SWA.CLEAN.1005.010
	55 Gal	SWA.CLEAN.1055.015



SEA-WASH® CITRUS CLEANER

SEA-WASH® Citrus Cleaner is a water based citrus cleaner and degreaser designed for use on most floors and other washable surfaces. It is a neutral so it will not dull the floor finish. Not for use in food-processing areas. It is a low foaming product and may be used in buckets, spray bottles and automatic scrubbing machines. It removes most types of particulate and oily soils.

PRODUCT	PACKAGING	PART #
Sea-Wash Citrus	6/1 Qt	SWA.CLEAN.0032.020
	4/1 Gal	SWA.CLEAN.0001.021





SEA-WASH® WC-10 CLEANER & DISPERSANT

SEA-WASH® WC-10 Cleaner & Dispersant is a revolutionary new concept in chemical cleaners for all phases of cleaning, dispersing, emulsifying, and herding of petroleum-based products. SEA-WASH® WC-10 Cleaner & Dispersant is designed to be an economically and environmentally safe cleaner in today's market. The product cleans mold, mildew, water-line scum, creosote, carbon dust, drilling muds, and cosmoline.



PRODUCT	PACKAGING	PART #
Sea-Wash WC-10	6/1 Qt	SWA.CLEAN.0032.024
	4/1 Gal	SWA.CLEAN.0001.011
	5 Gal	SWA.CLEAN.1005.012
	55 Gal	SWA.CLEAN.1055.004



SEA-WASH® SUPER 7 NEUTRAL pH - 100% CONCENTRATE

SEA-WASH® SUPER 7 Neutral pH- 100% Concentrate is a revolutionary new concept in chemical technology in today's chemical market. SEA-WASH® Super 7 is 100% concentrate product that has a neutral pH allowing to be used on sensitive surfaces. This concentrate can be diluted to your cleaning needs. SEA-WASH® Super 7 is designed as an all-purpose cleaner and used in floor cleaning equipment.

For scrubbing machines, dilute 399:1 For general purpose carpet and floor cleaning, dilute 19:1.

PRODUCT	PACKAGING	PART #
Sea-Wash Super 7	12/1Qt	SWA.CLEAN.0032.019
	5 Gal	SWA.CLEAN.1005.008
	55 Gal	SWA.CLEAN.1055.017

SEA-WASH® 2000 MULTI-PURPOSE ODOR REMOVER & CLEANER NEUTRAL pH- 100% CONCENTRATE

SEA-WASH® 2000 Multi-Purpose Odor Remover & Cleaner Neutral pH - 100% Concentrate is an alternative to hazardous alkaline and butyl-type cleaners. SeaWash 2000 is a highly concentrated, industrial strength cleaner that combines proven cost-effectiveness with unsurpassed cleaning ability. SeaWash 2000 is a non-hazardous, environmentally friendly cleaner that permanently kills ALL odors as it cleans

For carpet machines, dilute 100:1. For general purpose carpet and floor cleaning, dilute 19:1.



PRODUCT	PACKAGING	PART #
Sea-Wash 2000	5 Gal	SWA.CLEAN.1005.006
	55 Gal	SWA.CLEAN.1055.018

SEA-WASH® SEA-CLEAR GLASS CLEANER

SEA-WASH® Sea-Clear Glass Cleaner is a streak-free solution for glass cleaning. This product is designed for use on windows, mirrors, tile, plastic, vinyl, aluminum, sealed granite and much, much more. Not for use in food-processing areas.

PRODUCT	PACKAGING	PART #
Sea-Wash Sea-Clear	6/1 Qt	SWA.CLEAN.0032.026

SUPER S CLEANING PRODUCTS



SUPER S ALUMINUM BRIGHTNER

SUPER S ALUMINUM BRIGHTNER cleans and brightens aluminum, stainless steel, copper, brass and non-metals. In just seconds the industrial strength formula dissolves grease, grime and road film.

PRODUCT	PACKAGING	PART #
Aluminum Brightner	4/1 Gal	SUS S408
	5 Gal	SUS S409

SUPER S WINDSHIELD WASHER CONCENTRATE

Super S Windshield Washer Concentrate is a powerful windshield washer fluid that can be mixed to desired concentration.



PRODUCT	PACKAGING	PART #
WW Conc.	12/12 oz	SUS S112
	24/16 oz	SUS S112-16
	55 Gal	SUS S112-55



SUPER S EXTREME WINTER WINDSHIELD WASHER FLUID - 20°F

- Provides freeze protection to -20°F
- Helps remove frost, snow and ice in sub- zero temperatures
- Keeps windshields clean
- Improves visibility
- Does not harm paint, rubber or plastic
- Ideal for use in winter
- Dissolves road film and bug splatter

PRODUCT	PACKAGING	PART #
Extreme Winter	6/1 Gal	SUS 28-20
	55 Gal	SUS 28-20-55

SUPER S WINDSHIELD WASHER FLUID +32°

- All season windshield washer solvent
- Dissolves road film and bug splatter
- Keeps windshields clean
- Improves visibility
- Does not harm paint, rubber or plastic
- Ideal for use in winter +32° or summer



PRODUCT	PACKAGING	PART #
+32°	6/1 Gal	SUS 28-32B



SUPER S SUMMER WINDSHIELD WASHER FLUID +21°F

- Summer season windshield washer solvent
- Dissolves road film and bug splatter
- Keeps windshields clean
- Improves visibility
- Does not harm paint, rubber or plastic



PRODUCT	PACKAGING	PART #
Summer	6/1 Gal	SUS 28-21



SUPER S WINTER WINDSHIELD WASHER FLUID 0°F

- Provides freeze protection to 0°F
- Helps remove frost, snow and ice in sub- zero temperatures
- Keeps windshields clean
- Improves visibility
- Does not harm paint, rubber or plastic
- Ideal for use in winter
- Dissolves road film and bug splatter

PRODUCT	PACKAGING	PART #
Winter	6/1 Gal	SUS 28

SUPER S BUG WASH WINDSHIELD WASHER FLUID +32°F

- All season windshield washer solvent
- Dissolves road film and bug splatter
- Keeps windshields clean
- Improves visibility
- Does not harm paint, rubber or plastic
- Ideal for use in winter or summer



PRODUCT	PACKAGING	PART #
Bug Wash	6/1 Gal	SUS 28-32

SUPER S SPECIALTY FLUIDS

SUPER S DEF

Super S DEF is an American Petroleum Institute (API) certified Diesel Exhaust Fluid that meets international standards for purity and composition for use as a Nitrogen Oxide (NOx) reducing agent in all Selective Catalytic Reduction (SCR) Emission Control systems. DEF is a reducing agent which is injected into the hot exhaust gas stream downstream of the diesel particulate filter. It vaporizes in the hot exhaust gas to form ammonia and carbon dioxide which then reacts with the SCR system catalytic converter and the NOx (oxides of nitrogen) in the exhaust, converting the harmful NOx emissions to harmless nitrogen and water. DEF meets ISO 22241-2 specifications and meets all applicable standards and specifications for use in all SCR systems. Non-Toxic, Non-Flammable, Non-Polluting.



PRODUCT	PACKAGING	PART #
DEF	3/1 Gal	SUS 160-3
	3/2 Gal	SUS 160-2
	2/2.5 Gal	SUS 160-2.5
	55 Gal	SUS 160-55
	275 Gal	SUS 160 TOTE



SUPER S BAR & CHAIN OIL

Super S Bar & Chain Oil is a premium bar and chain lubricant designed to provide protection under all operating conditions. It is a combination of highly refined, thermally stable base stocks with natural solvency characteristics, and a non-water soluble "tackiness" agent resulting in a unique product that provides exceptional protection to the bar, chain, and sprockets. High Tac - No Sling • Reduces Throw Off • Increases Chain Life

PRODUCT	PACKAGING	PART #
Bar & Chain	6/1 Qt	SUS 90-6
	3/1 Gal	SUS 20-3
	55 Gal	SUS 19
Chain Lube	55 Gal	SUS 191
No Tac		

SUPER S SUPERTAC EXTREME TAC BAR & CHAIN OIL

Super S SuperTac Bar & Chain has all the great protection exhibited by Super S Bar & Chain along with extra tackifier which provides for a more viscous product. It meets or exceeds the needs of residential, commercial and industrial chain saws, as well as, the needs of the forest product industry under the most adverse operating conditions.



PRODUCT	PACKAGING	PART #
SuperTac Bar & Chain	3/1 Gal	SUS 20X



SUPER S PREMIUM POWER STEERING FLUID

Super S Premium Power Steering Fluid helps maintain efficiency, performance and the condition of power steering units.

Super S Premium Power Steering Fluid is blended with a high quality base oil and a balanced additive package to provide oxidation stability, anti-foam, and seal/hose compatibility. Super S Premium Power Steering Fluid contains a unique friction modifier additive that has been shown to reduce power steering pump noise (squeal). Recommended for complete fluid replacement in passenger cars, including Honda and Acura, and light trucks.

PRODUCT	PACKAGING	PART #
Premium Power Steering Fluid	12/12 oz	SUS 429L
	12/1 Qt	SUS 430



SUPER S POWER STEERING FLUID

Super S Power Steering Fluid is a carefully blended fluid providing excellent performance. Super S Power Steering Fluid contains anti-wear additives to reduce wear on pistons, bearings and valves in modern power steering systems. Recommended for top off in passenger cars and light trucks.



PRODUCT	PACKAGING	PART #
Power Steering Fluid	12/12 oz	SUS 29L
	24/12 oz	SUS 29-24
	12/1 Qt	SUS 30
	3/1 Gal	SUS 129-3
	55 Gal	SUS 29-55

SUPER S DOT 3 BRAKE FLUID

Super S DOT 3 Brake Fluid is a fully approved, DOT 3 type motor vehicle brake fluid suitable for use in all vehicles where DOT 3 fluids are recommended. It is suitable for both disc and drum brake systems.

Meets or exceeds standards #116 SAE J1703 and ISO 4925.



PRODUCT	PACKAGING	PART #
DOT 3	12/12 oz	SUS 31
	24/12 oz	SUS 31-24
	12/1 Qt	SUS 32
	3/1 Gal	SUS 33-3
	5 Gal	SUS 34
	55 Gal	SUS 31-55



DOT 4 BRAKE FLUID

Super S DOT 4 Brake Fluid surpasses specifications SAE J1704 and fully complies with Federal Motor Vehicle Safety Standard No. 116. Super S Heavy Duty DOT 4 Brake Fluid is ideal for all types of automotive braking systems, disc or drum brakes. Operates efficiently under all weather conditions.

PRODUCT	PACKAGING	PART #
DOT 4	12/12 oz	SUS 431
	12/1 Qt	SUS 432
	55 Gal	SUS 433

SUPER S DOT 5 BRAKE FLUID

Super S DOT 5 Brake Fluid eliminates brake fade and protects from corrosion. It exhibits outstanding high and low temperature properties for reliable braking performance.



PRODUCT	PACKAGING	PART #
DOT 5	12/12 oz	SUS 531

SUPER S SPECIALTY FLUIDS



SUPER S SOLVENT 140

Super S Solvent 140 is a high flash point solvent used for general-purpose cleaning. With proper agitation in conventional cleaning equipment, it will effectively remove grease, lubricating oils and metal working fluids from metal surfaces. It replaces common low flash point solvents such as Stoddard solvents and mineral spirits. It is compatible with most metals and plastics.

PRODUCT	PACKAGING	PART #
Solvent 140	5 Gal	SUS 188
	55 Gal	SUS 189



SUPER S MINERAL SPIRITS

Super S Mineral Spirits satisfy the broad range of applications for Stoddard solvents and are refined to low odor levels. Super S Mineral Spirits meet the general requirements for mineral spirits with solvent power and boiling range typical of a Stoddard solvent.

PRODUCT	PACKAGING	PART #
Mineral Spirits	5 Gal	SUS 4
	55 Gal	SUS 5



SUPER S K-1 KEROSENE

Super S K-1 Kerosene is a fuel K-1 kerosene ideally suited for use in kerosene burning heaters, lanterns and stoves. It meets or exceeds ASTM D 3699 standard for low-sulfur kerosene. It is also good for cleaning and removing grease, tar and oil

PRODUCT	PACKAGING	PART #
K-1 Kerosene	5 Gal	SUS 186
	55 Gal	SUS 187



SUPER S OIL STABILIZER

Super S Heavy Duty Oil Stabilizer when added to engine oil, is a high efficiency lubricant that will improve engine performance.

- Coats engine parts with a tough, slippery film that resists heat and pressure
- Keeps vital engine parts clean
- Improves Oil Viscosity
- Extends engine life
- Stops engine smoking
- Dramatically reduces exhaust smoke

PRODUCT	PACKAGING	PART #
Oil Stabilizer	12/1 Qt	SUS S180
	4/1 Gal	SUS S181



SUPER S SUPERDRY INDUSTRIAL ABSORBENT

Super S SuperDry is a premium grade industrial absorbent product made of "Diatomite" (not clay). It works like a sponge. SuperDry absorbs oil, transmission fluid, brake fluid, radiator coolant, and more. SuperDry is used for control and containment of spills in the garage and workshop. It is easy to apply, lightweight, non-toxic, non-combustible and safe for landfills.

PRODUCT	PACKAGING	PART #
Super Dry	25 lb	SUS 46



SUPER S CHARCOAL LIGHTER FLUID

Super S Charcoal Lighter Fluid is a high quality fluid formulated for fast ignition. It is a low soot, no odor, no taste formula, excellent for grilling and igniting a fire in a controlled environment. Super S Charcoal Lighter Fluid complies with South Coast Air Quality Management District Rule 1174 Ref. C56 or Ref. C65.

PRODUCT	PACKAGING	PART #
Charcoal Lighter Fluid	12/1 Qt	SUS S301
	12/16 oz	SUS S301-16

SUPER S CUSTOM PLUS SYNTHETIC BLEND MOTOR OIL

API SL & API SJ



CUSTOM PLUS™ SYNTHETIC BLEND MOTOR OIL

Custom Plus™ Motor Oils feature premium base oils in formulation with proven high-quality anti-wear additives. This oil is designed for use in gasoline engines, combining versatility, heavy-duty engine protection and cost effectiveness into one motor oil. It is formulated with high levels of dispersant and detergent additives that effectively control sludge and varnish to help prevent corrosion, wear and deposits. Custom Plus Motor Oils are excellent for all-season use in automotive gasoline engines. Custom Plus Motor Oils SAE 5W-20 and 5W-30 show acceptable performance where API SL is recommended. Custom Plus Motor Oils 10W-30, 10W-40 and 20W-50 show acceptable performance where API SJ is recommended.

PRODUCT	PACKAGING	PART #
5W-20	12/1 Qt	CUS 98201
5W-30	12/1 Qt	CUS 98202
10W-30	12/1 Qt	CUS 98203
10W-40	12/1 Qt	CUS 98204
	55 Gal	CUS 204-55
20W-50	12/1 Qt	CUS 98205
	5 Gal	CUS 205-5
	55 Gal	CUS 205-55

CUSTOM PLUS™ MULTI-PURPOSE D/M ATF

Custom Plus™ Multi-Purpose D/M ATF is designed for new generation, electronically controlled transmissions in cars and trucks including pre-2006 General Motors as well as Ford, Chrysler and most foreign manufacturers' transmissions where DEXRON® III H or MERCON® or previous specifications are recommended. It may also be used in many torque converters, and power shift and hydrostatic transmissions; and in some hydraulic systems and compressors where excellent low temperature flow and anti-wear properties are required.



PRODUCT	PACKAGING	PART #
D/M	12/1 Qt	CUS 98209
	3/1 Gal	CUS 98208
	55 Gal	CUS 209-55

SUPER S CUSTOM PLUS TURBO HD SYNTHETIC BLEND MOTOR OIL

API CI-4 PLUS/SL

CUSTOM PLUS™ TURBO HD SYNTHETIC BLEND MOTOR OIL

Custom Plus™ TURBO HD Synthetic Blend Motor Oil is recommended for all types of service in truck and automotive diesel and gasoline engines, including those with diesel particulate filters. It provides excellent engine protection, extends engine life and controls oil consumption. This product has been extensively tested and performs well in automotive service applications and is compatible with API approved engine oils. Custom Plus™ TURBO HD Synthetic Blend Motor Oil show exceptable performance where API CI-4 Plus, CH-4/SL is recommended as well as the performance requirements of Mack EO-M Premium Plus, ACEA E3-96, Navistar, ACEA E5-99, Volvo VDS-2, Cummins CES 20078, Global DHD-1, DB 228.3, and MB 228.3.



PRODUCT	PACKAGING	PART #
15W-40	12/1 Qt	CUS 98303
	3/1 Gal	CUS 98304
	5 Gal	CUS 98315
	55 Gal	CUS 98316
	BULK	CUS 98327

PRODUCT	PACKAGING	PART #
20W-50	12/1 Qt	CUS 98305
	3/1 Gal	CUS 98306
	5 Gal	CUS 98317
	55 Gal	CUS 98318
	BULK	CUS 98328

SUPER S CUSTOM PLUS TURBO HD SYNTHETIC BLEND MOTOR OIL

API CH-4 /SG

CUSTOM PLUS™ TURBO HD SYNTHETIC BLEND MOTOR OIL

Custom Plus™ TURBO HD Synthetic Blend Motor Oil is recommended for all types of service in truck and automotive diesel and gasoline engines, including those with diesel particulate filters. It provides excellent engine protection, extends engine life and controls oil consumption. This product has been extensively tested and performs well in automotive service applications and is compatible with API approved engine oils. Custom Plus™ TURBO HD Synthetic Blend Motor Oil show acceptable performance where API CH-4/SGJ is recommended.



PRODUCT	PACKAGING	PART #
15W-40	12/1 Qt	CUS 98307
	3/1 Gal	CUS 98308
	5 Gal	CUS 98319
	55 Gal	CUS 98320
	BULK	CUS 98329

PRODUCT	PACKAGING	PART #
20W-50	12/1 Qt	CUS 98309
	3/1 Gal	CUS 98310
	5 Gal	CUS 98321
	55 Gal	CUS 98322
	BULK	CUS 98330

PRODUCT	PACKAGING	PART #
25W-50	12/1 Qt	CUS 98311
	3/1 Gal	CUS 98312
	5 Gal	CUS 98323
	55 Gal	CUS 98324
	BULK	CUS 98331

PRODUCT	PACKAGING	PART #
25W-60	12/1 Qt	CUS 98313
	3/1 Gal	CUS 98314
	5 Gal	CUS 98325
	55 Gal	CUS 98326
	BULK	CUS 98332

SUPER S CUSTOM PLUS NON-DETERGENT MOTOR OIL



CUSTOM PLUS™ NON-DETERGENT MOTOR OIL

Custom Plus™ Non-Detergent SAE 40 Motor Oil is manufactured with high quality base oils and fortified with an anti-foaming additive for extra lubrication at an economical price. Custom Plus™ ND Motor Oil meets or exceeds car manufacturers' warranty requirements where an API Service SB motor oil is recommended. It provides economical lubrication for older cars in light duty service which do not require high performance oils. Always consult your owner's manual for proper recommendations.

PRODUCT	PACKAGING	PART #
ND 40	12/1 Qt	CUS 98336
	3/1 Gal	CUS 98337
ND 50	12/1 Qt	CUS 98334
	3/1 Gal	CUS 98335

SUPER S CUSTOM PLUS SYNTHETIC GEAR OIL

CUSTOM PLUS™ SYNTHETIC GEAR OIL

Custom Plus™ Synthetic Gear Oil are full synthetic heavy duty gear lubricants that provide extended drain service, improved fuel efficiency, and are designed to meet the service demands of automobile, light truck and the latest heavy duty manual transmissions, axles and drive units that call for API GL-5/MT-1. Custom Plus™ 75W-90 and 75W-140 Gear Oils are formulated for extreme pressure, severe service, and is thermally stable with a low pour point for all season use.

PRODUCT	PACKAGING	PART #
75W-90	35 lb	CUS 98004
	110 lb	CUS 98005
	400 lb	CUS 98006
75W-140	35 lb	CUS 98007
	110 lb	CUS.75W140.1110.118
	400 lb	CUS 98008

CUSTOM PLUS™ 80W-140 SYNTHETIC GEAR OIL

Custom Plus™ 80W-140 Synthetic Gear Oil is a full synthetic heavy duty gear lubricant developed for heavy duty differentials calling for GL-5 service. Applications also include rear wheel bearings and universal joints, automobile, light and heavy duty truck transfer cases, heavy construction and farm equipment, industrial gear units and manual transmissions.

PRODUCT	PACKAGING	PART #
80W-140	35 lb	CUS 98009
	110 lb	CUS 98010

SUPER S LICENSES & APPROVALS



LICENSED PRODUCT	VISCOSITY	LICENSE ORGANIZATION	LICENSE NUMBER	DESIGNATION
MULTI FLO HIGH MILEAGE	5W-20	API	2212	SN/RC/GF-5
MULTI FLO HIGH MILEAGE	5W-30	API	2212	SN/RC/GF-5
MULTI FLO HIGH MILEAGE	10W-30	API	2212	SN/RC/GF-5
MULTI FLO HIGH MILEAGE	10W-40	API	2212	SN
SUPER S DEXOS1	5W-30	API	2212	SN/RC/GF-5
SUPER S FG 2000	10W-30	API	2212	CK-4
SUPER S FG 2000	15W-40	API	2212	CK-4
SUPER S FG 2000	15W-40	API	2212	SN/CJ-4
SUPER S FG 2000	15W-40	API	2212	CJ-4, CI-4/SM,CI-4+
SUPER S FG 2000	15W-40	API	2212	CI-4/SL
SUPER S MULTI FLO	10W-40	API	2212	SM
SUPER S MULTI FLO	20W-50	API	2212	SM
SUPER S MULTI FLO	20W-50	API	2212	SN
SUPER S MULTI FLO	10W-40	API	2212	SN
SUPER S MULTI FLO HD	40	API	2212	SN
SUPER S MULTI FLO HD	30	API	2212	SN
SUPER S MULTI FLO SYNTHETIC BLEND	10W-30	API	2212	SN/RC/GF-5
SUPER S MULTI FLO SYNTHETIC BLEND	5W-30	API	2212	SN/RC/GF-5
SUPER S MULTI FLO SYNTHETIC BLEND	5W-20	API	2212	SN/RC/GF-5
SUPER S MULTI FLO SYNTHETIC BLEND	5W-20	API	2212	SN/ENERGY CONSERVING
SUPER S MULTI FLO SYNTHETIC BLEND	5W-30	API	2212	SN/ENERGY CONSERVING
SUPER S MULTI FLO SYNTHETIC BLEND	10W-30	API	2212	SN/ENERGY CONSERVING
SUPER S SUPERSYN	0W-20	API	2212	SN/ENERGY CONSERVING
SUPER S SUPERSYN	5W-30	API	2212	SN/RC/GF-5
SUPER S SUPERSYN	5W-20	API	2212	SN/RC/GF-5
SUPER S SUPERSYN	10W-30	API	2212	SN/RC/GF-5
SUPER S SUPERSYN	5W-40	API	2212	SN
SUPER S SUPERSYN	5W-20	API	2212	SM/ENERGY CONSERVING
SUPER S SUPERSYN	5W-30	API	2212	SM/ENERGY CONSERVING
SUPER S SUPERSYN	10W-30	API	2212	SM/ENERGY CONSERVING
SUPER S SUPERSYN	0W-20	API	2212	SN/RC/GF-5
SUPER S SUPERSYN	0W-40	API	2212	SN/RC/GF-5
SUPER S SYNBLEND	5W-30	API	2212	SN/RC/GF-5
SUPER S SYNBLEND	5W-20	API	2212	SN/RC/GF-5
SUPER S SYNBLEND	10W-30	API	2212	SN/RC/GF-5
SUPER S SYNBLEND	10W-30	API	2212	SM/ENERGY CONSERVING
SUPER S SYNBLEND	5W-30	API	2212	SM/ENERGY CONSERVING
SUPER S SYNBLEND	5W-20	API	2212	SM/ENERGY CONSERVING
SUPERSYN	5W-40	API	2212	SN
SUPERSYNS HD FLEET	15W-40	API	2212	CJ-4,CI-4/SM
SUPER S FULL SYNTHETIC MOTOR OIL	0W-20	GM	GB1E0517016	DEXOS1 GLOBAL
SUPER S FULL SYNTHETIC MOTOR OIL	5W-20	GM	GB1D0711016	DEXOS1 GLOBAL
SUPER S FULL SYNTHETIC MOTOR OIL	5W-30	GM	GB1A0924016	DEXOS1 GLOBAL
SUPER S SEMI-SYNTHETIC MOTOR OIL	5W-20	GM	GB1E0511016	DEXOS1 GLOBAL
SUPER S SEMI-SYNTHETIC MOTOR OIL	5W-30	GM	GB1F0423016	DEXOS1 GLOBAL
SUPER S DEXRON VI	ATF	GM	J-60153	DEXRON VI
SUPER S MULTI-FLO	5W-20	GM	GM6094M	
SUPER S MULTI-FLO	5W-30	GM	GM6094M	
SUPER S MULTI-FLO	10W-30	GM	GM6094M	
SUPER S SUPERSYN	5W-20	GM	GM6094M	
SUPER S SUPERSYN	5W-30	GM	GM6094M	
SUPER S SUPERSYN	10W-30	GM	GM6094M	
SUPER S FG-2000	15W-40	CAT ECF-2		
SUPER S FG-2000	15W-40	CAT ECF-3		
SUPER S FG-2000	15W-40	CUMMINS 20081		
SUPER S FG-2000	15W-40	DDC 93K218		
SUPER S FG-2000	15W-40	VOLVO VDS-4	417-0001-12-096	
SUPER S FG-2000	15W-40	MACK EO-0	417-0001-12-096	
SUPER S FG-2000	15W-40	RENAULT VI RLD-3	417-0001-12-096	
SUPER S TCW3	PREMIUM OUTBOARD OIL	NMMA	RL-31350	
SUPER S TCW3 SUPERSYN	2-CYCLE MARINE OIL	N MMA	RL-00453L	



**Protect engines against
oil-related problems
for **300,000 miles**
or **10 years**,
whichever comes first.***

Super S
SATISFACTION
ENGINE PROTECTION PLAN

PROTECTED

The **FREE 300,000 Mile/10 Year Limited Engine Protection Plan** is a maintenance plan for customers who exclusively change oil with Super S Motor Oil every 4 months or 5,000 miles.

Register online
at **www.SmittyInc.net**

Click the Super S Engine Protection Plan logo and complete the application including your Super S Authorized Installer Number. Each qualified applicant will receive confirmation of their enrollment in the Super S Engine Protection Program.

To Qualify:

- Vehicle is maintained with Super S engine oil every 4 months or 5,000 miles
- Vehicle has been manufactured within the last 48 months.
- Vehicle has been owned or leased less than 18 months by current owner.
- Vehicle has 75,000 miles or less.
- Vehicle has been regularly serviced in accordance with owner's manual specifications (severe driving conditions).

The oil filter and air cleaner elements must be maintained as recommended by the vehicle manufacturer. You need to take great care of your engine to make it last for 10 years or 300,000 miles and Super S Motor Oil will help you do just that.

* See the Super S Engine Protection Limited Warranty Statement for complete coverage online at www.SmittyInc.net.



The Following Super S products Qualify for the Super S Engine Protection Plan

Super S SuperSyn Full Synthetic Motor Oil
Super S Euro SuperSyn Full Synthetic Motor Oil
Super S Multi-Flo Synthetic Blend Motor Oil
Super S dexos1™ Premium Motor Oil



QUALITY ASSURANCE & CONSUMER CARE PROGRAM

At Smitty's Supply Inc. it is our mission to provide quality products and dependable service to our customers at competitive prices. We strive for continuous improvement in all that we do and challenge ourselves to provide a full and complete line of products and service advantages above our competition.

We developed the Super S Satisfaction program and Lubricant Warranty to guarantee the quality of the fluids and the packaging on all of our products.

QUALITY CONTROL AT ALL PRODUCTION STAGES

We assign quality control managers at all stages of production for inspection at specified intervals to insure products are not only meeting customers satisfaction, but meeting Smitty's Supply's set rigorous standards which often times exceed industry specifications.

Our state-of-the art laboratory provides an integrated solution for quality assurance and process control utilizing modern equipment such as:

- Cannon Auto Viscometers
- Cannon Cold Cranking Simulator
- Brookfield Low Temperature Viscometer

Products are tested for the following quality criteria at all stages of production. Samples are taken from the top & bottom of vessels and at set intervals on production lines for thorough testing. Certificate of Analysis is issued for approved product, reviewed and signed by laboratory personnel and logged in the database.

- Kinematic viscosities
- Elemental quantities
- Elemental contamination
- Foreign contamination (water, etc...)



Smitty's Supply is proud to be an ISO 9001:2015 facility, which strives to meet the quality needs of all our customers.

- We continually improve our processes on all levels and maintain a full-time, round-the-clock staff of highly trained Quality Assurance personnel.
- We perform daily equipment calibrations and maintain monthly metric systems to measure predetermined aspects of our business.
- Semi-annual internal audits are conducted of our entire facility and associated documentation to ensure we are meeting our annual business and quality goals.



Smitty's Supply Inc. ISO 9001:2015 Certified Laboratory Test Methods

TEST METHOD	ASTM METHOD
Nitrogen	ASTM D4629
Nitrogen	ASTM D5762
Viscosity @ 100°C	ASTM D7279
Viscosity @ 40°C	ASTM D7279
Viscosity Index	ASTM D2270
Cold Crank (Viscosity, cP)	ASTM D5293
Brookfield Viscosity (Viscosity, cP)	ASTM D2983
NOACK Volatility (Evaporation, % Loss)	ASTM D5800
X-Ray (Elemental Analysis, ppm)	ASTM D6481
Specific Gravity	ASTM D4052
Pour Point	ASTM D5949
ICP (Elemental Analysis, ppm)	ASTM D4951
Flash Point (Cleveland Open Cup)	ASTM D92
Flash Point (Pensky Martens Closed Cup)	ASTM D93
Color	ASTM D1500
Particle Count	ASTM D7647
Demulsibility (Water Separability)	ASTM D1401
MRV (Yield Stress/ Apparent Viscosity)	ASTM D4684
High Temperature/High Shear (HTHS) (Meets SAE J300 Specification)	ASTM D5481
Karl Fisher	ASTM E203

Download Our New App:



1-800-256-7575

Smittys Supply, Inc.
63415 Highway 51 North
Roseland, LA 70456



SMITTYSINC.NET

Rev June 2017