

**Landscape Lighting - Low Voltage Type UF**
**-20°C to +60°C, 150 Volts Rated,**


- APPLICATIONS**
- Outdoor Accent Lighting
  - Landscape Lighting
  - Security Lighting
  - Sunlight Resistant
  - Direct Burial
- CONSTRUCTION**
- Two fully annealed bare stranded copper conductors
  - Insulation/Jacket: Premium-grade PVC -20°C to +60°C
  - Final assembly: Insulated/Jacketed conductors duplexed in a flat construction for easy tear-down during installation
  - Color: Black is standard Available in white or brown, but subject to minimum order quantity
- STANDARDS**
- Meets or exceeds UL and cUL standards
- FEATURES**
- Approved for Outdoor Use (Sunlight Resistant)  
Suitable for Direct Burial Stranded Copper Conductor Black PVC Insulation/Jacket



Stock #	DESCRIPTION	AWG	#COND	NOM. OVERALL DIA. (Inches)	WEIGHT (Lb./Mft)
552131	LNDSKP LGHT 16/2 STR CU BK	16	2	0.156 × 0.307	41
552132	LNDSKP LGHT 14/2 STR CU BK	14	2	0.166 × 0.341	55
552134	LNDSKP LGHT 12/2 STR CU BK	12	2	0.186 × 0.37	69
552135	LNDSKP LGHT 10/2 STR CU BK	10	2	0.205 × 0.405	107
552136	LNDSKP LGHT 8/2 STR CU BK	8	2	0.27 × 0.53	163